



Mainstay™/MC

Floor Finish



High-performance finish for infrequent maintenance

Effective

- Versatile finish provides great durability
- Excellent mark, scuff and scratch resistance

Easy to Use

- Responds to spray buff maintenance and to UHS burnishings

Designed For

- Healthcare
 - Education
 - Lodging
-

Use Overview

Mainstay™/MC Floor Finish provides great durability excellent mark, scuff and scratch resistance and responds to spray buff maintenance and to UHS burnishings.

Preparation

- Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- Before the first application of Mainstay™/MC Floor Finish, remove all old finish with any Diversey stripper.

Coating

- Apply 3–4 medium coats of Mainstay™/MC Floor Finish with a clean finish mop. Let dry to the touch between coats (about 30 minutes).
- On porous resilient or stone floors, seal first with 2 coats of the recommended Diversey sealer.

Maintenance

- For daily cleaning dust mop or sweep.
- Then wet clean with recommended Diversey cleaner in an autoscrubber or with a damp mop.



Burnishing

- To renew gloss, spray buff as needed with recommended Diversey spray buff, a red or beige pad and a 175–1500 rpm machine. Or burnish with a UHS pad and a battery, cord electric or propane machine at 1500–2000+ rpm.

Recoating

- Dust mop or sweep floor. Scrub floor with an autoscrubber or floor machine using a blue pad and the recommended Diversey cleaner at the recommended dilution. Rinse well and let dry.
- Apply 1–2 new coats of Mainstay™/MC Floor Finish.

Product Specifications

Description	
Color/Form	Opaque white liquid
Flash Point	> 200° F (> 93.4° C)
pH	9.0
Scent	Ammonia
Shelf Life	2 years
Slip Resistance	0.5 minimum (ASTM D2047)
Solids %	16
Solubility	Dispersible
Specific Gravity	1.02

Available Items

Product Code	Description/Package Size	Dilution
5104917	1 x 5 gallon / 18.9 L Envirobox™/MC	Ready-to-Use

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at www.sealedair.com or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.

Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.