

Diversey

Ultra Low Odor Waterbased Finish

Finish for
Wood Floors



Industry leading water technology formulated for use as a one or two component finish.

Features

- Designed to work in conjunction with:
Recoat Adhesion Formula and Tacking Solution
Waterborne Crosslinker (optional)
Prominence™/MC Heavy Duty Floor Cleaner
Speedtrack™/MC Clean and Burnish Restorer
- Exclusive Versatile Formula
- Manufactured by Bona solely for Diversey
- Formulated without APEOs, NMPs or phosphates
- Optional use of crosslinker delivers improved adhesion, durability and chemical resistance
- Maximum VOC content of 145 g/L when used as a single component
- Maximum VOC content of 175 g/L with Waterborne Crosslinker

Benefits

- Excellent Durability
- Built to deliver superior scuff and scratch resistance, even in high traffic environments
- Protects against soil, perspiration and daily cleaning
- Enhances Natural Appearance
- Clear translucent color prevents discoloration over wood and paint lines
- Non-yellowing formula stays clear even after multiple recoats

Applications

- For use on wood floors.
- Excellent leveling, adhesion and low foam properties
- Fast drying for one day recoating projects
- Daily cleaning with Prominence and periodic restoring with Speedtrack extends the gloss reducing recoat frequency

Manufactured by
Bona®



Ultra Low Odor Waterbased Finish

Finish for Wood Floors



Use Directions

PREPARATION

Follow MFMA and NOFMA guidelines for acclimation time of wood prior to installation, sanding and finishing. Protect area and entrances with wet-floor signs before resuming work. Floors will be slippery when wet.

PREVIOUSLY COATED FLOORS

A test patch is strongly recommended to determine adhesion compatibility over a previous water base or other unknown finish.

NOTE: For best results and proper cleaning, use the Diversey RECOAT ADHESION FORMULA AND TACKING SOLUTION following label instructions.

NOTE: FLOOR MUST BE THOROUGHLY DULL, CLEAN AND GLOSSLESS BEFORE THE APPLICATION OF FINISH. Apply finish at recommended spread rate with proper applicator. STIR WELL BEFORE USING.

STIR WELL BEFORE USING

1. Blockade area.
2. Remove gum or tape with putty knife. Dust mop floor thoroughly.
3. Screen floor with dustless sanding system using 3M Surface Prep Pads in 2 directions until all gloss is removed. (250 sq. ft/ side) or #120 grit screens (250 sq. ft/side)

Ensure edges and corners are also properly prepared. Use hand tool or palm sander with #150 grit paper as needed. DO NOT over abrade.

4. Vacuum and tack with water or Diversey RECOAT ADHESION FORMULA AND TACKING SOLUTION dampened terry cloth towels beneath a push broom or a Diversey Speedmop system.
5. Allow floor to dry 30 minutes before finish application.
6. Apply 1 or more coat of ULTRA LOW ODOR WATERBASED FINISH using a lightweight T-Bar and foam applicator head.
7. Recoat when dry, usually about 3 hours with normal spread rate, temperature, and humidity. **Do not puddle finish and ensure adequate ventilation during drying and curing.**
8. Allow finish to cure for 24 hours before opening to light traffic, and minimum of 2 days before opening for regular use.

MAINTENANCE

Dust mop floors often with microfiber dust mops and wet clean as needed with Diversey Prominence™/MC Heavy Duty Floor Cleaner at recommended dilution and Diversey Speedmops.

NOTE: DO NOT wet clean floor for 14 days. Dust mop and spot mop only during this period. Meets ASTD D-2047 requirement for slip resistance.

Product Specifications

Description	
Certifications	GREENGUARD, MFMA, NWFA
Color/Form	Milky White Liquid
pH	8.0
Scent	Slight Sweet
Shelf Life	1 year

Available Items

Product Code	Description/Package Size	Dilution
5142227	1 x 5 gallon / 18.9 L Container	Ready-to-Use

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at www.sealedair.com or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.