



Recoat Adhesion Formula and Tacking Solution

Wood Finish Adhesion Promoter



Manufactured by:

Bona[®]

Removes dusts and contaminants from the wood floor and optimizes adhesion of the new finish coat.

Exclusive Formula

- ▶ Manufactured by Bona solely for Diversey
- ▶ Not formulated with APEOs, NMPs or phosphates

Versatile

- ▶ For use on all types of polyurethane finished hardwood floors.
- ▶ Suitable for use with dry screen or wet screen floor prep processes.
- ▶ Remove dusts when used as a tacking solution during dry screen process.
- ▶ Can be used with autoscrubber during wet screen process.

Easy to Use

- ▶ No mixing, ready to use product
- ▶ Fast drying formula will not leave residue on the floor
- ▶ Low foam

Designed For

- ▶ Education
 - ▶ Retail
 - ▶ Government
-



Use Overview

Recoat Adhesion Formula and Tacking Solution cleans and prepares the existing wood finish to optimize adhesion of the new coat of finish.

Directions for Wet Screening/Abrading

- ▶ Blockade area.
- ▶ Remove all gum and tape with a quality scraper, then dust mop the floor thoroughly.
- ▶ Apply **Recoat Adhesion Formula and Tacking Solution** using an automatic scrubber or 175 RPM rotary scrubber equipped with maroon pad. Set scrubber to the minimum flow rate and move machine slowly, in a single overlapping pattern until clean.

Note: Rinse residue immediately from floor.

- ▶ Ensure edges and corners are also properly prepared. Use hand tool or palm sander with #150 grit paper as needed. Do not over abrade.
- ▶ Rinse floor with automatic scrubber equipped with blue and clean water until all dust is removed, including corners, edges, and baseboards.
- ▶ Floor must be thoroughly dull and clean before re-coating. If the floor has any shiny spots, repeat wet abrade procedure and rinse floor.



Directions for use as tacking solution prior to refinishing

- ▶ Soak a clean, dry, prewashed cotton towel with **Recoat Adhesion Formula and Tacking Solution**.
- ▶ Wring out and wrap around a push broom.
- ▶ Tack floor until clean and dust free.
- ▶ Re-position or flip the towel after each pass. Change towel when dirty.
- ▶ Allow 30 minutes to dry before the application of finish.
- ▶ Apply finish within 2 hours of tacking the floor.

Product Specifications

Description	
Color/Form	Amber liquid
Flash Point	> 200° F (> 93.34° F)
pH	7.3
Scent	Slight sweet
Shelf Life	2 years
Solubility	Complete
Specific Gravity	1.01

Available Items

Product Code	Description/Package Size	Dilution
5142243	1 x 5 gal. / 18.9 L Container	Ready-to-Use

Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available on-line at www.diversey.com or by calling 888 352 2249.

Hazard Rating

HMIS		NFPA
0	Health	0
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

Bona® is a registered trademark of BonaKemi USA, Inc.

For additional information, please visit our website at www.diversey.com

© 2013 Sealed Air Corporation. All Rights Reserved. SPC30152 (13/105)

