



Diversey

Wiwax^{TM/MC}

Cleaning &
Maintenance
Emulsion



A unique blend of waxes, polymers and detergents to effectively clean and maintain rubber as well as linoleum, asphalt, marble and slate flooring. An integral part of a comprehensive floor care program for cleaning, stripping, and sealing rubber floors.

Features

- Cleans and shines
- Pleasant fragrance

Benefits

- Protects when used on regular basis

Applications

- For use as a rubber floor maintainer. Can also be used on linoleum, asphalt, marble and slate flooring.
- Can be used for the rejuvenation, restoration and daily cleaning of stone flooring.



Wiwax™/MC

Cleaning & Maintenance Emulsion



Use Directions

Automatic Scrubbing Machines

1. Dust mop or sweep.
2. Blockade areas to be cleaned. Floors will be very slippery until dry.
3. Add four (4) oz. per gallon (30 mL per liter) of this product to lukewarm water. Scrub floor with product. Trail mop excessive wet areas behind scrubber. Do not rinse floor after cleaning.
4. Let floor dry completely.

Mop and Bucket Cleaning

1. Dust mop or sweep.
2. Blockade areas to be cleaned. Floors will be very slippery until dry.
3. Add two (2) oz. per gallon (15 mL per liter) of this product to lukewarm water. Mop floor clean with this product. Pick up soil and excess cleaner with a tightly wrung-out cleaning mop. Do not rinse floor after cleaning.
4. Let floor dry completely.

Stone Floor Daily cleaning (Automatic Scrubbing Machine):

1. Dust mop or sweep floor.
2. Blockade areas to be cleaned. Floors will be very slippery until dry.
3. Add (1) oz. per gallon of this product to warm water. Scrub floor with product and TASKI® Crystal Shield™/MC Clean and Burnish #2. Trail mop excessive wet areas behind scrubber. Do not rinse floor after cleaning.
4. Let floor dry completely.

Stone Floor Rejuvenation (Automatic Scrubbing Machine):

1. Dust mop or sweep floor.
2. Blockade areas to be cleaned. Floors will be very slippery until dry.
3. Add thirteen (13) oz. per gallon (101 mL per liter) of this product to lukewarm water. Scrub floor with product. Trail mop excessive wet areas behind scrubber. Do not rinse floor after cleaning.
4. Let floor dry completely.
5. For optimal gloss, burnish the floor with TASKI® Crystal Shield™/MC Clean and Burnish #2

Stone Floor Rejuvenation (Mop and Bucket method):

1. Dust mop or sweep floor.
2. Blockade areas to be cleaned. Floors will be very slippery until dry.
3. Clean floor with a neutral floor cleaner according to label directions.

4. Add thirteen (13) oz. per gallon (101 mL per liter) of this product to lukewarm water. Pick up soil and excess cleaner with a tightly wrung-out cleaning mop. Do not rinse floor after cleaning.
5. Let air dry.
6. For optimal gloss, burnish the floor with TASKI® Crystal Shield™/MC Clean and Burnish #2.

Stone Floor Restoration (Automatic Scrubber Machine):

1. Dust mop or sweep floor.
2. Blockade areas to be cleaned. Floors will be very slippery until dry.
3. Add 2oz per gallon of this product to warm water. Scrub floor with product and TASKI® Crystal Shield™/MC Wet Tool 3. Complete 6 passes with auto-scrubber over entire area. Trail mop excessive wet areas behind scrubber. Do not rinse floor after cleaning.
4. Let floor dry completely.
5. Apply a thin, uniform coat (2500–3000 sq. ft./gal.) of Crystal Shield™/MC using the ProSpeed Applicator system. Allow 20–30 minutes of dry time. Temperature, humidity and ventilation may affect drying time.
6. Burnish the floor with TASKI® Crystal Shield™/MC Clean & Burnish Pad #2.
7. Apply a second thin, uniform coat (2500–3000 sq. ft./gal.) of Crystal Shield™/MC using the ProSpeed Applicator system.

FOR BEST RESULTS:

- Do not use on surfaces colder than 50°F/10°C.
- To avoid contamination, do not return unused product to original container.

NOTE: Floors will be slippery when wet or contaminated with foreign materials. Promptly clean-up spills and foreign materials. Not intended for use in outdoor areas. Meets ASTM D-2047 requirements for slip resistance.

Rubber Floors:

For optimum appearance, alternate use of this product at standard dilution and Profi™ Degreaser once desired shine is achieved. On heavily worn rubber floors apply up to three coats of Wiwax™ emulsion cleaner using the mop and bucket cleaning instructions with a 1:1 dilution ratio until desired shine is achieved. If high gloss is desired, apply instead, three coats of Carefree Floor Finish.

Product Specifications

Description	
Certifications	None
Color/Form	Milky white liquid
pH	8.5 (Concentrate)
Scent	Characteristic
Shelf Life	2 years

Available Items

Product SKU	Description/Package Size	Dilution
94512767	4 x 1 gallon / 3.78 L Containers	1:32, 1:64

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at www.sealedair.com or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.

www.sealedair.com

© 2016 Sealed Air Corporation. All Rights Reserved. PSS34040 (16/167)