



JonCrete™/MC

Superior Adhesion and Cure Seal

A water-based, acrylic epoxy sealer with superior adhesion and excellent resistance to water and frequent cleaning.

Features

- Single component system; no mixing required
- Simply apply with mop or roller
- Meets ASTM C309 requirements—standard specification for liquid membrane-forming compounds for curing concrete

Benefits

- Patented water-based formula eliminates flammability concerns
- Complies with air quality (VOC) regulations

Applications

- For use as a water-based sealer for concrete and Terazzo Floors
- Use to simultaneously cure and seal fresh concrete as soon as trowling is complete and the slab is hard enough to walk on
- Not intended for use on vinyl, natural stone, ceramic, cork, wood, or bamboo flooring



Use Directions

Always follow use instructions for referenced products.

Inspect the Floor: If the floor is heavily contaminated or shows the presence of curing compounds or coatings, refer to the appropriate removal instructions from original product supplier.

Blockade areas to be sealed or stripped. Floors will be very slippery until dry.

Prepare the Floor:

1. Dust mop or sweep floor.
2. *For Lightly Soiled Areas:* Machine scrub with a 1:64 (2 fl.oz./gal.) solution of JonCrete™/MC Daily Cleaner (Accumix® System) and a soft brush or pad. *For Heavily Soiled Areas:* Machine scrub with JonCrete™/MC Concrete Restorer. Allow solution to soak for 5-10 minutes then scrub with a soft brush or pad.
Note: Do not use JonCrete™/MC Concrete Restorer on surface colored or acid dyed concrete floors.
3. Flood the floor with water and agitate with a stiff brush or pad. Keep floor very wet throughout this procedure. Pick-up water immediately following agitation.
4. Flood rinse thoroughly with plain water, then squeegee or wet vac to ensure that excess water and loose concrete particles (laitance) are removed.
5. Allow floor to dry thoroughly.

Coat the Floor:

1. Apply 3-4 uniform full coats using a mop, roller or other suitable applicator.
2. Allow 1-2 hours drying time between coats. Open to foot traffic after 4 hours.

Maintenance:

1. Dust mop or sweep as necessary.
2. Clean daily with JonCrete™/MC Daily Cleaner at 1:512 (1 fl. oz./4 gal.) using an autoscrubber or swing machine with wet vac. Red pads or medium stiff brushes are recommended.
3. Rinse with clean water to remove any residue.

Recoating/Topcoating:

1. Follow the maintenance cleaning procedures, rinse and let dry.
2. Recoat with 1-2 uniform full coats or topcoat with any Diversey water-based polymer finish if desired.
3. Equipment should be cleaned immediately after use with water.

Removal:

1. Sealer can be removed by scrubbing with an abrasive pad or moderate brush under a rotary floor machine using a recommended Diversey floor stripper (see JonCrete™/MC Program Training Guide for further instructions).
2. Rinse thoroughly and let floor dry before re-applying.

Terrazzo Floors:

Prepare and coat the floor. Strip the floor with a recommended Diversey stripper following label use instructions. Apply 2 coats of concrete sealer. Topcoat with any recommended Diversey floor finish. Refer to application guide for additional information on terrazzo floors.

Maintenance and Recoat/Topcoat Procedures: Follow normal maintenance procedures for the respective topcoat finish applied.

NOTE: Floors will be slippery when wet or contaminated with foreign materials. Promptly clean-up spills and foreign materials. Meets ASTM D-2047 requirement for slip resistance. Not intended for use in outdoor areas.



FOR BEST RESULTS

- Not recommended for use on resilient floors
- If concrete is less than 30 days old, not more than one coat should be applied at not less than 200 sq.ft./gallon
- Test for adhesion in small patches before nishing entire area
- Do not dilute
- Do not use on surfaces colder than 10°C/50°F
- To avoid contamination, do not return unused product to original container
- Keep from freezing.

Product Specifications

Description	
Certifications	None
Color/Form	Milky White Liquid
pH	10.5
Scent	Amine
Shelf Life	2 years

Available Items

SKU Code		Description/Package Size	Dilution
95104861	 	1 x 5 gallon / 18.9 L Envirobox™/MC	Ready-to-Use

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at www.sealedair.com or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.