

Diversey

## Polyurethane 350 Finish

Oil Modified Wood  
Floor Finish



High gloss oil modified urethane finish formulated for one coat application on wood sports floors.

### Features

- Formulated without APEOs, NMPs or phosphates
- Maximum VOC content of 350 g/L
- Manufactured by Bona solely for Diversey Care

### Benefits

- Light amber color enhances the natural color of the wood floor
- Tough, high gloss with only one coat
- Provides outstanding resistance from soil, perspiration, heavy traffic and daily cleaning

### Applications

- For use on unsealed wood sport floors. Not intended for use on stone, resilient, or rubber flooring
- Can be used over most waterbased and oil modified finishes after proper preparation, drying and curing times
- Designed to work in conjunction with: Recoat Adhesion Formula and Tacking Solution, Prominence™/MC Heavy Duty Floor Cleaner and Speedtrack™/MC Clean and Burnish Restorer
- Applies flawlessly with the EZ Way™/MC Applicator or Heavyweight T-bar

Manufactured by:  
**Bona**



# Polyurethane 350 Finish

## Oil Modified Wood Floor Finish



### Use Directions

- Stir well before using. Blockade area. Remove gum or tape with putty knife. Dust mop floor thoroughly.
- Screen floor with #120 grit screens in 2 directions until all gloss is removed. (250 sq. ft./side). Ensure edges and corners are also properly prepared. Use hand tool or palm sander with #150 grit paper as needed. Do not over abrade.
- Vacuum and tack with Diversey Recoat Adhesion Formula and Tacking Solution.
- Allow floor to dry 30 minutes before finish application.
- Apply 1 coat Polyurethane 350 Finish using a heavy weight T-Bar and woven applicator head. Do not puddle finish and ensure adequate ventilation during drying and curing.
- Allow finish to cure for 48 hours before opening to light traffic, and a minimum of 7 days before opening for regular use. Adequate ventilation is imperative during the drying and curing process. Colder temperatures and/or high humidity will slow dry time.

### Maintenance

- Dust mop floors often with microfiber dust mops and wet clean using the Speed Mop System as needed with Prominence™/MC Heavy Duty Floor Cleaner according to label directions. Use Speedtrack™/MC periodically to restore gloss and increase traction.

NOTE: DO NOT wet clean floor for 14 days. Dust mop and spot mop only during after recoat.

### Special Handling

- Always wear appropriate personal protective equipment.
- Used finish materials (e.g., clean-up rags, steel wool, tacking towels) and sanding dust can spontaneously ignite if improperly discarded.
- Do not store waste finish materials or sanding dust in a pile or discard into the regular trash.
- Place all waste materials into a water-filled metal container and discard according to local, state and federal regulations.

### Product Specifications

Description	
Certifications	MFMA, NWFA
Color/Form	Amber liquid
pH	NA (RTU)
Scent	Solvent
Shelf Life	2 years*

\* When stored in unopened container at ambient temperatures. High temperatures can accelerate aging. Store on lower shelf in warehouse.

### Available Items

SKU Code	Description/Package Size	Dilution
95142180	1 x 5 gallon / 18.9 L Container	Ready-to-Use

### Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at [www.sealedair.com](http://www.sealedair.com) or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.