

**Diversey**

## Pro Strip™ ULTRA

Heavy Duty  
Floor Stripper



An ultra strength stripper designed for the removal of “tough to strip” finishes and sealers.

### Reduces Labor

- Fast penetration of UHS burnished finishes and sealer layers
- Designed to work the first time to reduce “restrips”

### Low Odor

- Not formulated with butyl or ammonia
- Reduces facility complaints regarding floor stripping odors

### Versatile Problem Solver

- Concentrate not regulated as hazardous waste for disposal under EPA Resource Conservation and Recovery Act (RCRA) regulations
- New stronger concentration for lower in-use cost
- Works in cool water
- PPE is not required at specified use dilution

### Designed For

- Healthcare
- Food Service
- Education
- Retail
- BSC
- Lodging
- Government

# Use Overview

Pro Strip™ ULTRA Heavy Duty Floor Stripper is a powerful, fast-acting stripper that begins to emulsify most finishes upon contact, reducing normal soak times and removing multiple layers of finish with fewer passes. Can be applied on VCT, terrazzo and concrete floors.

- Use appropriate personal protective equipment. Dilute product as follows:
  - Light Build-up of Floor Finishes:**
    - Dilute product between 1:8 (16 fl. oz./gal.) and 1:10 (13 fl. oz./gal.) with cool water.
  - Heavy Build-up of Floor Finishes:**
    - Dilute product at 1:6 (24 fl. oz./gal.) with cool water.
  - Heavy Build-up of Concrete Sealers:**
    - Dilute product at 1:4 (32 fl. oz./gal.) with cool water.
- Blockade areas to be stripped. Floors will be very slippery when stripper is applied. Exercise caution.
- Apply liberal amounts of solution uniformly to floor with a mop. Start with the edges to give them more soak time. If splashing occurs, wipe off surfaces with a clean rag dampened with water.
- Let stripper solution soak for 5–10 minutes. Mop agitate to loosen finish or sealer. Re-wet as necessary, do not allow stripper to dry on the floor. Longer soak times may be necessary in cases of extreme buildup.



- Hand or machine scrub thoroughly using black pads or stripping brush.
- Pick-up all of the solution with a clean mop, wet vac or automatic scrubber.
- Mop up any “tracks” left by wet vacs or automatic scrubbers before they dry. Thoroughly rinse floor with clean water, using a mop and bucket.
- Let floor dry completely before applying recommended Diversey brand floor sealer or finish.

Pro Strip™ ULTRA Heavy Duty Floor Stripper meets the newest and most stringent VOC standards in North America, including those adopted by the California Air Resources Board (CARB).

## Product Specifications

Description	
Color/Form	Colorless liquid
Dilution	1:4 (Concrete Sealer) 1:6 (Heavy Build-up) 1:8–1:10 (Light Build-up)
Flash Point	> 200° F (> 93.4° C)
pH	12.3 (Concentrate) 11.7 (Dilution, 1:4)
Scent	Cherry Almond
Shelf Life	2 years
Solubility	Complete
Specific Gravity	1.025

## Available Items

Product Code	Description/Package Size	Dilution
95386176	1 x 5 gallon / 18.9 L Envirobox™/MC	1:4–1:10

## Hazard Rating

HMIS	Concentrate	NFPA	HMIS	Use Dilution 1:4	NFPA
3	Health	3	2	Health	2
0	Flammability	0	0	Flammability	0
0	Reactivity	0	0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

## Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at [www.sealedair.com](http://www.sealedair.com) or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.