

MAXIM®

18% High Gloss Floor Finish

Features:

Economical and Durable
Excellent Off-the-Mop Gloss
Easy to Maintain, Non-Yellowing
For Occasional Spray Buffing or Burnishing

Description

This product is a simplified floor finish that provides the end user with a superior high gloss finish that is extremely tough and durable. This product is self-sealing so less products are needed to provide a superior wet look gloss. This product is formulated to respond to low, high, and ultra high speed maintenance techniques.

Directions

For floor finishing:

- 1 Thoroughly strip floor according to stripper label instructions, and allow to dry completely.
- 2 Use a mop or applicator to apply 3 - 5 coats of sealer. Allow 30 - 45 minutes of drying time between coats.
- 3 For maintenance, dust mop or damp mop as needed.
- 4 For restoration, damp mop thoroughly with floor cleaner, and buff or burnish with spray buff or mop-on restorer.

For concrete, terrazzo, marble or granite:

- 1 Apply two coats of floor sealer according to sealer label instructions.
- 2 Use a mop or applicator to apply 2 - 5 coats of finish. Allow 30 - 45 minutes of drying time between coats.
- 3 Maintain and restore as above.

Recommended pads for buffing or burnishing:

175 - 1500 RPM: Soft White or Red Pad
 1500+ RPM: White, Champagne, or Light Natural Pad



Applications

For low maintenance areas such as:

- > Schools
- > Hospitals
- > Offices

Specifications

Color	White
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Density	8.55
Non-volatile solids	18%
Coverage	2000 sq. ft. / gal.

Packaging

4/1 gallon	121800-41
5 gallon	121800-05
55 gallon	121800-55