

# MAXIM<sup>®</sup>

## Ultrashield 22 UF 22% Urethane Fortified Floor Finish

### Features:

- Balances Price with Performance**
- Durable, Easy to Maintain, Non-Yellowing**
- Good Off-the-Mop Gloss**

### Description

This product is designed for heavy traffic areas such as supermarkets, retail, and institutional settings on all types of resilient flooring. Unique water based urethane emulsion gives a superior wet look gloss with superb detergent resistance and durability.

Contains UFW technology to prevent discoloration and dirt penetration to stay looking clean longer, extending the period between stripping cycles.

### Directions

*Keep from freezing.*

#### For floor finishing:

- 1 Thoroughly strip floor according to stripper label instructions, and allow to dry completely.
- 2 Use a mop or applicator to apply 3 - 7 coats of finish. Allow 30 - 45 minutes of drying time between coats.
- 3 Allow a minimum of 2 hours of drying time before burnishing. For best results, allow 24 hours of drying time before burnishing, and use a floor cleaner with a damp mop or auto scrubber with a Red Pad.
- 4 For maintenance, dust mop or damp mop as needed.
- 5 For periodic deep scrub and before recoating, use a floor cleaner with autoscrubber and Blue Pad.

#### For concrete, terrazzo, marble or granite:

- 1 Apply two coats of floor sealer according to sealer label instructions.
- 2 Use a mop or applicator to apply 3 - 5 coats of finish. Allow 30 - 45 minutes of drying time between coats.
- 3 Burnish, maintain and restore as above.

#### Recommended pads for buffing or burnishing:

*Americo Combo | ETC Gorilla Lite | Glit Joey | Microtron White Polish  
3M White Polish | Triple S White Polish*



### Applications

#### For daily maintenance in:

- > Schools and offices
- > Supermarkets and retail
- > Hospitals and medical centers

### Specifications

Color .....	White
Fragrance .....	Characteristic
pH Range .....	8.0 - 8.5
Dilution .....	RTU
Density .....	8.60
Non-volatile solids .....	22%
Coverage .....	2000 sq. ft. / gal.

### Packaging

4/1 gallon	152400-41
5 gallon	152400-05
55 gallon	152400-55