

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : A00178 MST VANDALISM MRK RMVR 20NET16

Material number : 00000000001001632

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : 404-352-1680

**Emergency telephone numbers****For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation  
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616**Recommended use of the chemical and restrictions on use**

Recommended use : Specialty Cleaner and Remover

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	aromatic

**GHS Classification**

Flammable aerosols : Category 1  
 Gases under pressure : Liquefied gas  
 Skin irritation : Category 2  
 Eye irritation : Category 2A  
 Reproductive toxicity : Category 2  
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)  
 Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

**GHS label elements**

Hazard pictograms : 

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

H280 Contains gas under pressure; may explode if heated.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H361 Suspected of damaging fertility or the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

## Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Pressurized container: Do not pierce or burn, even after use.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P362 Take off contaminated clothing and wash before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

P501 Dispose of contents/container in accordance with local regulation.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 50 - < 70

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

toluene	108-88-3	>= 10 - < 20
propane	74-98-6	>= 5 - < 10
2-butoxyethanol	111-76-2	>= 5 - < 10
butanone	78-93-3	>= 5 - < 10
butane	106-97-8	>= 5 - < 10

The exact percentages of disclosed substances are withheld as trade secrets.

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
- In case of skin contact : Wash off with soap and plenty of water.  
Wash off immediately with plenty of water for at least 15 minutes.  
Wash contaminated clothing before re-use.  
Call a physician if irritation develops or persists.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.  
  
Chronic effects are delayed and symptoms may not be observed during an exposure.  
Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling, respiratory issues, and general pain.  
Effects are dependent on exposure (dose, concentration, contact time).  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure if inhaled.  
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

---

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Foam  
Dry chemical  
Water
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Use a water spray to cool fully closed containers.  
Standard procedure for chemical fires.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.
- 

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.
-

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

Smoking, eating and drinking should be prohibited in the application area.  
 Take precautionary measures against static discharges.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Dispose of rinse water in accordance with local and national regulations.  
 Do not breathe vapours or spray mist.  
 Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
 No smoking.  
 Observe label precautions.  
 Keep in a cool, well-ventilated place.  
 Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Strong oxidizing agents  
 Do not store near acids.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA Z-1
		TWA	750 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		STEL	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA P0
		STEL	750 ppm 1,780 mg/m <sup>3</sup>	CAL PEL
		C	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m <sup>3</sup>	CAL PEL
		toluene	108-88-3	TWA
TWA	100 ppm 375 mg/m <sup>3</sup>			NIOSH REL
ST	150 ppm 560 mg/m <sup>3</sup>			NIOSH REL
TWA	200 ppm			OSHA Z-2
CEIL	300 ppm			OSHA Z-2
Peak	500 ppm			OSHA Z-2
TWA	100 ppm 375 mg/m <sup>3</sup>			OSHA P0

## A00178 MST VANDALISM MRK RMVR 20NET16

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

		STEL	150 ppm 560 mg/m <sup>3</sup>	OSHA P0
		PEL	10 ppm 37 mg/m <sup>3</sup>	CAL PEL
		C	500 ppm	CAL PEL
		STEL	150 ppm 560 mg/m <sup>3</sup>	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		PEL	1,000 ppm 1,800 mg/m <sup>3</sup>	CAL PEL
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 240 mg/m <sup>3</sup>	OSHA Z-1
		TWA	25 ppm 120 mg/m <sup>3</sup>	OSHA P0
		PEL	20 ppm 97 mg/m <sup>3</sup>	CAL PEL
butanone	78-93-3	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		ST	300 ppm 885 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 590 mg/m <sup>3</sup>	OSHA Z-1
		TWA	200 ppm 590 mg/m <sup>3</sup>	OSHA P0
		STEL	300 ppm 885 mg/m <sup>3</sup>	OSHA P0
		PEL	200 ppm 590 mg/m <sup>3</sup>	CAL PEL
		STEL	300 ppm 885 mg/m <sup>3</sup>	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		TWA	800 ppm 1,900 mg/m <sup>3</sup>	OSHA P0
		PEL	800 ppm 1,900 mg/m <sup>3</sup>	CAL PEL

## Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after	25 mg/l	ACGIH BEI

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

				exposure ceases)		
METHYLBENZENE	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
METHYLBENZENE		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
METHYLBENZENE		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3.mg/g Creatinine	ACGIH BEI
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200.mg/g Creatinine	ACGIH BEI
2-BUTANONE	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

**Personal protective equipment**

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.  
Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves  
: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Safety glasses  
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection

: Impervious clothing  
Choose body protection according to the amount and

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : colourless

Odour : aromatic

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point : No data available

Flash point :  
Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.810 g/cm<sup>3</sup>

Solubility(ies)

Water solubility : partly soluble

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Heat of combustion : 35.04 kJ/g

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous : Vapours may form explosive mixture with air.



**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

reactions	No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Acids Oxidizing agents
Hazardous decomposition products	: Carbon monoxide Carbon dioxide (CO <sub>2</sub> )

**SECTION 11. TOXICOLOGICAL INFORMATION**
**Potential Health Effects**

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.  Chronic effects are delayed and symptoms may not be observed during an exposure. Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling, respiratory issues, and general pain. Effects are dependent on exposure (dose, concentration, contact time).

**Carcinogenicity:**

<b>IARC</b>	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
<b>ACGIH</b>	Confirmed animal carcinogen with unknown relevance to humans 2-butoxyethanol 111-76-2
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
<b>NTP</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Acute toxicity**
**Product:**

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
---------------------	---

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

Acute inhalation toxicity : Acute toxicity estimate : 17.65 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

**Components:****acetone:**

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l  
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

**2-butoxyethanol:**

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

**butanone:**

Acute oral toxicity : LD50 Oral Rat: 2,737 mg/kg

Acute inhalation toxicity : LC50 Mouse: 32,000 mg/l  
Exposure time: 4 h

LC50 : 38,000 mg/l

Acute dermal toxicity : LD50 Dermal Rabbit: 6,480 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: Irritating to skin.

**Serious eye damage/eye irritation****Product:**

Remarks: Irritating to eyes.

**Respiratory or skin sensitisation**

No data available

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**Components:****toluene:**

Remarks: No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

**Components:****toluene :**

Partition coefficient: n-octanol/water : Pow: 2.73

**butanone :**

Partition coefficient: n-octanol/water : log Pow: 0.29

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

**butane :**
 Partition coefficient: n-  
 octanol/water : Pow: 2.89
**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation

 40 CFR Protection of Environment; Part 82 Protection of  
 Stratospheric Ozone - CAA Section 602 Class I  
 Substances

Remarks

 This product neither contains, nor was manufactured  
 with a Class I or Class II ODS as defined by the U.S.  
 Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A  
 + B).

 Additional ecological  
 information

: No data available

**Components:****toluene :**
 Additional ecological  
 information

: No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS**
**Disposal methods**

Waste from residues

 : Do not dispose of waste into sewer.  
 Do not contaminate ponds, waterways or ditches with  
 chemical or used container.  
 Dispose of in accordance with local regulations.

Contaminated packaging

 : Empty remaining contents.  
 Dispose of as unused product.  
 Do not re-use empty containers.  
 Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION**

 Transportation Regulation: 49 CFR (USA):  
 ORM-D, CONSUMER COMMODITY

 Transportation Regulation: IMDG (Vessel):  
 UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

 Transportation Regulation: IATA (Cargo Air):  
 UN1950, Aerosols, flammable, 2.1, - Limited quantity

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

Transportation Regulation: IATA (Passenger Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

**SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

**EPCRA - Emergency Planning and Community Right-to-Know Act**
**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene	108-88-3	1000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Gases under pressure  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene	108-88-3	17 %
2-butoxyethanol	111-76-2	8.5 %

**California Prop. 65**

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018



**WARNING:** This product can expose you to chemicals including toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).


**The components of this product are reported in the following inventories:**

**DSL** All components of this product are on the Canadian DSL  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

**Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

**SECTION 16. OTHER INFORMATION**
**Further information**
**NFPA:**

**HMIS III:**

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>4</b>
<b>PHYSICAL HAZARD</b>	<b>3</b>

0 = not significant, 1 = Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

**OSHA - GHS Label Information:**

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

: **Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after

**A00178 MST VANDALISM MRK RMVR 20NET16**

Version 2.0

Revision Date 04/20/2018

Print Date 05/31/2018

handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	2.0
Revision Date:	04/20/2018
Print Date:	05/31/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.