

PRODUCT SALES SHEET

G00728 Moly Grease



Features

- Moly for Extra EP Ability
- 550+ Dropping Point, Non-Melt Grease
- 65 Timken OK Load
- Resists Weather, Dirt Water, Etc

Description

Our MOLY-GREASE is a non-melt gray colored lubricant containing molybdenum disulfide. This product is fortified to provide anti-wear and low friction performance through a wide temperature range. The molybdenum disulfide contained in MOLY-GREASE reduces friction and protects against excessive wear, from extreme loads, galling and seizing. The moly "plates out" on metal surfaces, imparting extra protection to the parts and extending the lubrication cycle. MOLY-GREASE is exceptionally resistant to most acids, salt spray, steam, dirt, dust, water, oxidation and weather. Our product has excellent adhesive and cohesive properties, as well as high shock protection. MOLY-GREASE protects equipment indoors or outdoors, even under high temperatures and heavy loads.

| TECHNICAL INFO: | | |
|--------------------------|-----------------------------|-----------|
| Physical Properties | Appearance | |
| | Color | Black |
| | Odor/Fragrance | Petroleum |
| | рН | N/A |
| | Spray Pattern | N/A |
| Environmental Profile | Glycol Ether Content | None |
| | Biodegradability | No |
| | Chlorinated Solvents | None |
| | Green Status | None |
| | Recyclable Packaging | Yes |
| Regulatory Profile | % VOC By Weight | 3.0 |
| | VOC Restricted Regions | None |
| | Food Processing Suitability | H2 |
| | EPA# | N/A |
| | Flammability per CPSC | N/A |
| | Flash Point | > 400° F |



Label Datecode: 04/08

Manufactured by:

