

# **A00810 MST DUST MOP TREATMENT 20NET18**

Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018

## **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : A00810 MST DUST MOP TREATMENT 20NET18

Material number : 00000000001003402

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : 404-352-1680

## **Emergency telephone numbers**

For SDS Information: Compliance Services 1-877-428-9937For a Medical Emergency: 877-541-2016 Toll Free - All Calls RecordedFor a Transportation: CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Floor Care

#### **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	white
Odour	characteristic

## **GHS Classification**

Gases under pressure : Liquefied gas

**GHS** label elements

Hazard pictograms :

 $\Diamond$ 

Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Prevention**:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P251 Pressurized container: Do not pierce or burn, even after

use. Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place.



# **A00810 MST DUST MOP TREATMENT 20NET18**

Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018

P412 Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 10 - < 20
Distillates (petroleum), hydrotreated light	64742-47-8	>= 5 - < 10
butane	106-97-8	>= 5 - < 10
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 5 - < 10
propane	74-98-6	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended. Move out of dangerous area.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

Rinse immediately with plenty of water for at least 15 minutes.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Causes skin irritation.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.



Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.
 Evacuate personnel to safe areas.
 Ensure adequate ventilation.

Remove all sources of ignition.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid contact with skin and eyes.



Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Always replace cap after use.

Dispose of rinse water in accordance with local and national

regulations.

Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Keep in a dry, cool and well-ventilated place.

Materials to avoid : Oxidizing agents

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
	_	TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm	OSHA Z-1



# **A00810 MST DUST MOP TREATMENT 20NET18**

Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018

	1,800 mg/m3	
TWA	1,000 ppm 1,800 mg/m3	OSHA P0
PEL	1,000 ppm 1,800 mg/m3	CAL PEL

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : white

Odour : characteristic
Odour Threshold : No data available
pH : Not applicable
Melting point/freezing point : No data available
Boiling point : No data available

Flash point

Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : The product is not flammable.

Upper explosion limit : No data available Lower explosion limit : No data available



# **A00810 MST DUST MOP TREATMENT 20NET18**

Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018

Vapour pressure : No data available Relative vapour density : No data available

Density : 0.93 g/cm3

Solubility(ies)

Water solubility : emulsifiable
Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or



# **A00810 MST DUST MOP TREATMENT 20NET18**

Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

**Acute toxicity** 

**Product:** 

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Skin corrosion/irritation

**Product:** 

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

**Product:** 

Remarks: May irritate eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity



# **A00810 MST DUST MOP TREATMENT 20NET18**

Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

**Aspiration toxicity** 

No data available

**Further information** 

**Product:** 

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated light:

Remarks: No data available

## **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

No data available

Persistence and degradability

No data available

**Bioaccumulative potential** 

**Product:** 

Partition coefficient: n-

: Remarks: No data available

octanol/water **Components:** 

butane:

Partition coefficient: n-

: Pow: 2.89

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

40 CFR Protection of Environment; Part 82 Protection of Regulation

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S.



# **A00810 MST DUST MOP TREATMENT 20NET18**

Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018

Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

Components:

Distillates (petroleum), hydrotreated light :

Additional ecological

information

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

## **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.



Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

#### **EPCRA - Emergency Planning and Community Right-to-Know Act**

## **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Gases under pressure

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### California Prop. 65



WARNING: This product can expose you to chemicals including ethylbenzene, benzene, naphthalene, which is/are known to the State of California to cause cancer, and toluene, benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more

information go to www.P65Warnings.ca.gov.

# The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

**DSL** All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)




Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA:



Special hazard.

#### HMIS III:

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms



Signal word Warning:

Hazard statements Contains gas under pressure; may explode if heated. Precautionary statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use.

Storage: Protect from sunlight. Store in a well-ventilated place. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	5.0
Revision Date:	12/17/2017
Print Date:	05/31/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.



# **A00810 MST DUST MOP TREATMENT 20NET18**

Version 5.0 Revision Date 12/17/2017 Print Date 05/31/2018