ZepInc

Version 2.0

Revision Date 03/06/2017

Print Date 06/01/2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	127734 TM BAYBERRY 30% 12/CS 12N5.3
Material number	:	00000000001042705
Manufacturer or supplier's d	leta	ils
Company	:	Zep Inc.
Address	:	1310 Seaboard Industrial Blvd., NW Atlanta, GA 30318
Telephone	:	404-352-1680

Emergency telephone numbers		
For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation Emergency	:	CHEMTREC: 800-424-9300 - All Calls Recorded. In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Air Care

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Liquefied gas
Colour	colourless
Odour	characteristic

GHS Classification

Flammable aerosols	:	Category 1
Gases under pressure	:	Liquefied gas
Eye irritation	:	Category 2A
Skin sensitisation	:	Category 1
Specific target organ toxicity -	:	Category 3 (Central nervous system)
single exposure		

GHS label elements

Ono laber elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.



sion 2.0	Revision Date 03/06/2017	Print Date 06/01/2018
Precautionary statements	 Prevention: P210 Keep away from heat, hot and other ignition sources. No sr P211 Do not spray on an open fl P251 Pressurized container: Do use. P261 Avoid breathing dust/ fume P264 Wash skin thoroughly after P271 Use only outdoors or in a w P272 Contaminated work clothin the workplace. P280 Wear protective gloves/ ey Response: P302 + P352 IF ON SKIN: Wash P304 + P340 + P312 IF INHALE and keep comfortable for breathi CENTER/doctor if you feel unwe P305 + P351 + P338 IF IN EYES for several minutes. Remove cor easy to do. Continue rinsing. P333 + P313 If skin irritation or r advice/ attention. P337 + P313 If eye irritation pers attention. P363 Wash contaminated clothir Storage: P403 Store in a well-ventilated p P410 + P412 Protect from sunlig temperatures exceeding 50 °C/ C Disposal: Dispose of contents/container in regulation. 	moking. lame or other ignition source. not pierce or burn, even after e/ gas/ mist/ vapours/ spray. r handling. well-ventilated area. ng should not be allowed out of re protection/ face protection. n with plenty of soap and water ED: Remove person to fresh and ing. Call a POISON ell. S: Rinse cautiously with water ntact lenses, if present and rash occurs: Get medical sists: Get medical advice/ ng before reuse. elace. pht. Do not expose to 122 °F.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 50 - < 70
propane	74-98-6	>= 20 - < 30
eugenol	97-53-0	>= 1 - < 5
cinnamon oil	8015-91-6	>= 1 - < 5
cinnamaldehyde	104-55-2	>= 0.1 - < 1
benzyl salicylate	118-58-1	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	 Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure.



sion 2.0	Revision Date 03/06/2017	Print Date 06/01/2018
	If unconscious place in recovery advice.	position and seek medical
In case of skin contact	 If skin irritation persists, call a ph Wash off immediately with plenty minutes. If on clothes, remove clothes. Wash contaminated clothing bef 	of water for at least 15
In case of eye contact	: Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsin If eye irritation persists, consult a In case of contact, immediately f for at least 15 minutes.	a specialist.
If swallowed	 Keep respiratory tract clear. Never give anything by mouth to If symptoms persist, call a physic DO NOT induce vomiting unless physician or poison control center 	cian. directed to do so by a
Most important symptoms and effects, both acute and delayed	 Effects are immediate and delay Symptoms may include irritation. Symptoms may include central nor resulting in headache, nausea and Effects are dependent on exposit contact time). Causes serious eye irritation. May cause drowsiness or dizzing May cause an allergic skin react Review section 2 of SDS to see 	, redness, pain, and rash. nervous system depression, nd/or dizziness. ure (dose, concentration, ess. ion.
Notes to physician	: Treat symptomatically. Symptor	ns may be delayed

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Fire residues and contaminated fire extinguishing water must

Version 2.0	Revision Date 03/06/2017	Print Date 06/01/2018
	be disposed of in accordance For safety reasons in case of separately in closed containr Use a water spray to cool ful	f fire, cans should be stored ments.
Special protective equipment for firefighters	: Wear self-contained breathin necessary.	ng apparatus for firefighting if

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	 Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE


Advice on safe handling	 Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Do not breathe vapours or spray mist. Always replace cap after use.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep in a dry, cool and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Store and keep away from, oxidizing agents and acids.





Version 2.0

Revision Date 03/06/2017



ZepInc

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI
				shift (As	-	
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection Material Remarks		Protective gloves The suitability for a specific workplace should be discussed

Version 2.0	Revision Date 03/06/2017 Print Date 06/01/2018			
	with the producers of the protective	e gloves.		
Eye protection	: Ensure that eyewash stations and the workstation location. Safety glasses	safety showers are close to		
Skin and body protection	: Impervious clothing Choose body protection according concentration of the dangerous su			
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at	the end of workday.		

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquefied gas
Colour	:	colourless
Odour	:	characteristic
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	
		Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Extremely flammable aerosol.
Linner evelopien limit		No data available
Upper explosion limit	•	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	No data available
Solubility(ies)		
Water solubility	:	partly soluble
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Heat of combustion	:	36.86 kJ/g



Version 2.0

Revision Date 03/06/2017



SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to sucid	
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents Acids Bases
Hazardous decomposition products	: Carbon monoxide Carbon dioxide (CO2)

SECTION 11. TOXICOLOGICAL INFORMATION

Aggravated Medical Condition Symptoms of Overexposure	 None known. Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Effects are dependent on exposure (dose, concentration, contact time).
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

sion 2.0	Revision Date 03/06/2017	Print Date 06/01/201
Product:		
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg Method: Calculation method	/kg
Components:		
acetone: Acute oral toxicity	: LD50 Rat: 5,800 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h	
	LC50 Rat: 50.1 mg/l	
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg	
	LD50 Rabbit: > 7,426 mg/kg	
propane: Acute inhalation toxicity	: LC50 Mouse: 1,237 mg/l Exposure time: 2 h	
	LC50 Rat: 658 mg/l Exposure time: 4 h	
	LC50 Rat: 1,355 mg/l	
cinnamon oil: Acute oral toxicity	: LD50 Oral Rat: 2,650 mg/kg	
Acute dermal toxicity	: LD50 Dermal Rabbit: > 5,000 mg/kg)
cinnamaldehyde: Acute oral toxicity	: LD50 Oral Rat: 2,220 mg/kg	
benzyl salicylate:	: LD50 Oral Rat: 2,227 mg/kg	

ZepInc

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Eye irritation

Respiratory or skin sensitisation

Version 2.0

Revision Date 03/06/2017



Print Date 06/01/2018

Product:

Classification: May cause sensitisation by skin contact.

Germ cell mutagenicity


No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available



STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Product:

Partition coefficient: n- octanol/water <u>Components:</u> cinnamaldehyde :	:	Remarks: No data available
Partition coefficient: n-	:	Pow: 1.83

Version 2.0	Revision Date 03/06/2017	Print Date 06/01/2018
octanol/water		
Mobility in soil		
No data available		
Other adverse effects		
No data available <u>Product:</u>		
Regulation	40 CFR Protection of Environm Stratospheric Ozone - CAA Sec Substances	
Remarks	This product neither contains, r with a Class I or Class II ODS a Clean Air Act Section 602 (40 0 + B).	as defined by the U.S.
Additional ecological information	: An environmental hazard cannot event of unprofessional handlin aquatic life with long lasting effe	g or disposal., Harmful to

Zepinc

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Version 2.0

Revision Date 03/06/2017



The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

 TSCA list
 : No substances are subject to a Significant New Use Rule. No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards :	Fire Hazard Sudden Release of Pressure Hazard Acute Health Hazard
SARA 302 :	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313 :	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop 65	This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA	On TSCA Inventory
DSL	All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)




Version 2.0

Revision Date 03/06/2017

Print Date 06/01/2018

SECTION 16. OTHER INFORMATION



OSHA - GHS Label Information:

Hazard pictograms	
Signal word	: Danger:
Hazard statements	 Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements	:
	 Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/eye protection/face protection. Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse. Storage: Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.0
Revision Date:	03/06/2017
Print Date:	06/01/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Version 2.0

Revision Date 03/06/2017



Print Date 06/01/2018

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.