

RecMic II Series

- Plug&Play with Dragon SpeechRecognition by Nuance©
- Speech Recognition in noisy environments
- Customizable buttons events
- · Beam forming

- Plug&Play with Windows SpeechRecognition
- Microphone stand for handsfree dictation
- Noise cancellation
- · Acceleration sensor



Designed for Speech Recognition

EXPERIENCE A NEW DIMENSION OF SPEECH-to-TEXT.

The RecMic II Series is created to cater to the high demands of professionals who want excellent usability and results with any speech-to-text solution. The four models of this new series are providing the benefits of the innovative noise cancellation technology with the intelligent Two-Microphone-System for flexible directionality and noise cancellation. All devices also come with an extra smooth UV-coating and silent buttons to reduce disturbing touch noises. The antimicrobial surface meets hygienic requirements, especially in medical areas.



Specifications

Storage Media

Internal memory No

8GB (RM-4015P)

USB functionality

USB Speed USB 2.0 High Speed USB Classes USB Audio class

HID mouse

HID vendor (default) / keyboard

Device operation

Main Switch Slide Switch (RM-4100S, RM-4110S)
Push (RM-4010P, RM-4015P)
Programmable button 14 Low noise buttons
Optical trackball Yes, incl. left mouse click function (RM-4010P, RM4015P, RM-4110S)
Click lock function for drag & drop
Function buttons 4 (RM-4100S: 3 additional F-Buttons)

Recording Modes

Acceleration sensor

Recording format PCM (mono, 16bit, 44.1kHz

sampling)

Available

Record function

| Noise cancellation | Variable |
|-----------------------|-------------------------------------|
| Active Directionality | Variable |
| Noise analyzer | Available |
| Pop-filter | 3 layers |
| Operation Modes | |
| Olympus Mode | Available (default) |
| HID Keyboard Modes | Custom mode (Customizable button |
| | setting to control any third party |
| | application (via RCT - RecMic |
| | Configuration Tool software) |
| | Dragon Mode (Predefined setting for |
| | Dragon Speech Recognition) |
| | Windows Speech Recognition Mode |
| | (Predefined setting for Windows |
| | Speech Recognition) |
| Recording Scenes | Quiet environment |
| | Noisy environment for Speech |
| | Recognition |

Dictation

Other Features

Automatic stand Available

detection

Automatic microphone Yes, when placing on desk

mute

Specialized features for medical environment

Chemical resistance Ethanol Isopropanol

Antimicrobial Housing Polygiene®

Compatible Software

Olympus RecMic
Configuration Tool
(RCT)
Third party software

Any software which can be controlled via keyboard shortcuts (e.g. Ctrl + H)

Interfaces Input

| Microphone type | Intelligent 2 microphone system |
|-------------------------------|---------------------------------|
| Frequency response | 200 - 9000Hz |
| Microphone sensitivity / gain | - 39dBv |
| Input Level | - 48dBv / + 86dB SPL |
| Signal-to-noise ratio | 59dBA |
| Microphone characteristics | Omni-directional |

Interfaces Output

Speaker 28mm Integrated front loudspeaker
Max. working output 350mW

Power Supply

Standard USB Mode 278mA or less
Low Power USB mode 80mA or less

Dimensions

| Cable length | 2.5m |
|--------------|-------------------------------|
| Height | 171mm |
| Width | 32mm |
| Depth | 43.2mm |
| Weight | 185g including cable |
| | 170g (RM-4100S) |
| | 116g without cable (RM-4010P/ |
| | RM-4015P/RM-4110S) |

Noisy environment for Classic



Exterior

| Housing colour | Black |
|-------------------|-----------------------------------------|
| Symmetric Housing | Suitable for both left and right handed |
| | people |
| Haptics | Smooth Surface coating for minimal |
| | touch noises (UV coated) |
| LED | 7 |

Operating Systems & Requirements

| | • | • | |
|-------------------------------------------|--------|-----|--------------------------------------------------------------------------------|
| Windows | | | Windows 7/8.1/10 |
| System Recoff Olympus Configuration (RCT) | Recl | Mic | |
| Operating s | syster | n: | Microsoft® Windows® 7 • Ultimate/ Enterprise/Professional SP1 (x86/ x64) |
| | | | Microsoft® Windows® 8.1/10 • Enterprise/Pro (x86/x64) |
| CPU: | | | 1GHz or higher |
| Memory: | | | 1 GB or more (x86)/2 GB or more (x64) (Microsoft® Windows® 7/8.1) |
| | | | 2 GB or more (Microsoft® Windows® 10) |
| Hard disk s | pace | | 30 MB or more (A separate space is required to install .NET Framework.) |
| .NET Frame | ework | (| Version: 4.6 |
| Dragon sperecognition | | are | Dragon Professional/Legal v14 - 15 |
| | | | Dragon Medical Practice Edition 2 - 3 |
| | | | |

Box Contents

| Items | Particular RecMic model |
|-------|-----------------------------------|
| | Microphone stand |
| | Quick User Guide (EN/CZ/DK/DE/ES/ |
| | FI/FR/IT/LIT/NL/PL/RUSV) |
| | Olympus RecMic Configuration |
| | Tool (RCT) (to be downloaded from |
| | website) |

Available models

| Models | RM-4010P / RM-4015P |
|--------|---------------------|
| | RM-4100S |
| | RM-4110S |