TECHNICAL **SPECIFICATIONS**

PIXMA TS7450 series

GENERAL SPECIFICATIONS Model Numbers

PRINTER SPECIFICATIONS **Print Resolution** Print Technology Mono Print Speed

Colour Print Speed Photo Print Speed Borderless Printing

Two Sided Printing

CARTRIDGES AND YIELDS Standard Ink Cartridaes

Optional XL Ink Cartridges

Cartridge Yield (Plain paper)

Cartridge Yield (Photo print)

PAPER SUPPORT Paper Types

PIXMATS7450 (BLACK) PIXMATS7451 (WHITE) Wi-Fi, Print, Copy, Scan, Cloud

Up to 4800^[1] x 1200 dpi 2 FINE Cartridges (Black and Colour)

Approx. 13.0 ipm [2] Approx. 6.8 ipm [2]

Borderless 10x15cm: Approx. 43 seconds [2] Yes (A4, B5, Letter, 20x25cm, 13x18cm, 10x15cm, 13x13cm, 8.9x8.9cm, 17.5x25cm, 9.1x5.5cm)

Auto Duplex Print (A4, A5, B5, Letter - plain paper)

PG-560 (Black) CL-561 (Colour) PG-560XL (Black) CL-561XL (Colour)

A4 colour documents printing [3] Black: 180 pages

Black XI: 400 pages Colour: 180 pages Colour XL: 300 pages 10x15cm photo [3] Black: 1408* photos Black XL: 3252* photos Colour: 76 photos

Colour XL: 118 photos * Estimated supplemental yield

Plain Paper

Canon High Resolution Paper (HR-101N) Canon Pro Platinum (PT-101)

Canon Plus Glossy II (PP-201) Canon Pro Luster (LU-101) Canon Plus Semi-gloss (SG-201) Canon "Everyday Use" (GP-501) Canon Matte (MP-101)

T-Shirt Transfer

Envelopes Removable Photo Stickers (RP-101)

Magnetic Photo Paper (MG-101)
Greeting Card (manufactured by Avery and

RedRiverPaper)
Cardstock (manufactured by Neenah Paper and INKPRESS)

Canon Red Label Superior (WOP111) Canon Oce Office Colour Paper (SAT213) Double sided Matte (MP-101D)

Light Fabric Iron-on transfers (LF-101)
Dark Fabric Iron-on transfers (DF-101)

Maximum Paper Input

Automatic Document Feeder Paper Sizes

Rear Tray: Max. 20 sheets (photo paper) or Max. 100 sheets (plain paper)
Front Cassette: Max. 100 sheets (plain paper)

Up to 35 Sheets (1-sided)

Rear Tray:

A4/A5/B5/LTR/LGL/20x25cm/13x18cm/10x15cm/ 13x13cm/8.9x8.9cm/17.5x25cm, 9.1x5.5cm,

Envelopes(DL,COM10)

[Custom size] width 55mm - 215.9 mm.

length 89mm - 676mm

Front Cassette: A4, A5, B5, LTR [Custom size] width 148.0 mm - 215.9 mm,

length 210mm - 297mm

Rear Tray: Plain paper 64 - 105 g/m², Canon photo paper up to 300 a/m² Front Cassette: Plain Paper: 64-105 g/m²

Paper Weight

SCANNER SPECIFICATIONS Scanner Type Scanner Resolution (Optical) Scanning Depth (Input / Output) Maximum Document Size

COPIER SPECIFICATIONS

Copy Speed

Multiple Copy **Copy Functions**

Copy Zoom

INTERFACE

Display Type & Size Display Languages

Interface Type - PC / Mac

Interface Type - Other

Flatbed, ADF and CIS colour scanner

1200 x 2400 dpi [4] Colour: RGB each 16bit/8bit

Grevscale: 16 bit / 8 bit Flatbed: A4, LTR (216x297mm) ADF: A4, LTR, LGL

sFCOT: Approx. 20 sec. [5] sESAT: Approx. 4.0 ipm [5]

Document Copy, 2-sided copy, 2-on-1,

Collated copy (ADFonly)

25 - 400% Fit to page

99 conies max

OLED (1.44 inch)

33 Languages Selectable: Japanese/English (mm & inch)/German/French/Italian/Spanish/Dutch/ Portuguese/Norwegian/Swedish/Danish/Finnish/ Russian/Czech/Hungarian/Polish/Slovene/Turkish/ Greek/Simplified Chinese/Traditional Chinese/ Korean/Indonesian/Slovakian/Estonian/ Latvian/Lithuanian/Ukrainian/Romanian/

Bulgarian/Thai/Croatian/Vietnamese

Hi-Speed USB (B Port)

Wi-Fi: IEEE802.11 b/g/n Wi-Fi Security: WPA-PSK, WPA2-PSK, WEP Wireless LAN Frequency Band: 2.4GHz Canon PRINT Inkjet/SELPHY app

Easy-PhotoPrint Editor Bluetooth

PIXMA Cloud Link Canon Print Service Plugin (Android)

Apple AirPrint Wireless Direct WLAN PictBridge Mopria (Android)



TECHNICAL **SPECIFICATIONS**

PIXMA TS7450 series

SOFTWARE

Supported Operating Systems

Supported Mobile Systems **Operational Requirements**

Software Included

PHYSICAL FEATURES Weight Dimensions (W x D x H) **Acoustic Noise Levels** Recommended Operating Environment **Power Source**

Power Consumption

Windows 10, Windows 8.1, Windows 7 SP1 Operation can only be guaranteed on a PC with pre-installed Windows 7 or later.

macOS 10.12 6~macOS 10.15

iOS, iPadOS, Android, ChromeOS Display: 1024 x 768 XGA Installation: Internet, CD-ROM (Windows) MP Driver including Scanning Utility Easy-PhotoPrint Editor (download)

approx. 8.2 kg approx. 403 x 364 x 206 mm approx. 42.5(A) [6] Temperature: 15-30°C Humidity: 10-80%RH (no dew condensation) AC 100-240V, 50/60Hz Off: Approx. 0.3W Standby (connected to PC via USB): Approx. 0.9W (scanning lamp off)
Standby (all ports connected): Approx. 1.7W (scanning lamp is off)
Time to enter Standby mode: 10min 7sec
Copying: Approx. 14W ^[7]

Footnotes

- [1] Ink droplets can be placed with a minimum pitch of 1/4800 inch
- [2] Document print speeds are the averages of ESAT in Office Category Test for the default simplex mode, ISO/IEC 24734.
- Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host compute
- [3] Declared yield value in accordance with ISO/IEC 24711 standard. Values obtained by continuous printing.
- [4] Optical resolution is a measure of maximum hardware sampling resolution, based on ISO
- 14473 standard. [5] Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183.
- Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
- [4] Acoustic Noise is measured based on ISO7779 standard(colour printing) with default setting. $\ensuremath{^{[7]}}$ When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default
- [8] Some colours may not be available in your region.

Standard disclaimers

All specifications subject to change without notice.

Print speed may vary depending on system configuration, interface, software, document

complexity, print mode, page coverage, type of paper used etc.

Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield Scan speed may vary depending on system configuration, interface, software, scan mode

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

> Canon Inc. canon.com Canon Europe canon-europe.com English edition Canon Europa NV 2020

