#### 5756 DURABLE WHITEBOARD FOAM

Page 1 Issued: 22/10/2009 Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING				
Product name:	5756 DURABLE WHITEBOARD FOAM			
Product code:	5756			
Synonyms:	OTHER PRODUCT REFERENCES: 149-50-033 (21-003)			
Use of substance / preparation:	Cleaning Product			
Company name:	Durable Hunke & Jochheim GmbH			
	Westfalenstrasse 77-79			
	58636 Iserlohn			
	Germany			
	durable-clean@durable.de			
	Tel: 0049 2371 6620			
	Fax: +49 2371 662 311			
	Emergency tel: 0049-2371-662-0			
2. HAZARDS IDENTIFICATION				
Main hazards:	Extremely flammable.			
Other hazards:	Heating may cause an explosion.			
3. COMPOSITION / INFORMATION ON INGREDIENTS				
Hazardous ingredients:	BUTANE 1-10%			
	EINECS: 203-448-7 CAS: 106-97-8			
	[F+] R12			
•	ANIONIC / NON IONIC SURFACTANTS 1-10%			
	[Xi] R36/38			
Contains:	Propane Cas Nr 74-98-6 1-5%			
4. FIRST AID MEASURES (SYMPT	OMS)			
Skin contact:	There may be mild irritation at the site of contact.			
Eye contact:	There may be irritation and redness.			
Ingestion:	There may be irritation of the throat. Nausea and stomach pain may occur. There may be			
	vomiting.			
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or			
	mental confusion may occur.			
4. FIRST AID MEASURES (ACTIO	N)			
Skin contact:	Wash immediately with plenty of soap and water.			
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.			
Ingestion:	Do not induce vomiting. Consult a doctor.			
Inhalation:	Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.			

5756 DURABLE WHITEBOARD FOAM

5. FIRE-FIGHTING MEASURES				
Extinguishing media:	Carbon dioxide. Alcohol or polymer foam.			
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin			
	and eyes.			
6. ACCIDENTAL RELEASE MEAS	URES			
Personal precautions:	Refer to section 8 of SDS for personal protection details.			
Clean-up procedures:	Wash the spillage site with large amounts of water.			
7. HANDLING AND STORAGE				
Handling requirements:	Do not handle in a confined space. Smoking is forbidden.			
Storage conditions:	Store in cool, well ventilated area. Keep away from sources of ignition. Keep away from direct			
	sunlight.			
8. EXPOSURE CONTROLS / PERSONAL PROTECTION				
Hazardous ingredients:	BUTANE			
	WEL (8 hr TWA): 1450 mg/m3 WEL (15 min STEL): 1810 mg/m3			
Engineering measures:	Ensure there is sufficient ventilation of the area.			
Respiratory protection:	Respiratory protection not usually required. Refer to section 15			
Eye protection:	In case of splashing, ensure source of water is to hand, rinse immediately for 15 minutes holding			
	the eyelids open.			
Skin protection:	Avoid skin contact.			
9. PHYSICAL AND CHEMICAL PROPERTIES				
State:	Aerosol			
Colour:	White			
Odour:	Sweet-smelling			
Evaporation rate:	Negligible			
10. STABILITY AND REACTIVITY				
Stability:	Stable under normal conditions.			
	Heat. Direct sunlight. Sources of ignition. Hot surfaces.			
Haz. decomp. products:	In combustion emits toxic fumes.			
11. TOXICOLOGICAL INFORMATIO				
Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.			
12. ECOLOGICAL INFORMATION				
Mobility:	Volatile. Soluble in water.			
Persistence and degradability:	Biodegradable.			
Bioaccumulative potential:	No bioaccumulation potential.			

5756 DURABLE WHITEBOARD FOAM

Other adverse effects: Negligible ecotoxicity.

Transfer to a suitable container and arrange for collection by specialised disposal company.		
Arrange for collection by specialised disposal company.		
The user's attention is drawn to the possible existence of regional or national regulations		
regarding disposal.		
1950 ADR Class: 2		
5A		
AEROSOLS		
2.2		

IMDG / IMO			
UN no:	1950	Class:	2
EmS:	F-D,S-U	Marine pollutant:	
Labelling:	2.2		
IATA / ICAO			
UN no:	1950	Class:	2
Labelling:	2.2		
15. REGULATORY INFORMATION			
Hazard symbols:	Extremely flammable.		
	*		
Risk phrases:	R12: Extremely flammable.		
Safety phrases:	S2: Keep out of the reach of children.		
	S23: Do not breathe vapour.		
	Pressurized container: protect from sunlight and	do not expose to temperatures excee	eding
	50°C. Do not pierce or burn, even after use.		
	Do not spray on a naked flame or any incandesce	ent material. Keep away from source	s of
	ignition - No smoking. Keep out of the reach of ch	ildren.	

5756 DURABLE WHITEBOARD FOAM

	7 % by mass of the contents are flammable.
	S51: Use only in well-ventilated areas.
Precautionary phrases:	Pressurized container: protect from sunlight and do not expose to temperatures exceeding
	50°C. Do not pierce or burn, even after use.
Note:	The regulatory information given above only indicates the principal regulations specifically
	applicable to the product described in the safety data sheet. The user's attention is drawn to
	the possible existence of additional provisions which complete these regulations. Refer to all
	applicable national, international and local regulations or provisions.
16. OTHER INFORMATION	
Risk phrases used in s.3:	R12: Extremely flammable.
	R36/38: Irritating to eyes and skin.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and shall
	be used only as a guide. This company shall not be held liable for any damage resulting from
	handling or from contact with the above product.

[final page]