PORTWEST®



A109 - Grip Glove (Retail Pack)

Collection: General Handling Range: Hand Protection Materials: Polyester, Elastic

Dipping:

Inner Pack: 12 Outer Carton: 216



Premium quality latex palm dipped 10 gauge glove which provides good tear and abrasion resistance, for secure handling in both wet and dry conditions. Open back for ventilation and ergonomic design to reduce hand fatigue. Supplied in an individual pack for retail display.

General Handling

The general handling and grip glove category is one of the most popular collections within the Portwest hand protection range. A carefully selected range of coatings, including latex, nitrile, polyurethane and PVC, provides a broad range of styles suited to a diverse range of tasks.

Hand Protection

A wide and increasing range of hand protection products is available. In order to help cater to every need. Only the best materials and manufacturing methods are used in the production of Portwests' extensive range of Hand Protection products....

Standards

EN ISO 21420: 2020 Dexterity 4 EN 388: 2016 + A1: 2018 (2143A) ANSI/ISEA 105: 2016 CUT Level (A1)



Features

- Crinkle latex grip offers excellent grip
- Tough 10 gauge liner
- Breathable seamless liner
- Palm dipped to increase dexterity and ventilation
- Open back for breathability
- \bullet The essential construction glove
- Retail tag which aids presentation for retail sales
- CE certified
- UKCA marked

PORTWEST®



A109 - Grip Glove (Retail Pack) Commodity Code: 6116102091

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)

Bracetown Business Park

D15 YN2P, Ireland

Cert No: 2777/14699-01/E00-00

SATRA Technology Centre Ltd (Notified Body No.: AB: 0321)

SATRA Technology Park NN16 8SD, United Kingdom

Cert No: AB0321/21064-01/E00-00

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
A109ORRM	Orange	59.0	28.0	50.0	0.0880	0.0826	5036108150373	25036108603323
A109ORRL	Orange	59.0	28.0	50.0	0.0980	0.0826	5036108150380	25036108603316
A109ORRXL	Orange	59.0	28.0	50.0	0.1060	0.0826	5036108150397	25036108603330