

FW34 - Steelite Lusum Safety Trainer S1P HRO

Collection: Steelite™ Work

Upper: Cow Suede Leather

Sole: EVA/Rubber

Outer Carton: 12

Steelite™ Work

Fully Compliant with all current standards, ideal for industrial wear with a strong and flexible construction.

Foot Protection

Innovation, design, styling and quality components define the Portwest foot protection collection.



Standards

EN ISO 20345: 2011 S1P
AS 2210.3

Features

- Reinforced ankle protection
- Available in a selection of bright colours
- Suede and textile upper
- Padded collar for added comfort
- Made with cow suede leather for a premium finish
- Cemented construction
- Removable EVA cushion footbed
- New colour
- Lightweight EVA cushioned midsole
- CE certified
- UKCA marked

FW34 - Steelite Lusum Safety Trainer S1P HRO Commodity Code: 6403400000

Test House

Intertek Italia S.p.A. (Notified Body No.: NB: 2575)
Via Guido Miglioli 2/A,
-, Italy
Cert No: LECFI00381300

ITS Testing Services (UK) Ltd. (Intertek) (Notified Body No.: 0362)
Centre Court
LE19 1WD, UK
Cert No: LECFI00383272

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
FW34RER36	Red	64.0	42.0	38.0	1.1000	0.1021	5036108251742	25036108740479
FW34RER37	Red	64.0	42.0	38.0	1.0900	0.1021	5036108251759	25036108740486
FW34RER38	Red	64.0	42.0	38.0	1.1400	0.1021	5036108251766	25036108740493
FW34RER39	Red	64.0	42.0	32.0	1.1700	0.0860	5036108251773	25036108740509
FW34RER40	Red	64.0	42.0	38.0	1.2100	0.1021	5036108251780	25036108740516
FW34RER41	Red	64.0	42.0	38.0	1.2400	0.1021	5036108251797	25036108740523
FW34RER42	Red	68.0	44.0	38.0	1.2600	0.1137	5036108251803	25036108740530
FW34RER43	Red	68.0	44.0	38.0	1.4200	0.1137	5036108251810	25036108740547
FW34RER44	Red	68.0	44.0	38.0	1.3600	0.1137	5036108251827	25036108740554
FW34RER45	Red	68.0	44.0	38.0	1.3600	0.1137	5036108251834	25036108740561
FW34RER46	Red	71.0	44.0	39.0	1.4400	0.1218	5036108251841	25036108740578
FW34RER47	Red	71.0	44.0	39.0	1.5100	0.1218	5036108251858	25036108740585
FW34RER48	Red	71.0	44.0	39.0	1.5400	0.1218	5036108251865	25036108740592