

P306 - FFP3 Ultimate Valved Reusable Respirator (Pk5)

Collection: Disposable Mask FFP3

Range: Disposable Masks

Materials: PP, EVA Foam

Inner Pack: 5

Outer Carton: 12

Product information

Experience ultimate comfort and protection with our FFP3 valved respirator. With low breathing resistance, an innovative moulded nose bridge, and an all-round foam gasket, it's ergonomically designed to fit most face shapes. The wide adjustable elastic head straps provide a secure and comfortable fit, while the high-performing exhalation valve efficiently reduces heat and moisture inside the mask. R D certified reusable for more than one working shift, and with a Dolomite clogging test for maximised breathing comfort, it's the perfect choice for your respiratory needs.



Disposable Mask FFP3

Disposable mask FFP3 level, protects against solid and liquid particles of high toxicity. Minimal % of filtration 99%. Protects up to 20 times the TLV (Assigned Protection Factor for FFP3 masks) or up to 50 times TLV (Nominal Protection Factor for FFP3 masks). Examples of applications: Sanding of hard wood (beech, oak) / treatment of wood using copper, chrome or arsenic based products / impact stripping of paint / sanding of cement. Exceptional quality and performance are ensured across our range of disposable masks.

Disposable Masks

Our Biztex® brand ensures exceptional quality and performance across our full range of disposable masks. The extensive Biztex® range offers a high level of protection and quality safeguarding the wearer against many workplace risks including liquid chemicals, static electricity, dry particles and radioactive contamination. The complete Biztex® range includes disposable masks and limited-life garments.

Standards

EN 149:2001 +A1:2009 FFP3 (R D)

Features

- Reusable for more than one working shift
- Excellent face fit test performance
- Internal foam gasket ensures a tight face seal
- Wide adjustable head straps for ultimate wearer comfort
- Soft nose bridge for a secure and comfortable fit
- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- 100% metal free
- Dolomite optional clogging test (D) to provide more comfortable breathing and longer lasting filtration performance
- Retail box which aids presentation for retail sales
- CE certified
- UKCA marked

P306 - FFP3 Ultimate Valved Reusable Respirator (Pk5) **Commodity Code: 6307909311**

Test House

INSPEC International B.V. (Notified Body No.: NB: 2849)
Beechavenue 54 - 62
, Netherlands
Cert No: PPE23162519

INSPEC International Ltd. (Notified Body No.: AB: 0194)
56 Leslie Hough Way
M6 6AJ, UK
Cert No: UKCA-B-231362

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
P306WHR	White	44.0	40.0	33.0	0.2500	0.0581	5036108400485	25036108885309