

Pelikan Hardcopy Production AG
8620 Wetzikon

Date printed 03.08.2016, Revision 03.08.2016

Version 04. Supersedes version: 03

Page 1 / 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

22-467

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Ink

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Pelikan Hardcopy Production AG
Haldenstrasse 28
8620 Wetzikon / SWITZERLAND
Phone +41 (0) 44 9861-299

Address enquiries to

Technical information

Safety Data Sheet sdb@chemiebuero.de

1.4 Emergency telephone number

Company +41 (0) 44 9861-299 Mo-Fr 8:00-17:00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

No classification.

2.2 Label elements

Hazard pictograms

Hazard statements none

Special labelling EUH210 Safety data sheet available on request.

2.3 Other hazards

Human health dangers Frequent persistent contact with the skin can cause skin irritation.

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards Further hazards were not determined with the current level of knowledge.

Pelikan Hardcopy Production AG
8620 Wetzikon

Date printed 03.08.2016, Revision 03.08.2016

Version 04. Supersedes version: 03

Page 2 / 11

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
1 - <10	Ethylene glycol
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1
	GHS/CLP: Acute Tox. 4: H302 - STOT RE 2: H373
1 - <10	2,2'-oxybisethanol
	CAS: 111-46-6, EINECS/ELINCS: 203-872-2, EU-INDEX: 603-140-00-6
	GHS/CLP: Acute Tox. 4: H302 - STOT RE 2: H373
1 - <5	2-(2-Butoxyethoxy)ethanol
	CAS: 112-34-5, EINECS/ELINCS: 203-961-6, EU-INDEX: 603-096-00-8, Reg-No.: 01-2119475104-44-xxxx
	GHS/CLP: Eye Irrit. 2: H319

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Take off contaminated clothing and wash before reuse.

Inhalation

Ensure supply of fresh air.
In the event of symptoms seek medical treatment.

Skin contact

When in contact with the skin, clean with soap and water.
Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion

Seek medical advice immediately.
Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Product itself is non-combustible. Fire extinguishing method of surrounding areas must be considered.

Extinguishing media that must not be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Not combusted hydrocarbons.
Nitrogen oxides (NOx).

5.3 Advice for firefighters

Use self-contained breathing apparatus.
Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

Pelikan Hardcopy Production AG
8620 Wetzikon

Date printed 03.08.2016, Revision 03.08.2016

Version 04. Supersedes version: 03

Page 3 / 11

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Ensure adequate ventilation.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up mechanically.
Take up residues with absorbent material (e.g. sand, sawdust, general-purpose binder).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

The normal safety precautions for handling chemicals must be observed.
The product is not combustible.
Wash hands before breaks and after work.
Use barrier skin cream.
Take off contaminated clothing and wash before reuse.
Do not eat, drink, smoke or take drugs at work.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Do not store together with food and animal food/diet.
Keep container in a well-ventilated place.
Keep container tightly closed.
Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2

Pelikan Hardcopy Production AG
8620 Wetzikon

Date printed 03.08.2016, Revision 03.08.2016

Version 04. Supersedes version: 03

Page 4 / 11

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Glycerol
CAS: 56-81-5, EINECS/ELINCS: 200-289-5
Long-term exposure: 10 mg/m ³ , (mist)
2-(2-Butoxyethoxy)ethanol
CAS: 112-34-5, EINECS/ELINCS: 203-961-6, EU-INDEX: 603-096-00-8, Reg-No.: 01-2119475104-44-xxxx
Long-term exposure: 10 ppm, 67,5 mg/m ³
Short-term exposure (15-minute): 15 ppm, 101,2 mg/m ³
2,2' -oxybisethanol
CAS: 111-46-6, EINECS/ELINCS: 203-872-2, EU-INDEX: 603-140-00-6
Long-term exposure: 23 ppm, 101 mg/m ³
Ethylene glycol
CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1
Long-term exposure: 20 ppm, 52 mg/m ³ , Vapour, particulate: 10 mg/m ³
Short-term exposure (15-minute): 40 ppm, 104 mg/m ³

Ingredients with occupational exposure limits to be monitored (EU)

Substance / EC LIMIT VALUES
2-(2-Butoxyethoxy)ethanol
CAS: 112-34-5, EINECS/ELINCS: 203-961-6, EU-INDEX: 603-096-00-8, Reg-No.: 01-2119475104-44-xxxx
Eight hours: 10 ppm, 67,5 mg/m ³
Short-term (15-minute): 15 ppm, 101,2 mg/m ³
Ethylene glycol
CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1
Eight hours: 20 ppm, 52 mg/m ³ , H
Short-term (15-minute): 40 ppm, 104 mg/m ³

DNEL

Substance
2-(2-Butoxyethoxy)ethanol, CAS: 112-34-5
worker, inhalative, Long-term - systemic effects: 67,5 mg/m ³ .
worker, dermal, Long-term - systemic effects: 83 mg/kg bw/day.
worker, inhalative, Long-term - local effects: 67,5 mg/m ³ .
worker, inhalative, Acute - local effects: 101,2 mg/m ³ .
general population, inhalative, Acute - local effects: 60,7 mg/m ³ .
general population, inhalative, Long-term - systemic effects: 40,5 mg/m ³ .
general population, dermal, Long-term - systemic effects: 50 mg/kg bw/day.
general population, inhalative, Long-term - local effects: 40,5 mg/m ³ .
general population, oral, Long-term - systemic effects: 5 mg/kg bw/day.

PNEC

Substance
2-(2-Butoxyethoxy)ethanol, CAS: 112-34-5
freshwater, 1,1 mg/l.
seawater, 0,11 mg/l.
sediment (freshwater), 4,4 mg/kg.

Pelikan Hardcopy Production AG
8620 Wetzikon

Date printed 03.08.2016, Revision 03.08.2016

Version 04. Supersedes version: 03

Page 5 / 11

sediment (seawater), 0,44 mg/kg.

sewage treatment plants (STP), 200 mg/l.

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	0,4mm butyl rubber, > 120 min (EN 374) The details concerned are recommendations. Please contact the glove supplier for further information.
Skin protection	Protective clothing.
Other	Avoid contact with eyes and skin.
Respiratory protection	Not required under normal conditions.
Thermal hazards	none
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Color	yellow
Odor	characteristic
Odour threshold	not applicable
pH-value	8,6
pH-value [1%]	not determined
Boiling point [°C]	> 100
Flash point [°C]	not applicable
Flammability (solid, gas) [°C]	not applicable
Lower explosion limit	not applicable
Upper explosion limit	not applicable
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	not determined
Density [g/ml]	1,07 (25°C / 77,0°F)
Bulk density [kg/m³]	not applicable
Solubility in water	miscible
Partition coefficient [n-octanol/water]	not determined
Viscosity	2,29 mm²/s (25°C)
Relative vapour density determined in air	not applicable
Evaporation speed	not applicable
Melting point [°C]	< 0
Autoignition temperature [°C]	not applicable
Decomposition temperature [°C]	not determined

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

Pelikan Hardcopy Production AG
8620 Wetzikon

Date printed 03.08.2016, Revision 03.08.2016

Version 04. Supersedes version: 03

Page 6 / 11

10.2 Chemical stability

The product is stable under standard conditions.

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.

Pelikan Hardcopy Production AG
8620 Wetzikon

Date printed 03.08.2016, Revision 03.08.2016

Version 04. Supersedes version: 03

Page 7 / 11

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product
ATE-mix, inhalative, > 20 mg/l 4h.
ATE-mix, dermal, > 2000 mg/kg.
ATE-mix, oral, > 2000 mg/kg.
Substance
2-(2-Butoxyethoxy)ethanol, CAS: 112-34-5
LD50, dermal, Rabbit: 4000 mg/kg.
LD50, oral, Rat: 5660 mg/kg.
Ethylene glycol, CAS: 107-21-1
LD50, dermal, Rabbit: 10600 mg/kg bw.
LD50, oral, Rat: 4700 mg/kg bw.
2,2' -oxybisethanol, CAS: 111-46-6
LD50, dermal, Rabbit: 13300 mg/kg.
LD50, oral, Rat (male): 19600 mg/kg.
LC50, inhalative, Rat: > 4,6 mg/l 4h.

Serious eye damage/irritation	Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Skin corrosion/irritation	Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Respiratory or skin sensitisation	Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Specific target organ toxicity — single exposure	Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Specific target organ toxicity — repeated exposure	Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Mutagenicity	Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Reproduction toxicity	Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Carcinogenicity	Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Aspiration hazard	Does not contain a relevant substance that meets the classification criteria.
General remarks	

none

Pelikan Hardcopy Production AG
8620 Wetzikon

Date printed 03.08.2016, Revision 03.08.2016

Version 04. Supersedes version: 03

Page 8 / 11

SECTION 12: Ecological information

12.1 Toxicity

Substance
2-(2-Butoxyethoxy)ethanol, CAS: 112-34-5
LC50, (96h), <i>Lepomis macrochirus</i> : 1300 mg/l (IUCLID).
EC50, (48h), <i>Daphnia magna</i> : > 100 mg/l (IUCLID).
Ethylene glycol, CAS: 107-21-1
LC50, (96h), <i>Pimephales promelas</i> : >10000 mg/l.
EC50, (72h), <i>Pseudokirchneriella subcapitata</i> : >1000 mg/l.
EC50, (48h), <i>Daphnia magna</i> : 34440 mg/l.
NOEC, <i>Daphnia magna</i> : 24000 mg/l.
NOEC, fish: 6090 mg/l.
2,2' -oxybisethanol, CAS: 111-46-6
LC50, (96h), <i>Pimephales promelas</i> : 75200 mg/l.
EC50, (96h), <i>Pseudokirchneriella subcapitata</i> : > 100 mg/l.
EC50, (48h), <i>Daphnia magna</i> : 48900 mg/l.

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

Accumulation in organisms is not expected.

12.4 Mobility in soil

Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the authorities if necessary.

Waste no. (recommended)

080313

Contaminated packaging

Packaging that cannot be cleaned should be disposed of as for product.
Uncontaminated packaging may be taken for recycling.

Waste no. (recommended)

150102

Pelikan Hardcopy Production AG
8620 Wetzikon

Date printed 03.08.2016, Revision 03.08.2016

Version 04. Supersedes version: 03

Page 9 / 11

SECTION 14: Transport information

14.1 UN number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

Pelikan Hardcopy Production AG
8620 Wetzikon

Date printed 03.08.2016, Revision 03.08.2016

Version 04. Supersedes version: 03

Page 10 / 11

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC; (EU) 2015/830

TRANSPORT-REGULATIONS DOT-Classification, ADR (2015); IMDG-Code (2015, 37. Amdt.); IATA-DGR (2016).

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011). CHIP 3/ CHIP 4

- Observe employment restrictions for people none

- VOC (2010/75/CE) < 1 %

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

**16.1 Hazard statements
(SECTION 03)**

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.
(kidneys)

H373 May cause damage to organs through prolonged or repeated exposure.
H302 Harmful if swallowed.

Pelikan Hardcopy Production AG**8620 Wetzikon**

Date printed 03.08.2016, Revision 03.08.2016

Version 04. Supersedes version: 03

Page 11 / 11

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging
 DMEL = Derived Minimum Effect Level
 DNEL = Derived No Effect Level
 EC50 = Median effective concentration
 ECB = European Chemicals Bureau
 EEC = European Economic Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 ELINCS = European List of Notified Chemical Substances
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IC50 = Inhibition concentration, 50%
 IMDG = International Maritime Code for Dangerous Goods
 IUCLID = International Uniform Chemical Information Database
 LC50 = Lethal concentration, 50%
 LD50 = Median lethal dose
 MARPOL = International Convention for the Prevention of Marine Pollution from Ships
 PBT = Persistent, Bioaccumulative and Toxic substance
 PNEC = Predicted No-Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
 TLV®/TWA = Threshold limit value – time-weighted average
 TLV®STEL = Threshold limit value – short-time exposure limit
 VOC = Volatile Organic Compounds
 vPvB = very Persistent and very Bioaccumulative

16.3 Other information**Classification procedure****Modified position**

SECTION 15 been added: EUH210 Safety data sheet available on request.

SECTION 2 deleted: P501 Dispose of contents/container to in accordance with local/regional/national/international regulation.

SECTION 2 deleted: P314 Get medical advice / attention if you feel unwell.

SECTION 2 deleted: P102 Keep out of reach of children.

SECTION 2 deleted: P101 If medical advice is needed, have product container or label at hand.

SECTION 2 deleted: STOT RE 2

SECTION 2 deleted: H373 May cause damage to organs through prolonged or repeated exposure if swallowed. (kidneys)

SECTION 2 deleted: WARNING

SECTION 2 deleted: health hazard

SECTION 8 been added: Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.

SECTION 12 been added: Spillages may penetrate the soil causing ground water contamination.

SECTION 13 been added:

SECTION 16 deleted: Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.



Copyright: Chemiebuero®

