ISO/IEC 19752 Declaration of Yield

For Monochrome Toner Laser Cartridges

Description: Monochrome: Brother HL-5200/5240/5250/5270/5280

prp

	RPS PN:	Monochrome 628473 TN3170						Average Continuous Composite Crtg Yields						
OEM Equiv.: OEM Yield Spec.:		7000						к 7200						
Pa	ge Yield I	nformation:												
Color	Yield Average	Standard Deviation	90% Lower Confidence	90% Upper Confidence	Printer 1 Test 1	Printer 1 Test 2	Printer 1 Test 3	Printer 2 Test 1	Printer 2 Test 2	Printer 2 Test 3	Printer 3 Test 1	Printer 3 Test 2	Printer 3 Test 3	
Black/Monochrome	7389	298	7204	7574	7630	7111	7520	7010	7765	7210	7500	7040	7714	
Dates of Test:			Start Date 28/05/2012		End Date 13/08/2012		Printer 3			Computer model: PC Software used/Driver version: PCL 6 Operating system: Windows 7 32-bit				
			Printer 1		Printer 2				r		Printer model: HP M 506 Version of PDF Reader: Adobe Reader 11			
Pi	rinter Ser	ial Number:	E66602FOJ645358		E63658L8J840419		E63658L8J840407		l		Power (off/on) Everyday: Yes			
Average Conditions of test T °C / %RH: 24 °C 42 %											Number of Cartridges sets Used in Testing: 9 Number of Cartridges sets Used in Calculations: 9 Shake Procedure Used? When aplicable,at 1st and 2nd fade			
Brief T	echnical i	information										Num		Print Mode: Continuous Jsed in Testing: 3 Media Used: A4 Paper Weight: 80 gsm

All Products with dates of release after the ISO standards 19752 (for monochrome crtgs) and 19798 (for color crtgs) have been tested follo wing these same standards. For other products this type of analysis has only been made when major changes to configurations has been done in any of the manufacturing locations.

Please note:

These products are not related or affiliated with any of the above trade marks referenced in models descriptions. These trademarks are only mentioned for a clear identification of the remanufactured product tested.