Manufacturer (trade mark):	PRPS	Type/Model OEM:	TN326BK
Lot/Part number:	*4236845*	Toner color(s):	BLACK
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	4000		
Test device:	E73444A5J184060 / E73444A5J184051 / E73444C5J197444	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test climate:			
Temperature:	23	Relative humidity:	47
Deviations of the determined test conditions			
Tester 1):	Aleksandar Kojic	Test location 2):	SERBIA
Test date:	22/04/2016		

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation		Charge/Serial number
1	4009	Yes		Sample 1
2	4005	Yes		Sample 2
3	4005	Yes	We use for A1 the	Sample 3
4	4007	Yes	MAX, for A2 the	Sample 4
5	4008	Yes	MEDIAN and for A3 the	Sample 5
6	4007	Yes	MIN value of the list at	Sample 6
7	4007	Yes	left	Sample 7
8	4009	Yes		Sample 8
9	4009	Yes		Sample 9

Comparing Sample (B)	Type	Used for valuation		Charge/Serial number
1	4000	Yes/no	Yes	OEM Sample/Spec
2	4000	Yes/no	Yes	OEM Sample/Spec
3	4000	Yes/no	Yes	OEM Sample/Spec
4		Yes/no		
5		Yes/no		

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?	Yes/no	Yes
If there are no information of the AMES test in the EG Safety Data Sheet Is there a test report about the AMES test of the used toner?	Yes/no	Not Aplicable
If not: Description	All MSDSs mention Ames test	

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?	Yes/no	Yes
Is the interaction between printer and toner module acceptable?	Yes/no	Yes
If not: Description		

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?	Yes/no	Yes
If not: Describe fault		

Checking the yield number (5.5) **BLACK**

	1	2	3	Average (Ā or V)
Yield A: (A1+A2+A3)/3= Ā	4009	4007	4005	4007
Yield V: (V1+V2+V3)/3=V	4000	4000	4000	4000

Alternative:

Yield A: Result of test after ISO/IEC 19752 Ā	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 V	
Reference to the test protocol:	
Test date:	
Result: EZ=Ā/V	1,00

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	20,8		
Average value of the 2 areas F comparing print V1:	23,6		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	2,8	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	21,2		
Average value of the 2 areas F comparing print V2:	23,6		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	2,4	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	20,2		
Average value of the 2 areas F comparing print V3:	23,5		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	3,3	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3) **BLACK**

Test print A1

Color values 1 6 A F	1	6	A	F
after 50 pages	80,4	63,6	47,2	22,7
Color values 1 6 A F	1	6	A	F
The biggest deviation	0,8	1,9	2,5	2,9

Comparing print V1

Color values 1 6 A F	1	6	A	F
after 50 pages	82,2	66,3	49,1	25,5

Color values 1 6 A F	1	6	A	F
The biggest deviation	1,3	4,1	3,2	3,3
Result determination	1	6	A	F
Difference ΔL≤8	0,5	2,2	0,7	0,4
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 BLACK

Color values 1 6 A F	1	6	A	F
after 50 pages	79,6	62,5	46,1	23,6
Color values 1 6 A F	1	6	A	F
The biggest deviation	1,8	1,2	1,2	3,9

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	82,2	65,7	47,8	26
Color values 1 6 A F	1	6	A	F
The biggest deviation	1,5	4,2	1,8	4
Result determination	1	6	A	F
Difference ΔL≤8	0	3	0,6	0,1
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 BLACK

Color values 1 6 A F	1	6	A	F
after 50 pages	77,5	57,4	42,7	21,8
Color values 1 6 A F	1	6	A	F
The biggest deviation	1	2,5	1,6	2,5

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	81,3	66,3	48,7	26
Color values 1 6 A F	1	6	A	F
The biggest deviation	1,7	7,2	4,5	3,7
Result determination	1	6	A	F
Difference ΔL≤8	0,7	4,7	2,9	1,2
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesition
Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes
If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)
Are the color diferences in between the acceptable parameters (pattern B2-B5) ΔE≤8 ? Yes
If not: Describe deviation

Checking the background (5.6.6)
Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes
If not: Describe deviation

Checking the ghosting (5.6.7)
Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes
If not: Describe deviation

Checking toner miscibility (5.6.8)
Is the toner miscibility given? N/A
If not: Describe deviation

OVERALL RESULT: **Passed**

Manufacturer (trade mark):	**PRPS**	Type/Model OEM:	TN326C
Lot/Part number:	***4236852***	Toner color(s):	**CYAN**
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	3500		
Test device:	E73444A5J184060 / E73444A5J184051 / E73444C5J197444	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test climate:			
Temperature:	23	Relative humidity:	47
Deviations of the determined test conditions			
Tester 1):	Aleksandar Kojic	Test location 2):	**SERBIA**
Test date:	**22/04/2016**		

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation		Charge/Serial number
1	3508	Yes		Sample 1
2	3510	Yes		Sample 2
3	3508	Yes	We use for A1 the	Sample 3
4	3512	Yes	MAX, for A2 the	Sample 4
5	3510	Yes	MEDIAN and for A3 the	Sample 5
6	3508	Yes	MIN value of the list at	Sample 6
7	3508	Yes	left	Sample 7
8	3510	Yes		Sample 8
9	3510	Yes		Sample 9

Comparing Sample (B)	Type	Used for valuation		Charge/Serial number
1	3500	Yes/no	Yes	OEM Sample/Spec
2	3500	Yes/no	Yes	OEM Sample/Spec
3	3500	Yes/no	Yes	OEM Sample/Spec
4		Yes/no		
5		Yes/no		

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?	Yes/no	Yes
If there are no information of the AMES test in the EG Safety Data Sheet Is there a test report about the AMES test of the used toner?	Yes/no	Not Aplicable
If not: Description	All MSDSs mention Ames test	

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?	Yes/no	Yes
Is the interaction between printer and toner module acceptable?	Yes/no	Yes
If not: Description		

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?	Yes/no	Yes
If not: Describe fault		

Checking the yield number (5.5) **CYAN**

	1	2	3	Average (Ā or V)
Yield A: (A1+A2+A3)/3= Ā	3512	3510	3508	3510
Yield V: (V1+V2+V3)/3=V	3500	3500	3500	3500
Alternative:				
Yield A: Result of test after ISO/IEC 19752 Ā				
Reference to the test protocol:				
Test date:				
Yield V: Result of test after ISO/IEC 19752 V				
Reference to the test protocol:				
Test date:				
Result: EZ=Ā/V				1,00

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	45,6		
Average value of the 2 areas F comparing print V1:	51		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	5,4	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	46,8		
Average value of the 2 areas F comparing print V2:	50,9		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	4,1	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	42,6		
Average value of the 2 areas F comparing print V3:	50,1		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	7,5	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3) **CYAN**

Test print A1				
Color values 1 6 A F	1	6	A	F
after 50 pages	84,7	70	51,1	48,4
Color values 1 6 A F	1	6	A	F
The biggest deviation	1,5	4,1	5	4,9
Comparing print V1				
Color values 1 6 A F	1	6	A	F
after 50 pages	87,6	72,2	55,2	51,7

Color values 1 6 A F	1	6	A	F
The biggest deviation	1,5	1,2	1,6	2,3
Result determination	1	6	A	F
Difference ΔL≤8	0	2,9	3,4	2,6
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 CYAN

Color values 1 6 A F	1	6	A	F
after 50 pages	84,5	68,8	53	50,1
Color values 1 6 A F	1	6	A	F
The biggest deviation	2,9	4,8	7,5	6,4

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	86,8	71,1	54,9	51,3
Color values 1 6 A F	1	6	A	F
The biggest deviation	1,2	1,1	1,8	2,3
Result determination	1	6	A	F
Difference ΔL≤8	2	3,7	5,7	4,1
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 CYAN

Color values 1 6 A F	1	6	A	F
after 50 pages	80,4	63,3	46,8	44,5
Color values 1 6 A F	1	6	A	F
The biggest deviation	2,4	3,5	4	3,1

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	86,1	71,1	54,3	51,3
Color values 1 6 A F	1	6	A	F
The biggest deviation	0,9	1,9	2,1	2,2
Result determination	1	6	A	F
Difference ΔL≤8	1,5	1,6	1,9	0,9
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesition
Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes
If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)
Are the color diferences in between the acceptable parameters (pattern B2-B5) ΔE≤8 ? Yes
If not: Describe deviation

Checking the background (5.6.6)
Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes
If not: Describe deviation

Checking the ghosting (5.6.7)
Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes
If not: Describe deviation

Checking toner miscibility (5.6.8)
Is the toner miscibility given? N/A
If not: Describe deviation

OVERALL RESULT: **Passed**

Manufacturer (trade mark):	PRPS	Type/Model OEM:	TN326M
Lot/Part number:	*4236869*	Toner color(s):	MAGENTA
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	3500		
Test device:	E73444A5J184060 / E73444A5J184051 / E73444C5J197444	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test climate:			
Temperature:	23	Relative humidity:	47
Deviations of the determined test conditions			
Tester 1):	Aleksandar Kojic	Test location 2):	SERBIA
Test date:	22/04/2016		

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation		Charge/Serial number
1	3508	Yes		Sample 1
2	3510	Yes		Sample 2
3	3510	Yes	We use for A1 the	Sample 3
4	3508	Yes	MAX, for A2 the	Sample 4
5	3508	Yes	MEDIAN and for A3 the	Sample 5
6	3509	Yes	MIN value of the list at	Sample 6
7	3508	Yes	left	Sample 7
8	3510	Yes		Sample 8
9	3510	Yes		Sample 9

Comparing Sample (B)	Type	Used for valuation		Charge/Serial number
1	3500	Yes/no	Yes	OEM Sample/Spec
2	3500	Yes/no	Yes	OEM Sample/Spec
3	3500	Yes/no	Yes	OEM Sample/Spec
4		Yes/no		
5		Yes/no		

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?	Yes/no	Yes
If there are no information of the AMES test in the EG Safety Data Sheet Is there a test report about the AMES test of the used toner?	Yes/no	Not Aplicable
If not: Description	All MSDSs mention Ames test	

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?	Yes/no	Yes
Is the interaction between printer and toner module acceptable?	Yes/no	Yes
If not: Description		

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?	Yes/no	Yes
If not: Describe fault		

Checking the yield number (5.5) — **MAGENTA**

	1	2	3	Average (Ā or V)
Yield A: (A1+A2+A3)/3= Ā	3510	3509	3508	3509
Yield V: (V1+V2+V3)/3=V	3500	3500	3500	3500
Alternative:				
Yield A: Result of test after ISO/IEC 19752 Ā				
Reference to the test protocol:				
Test date:				
Yield V: Result of test after ISO/IEC 19752 V				
Reference to the test protocol:				
Test date:				
Result: EZ=Ā/V				1,00

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	45,8		
Average value of the 2 areas F comparing print V1:	46,9		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	1,1	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	45,4		
Average value of the 2 areas F comparing print V2:	46,7		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	1,3	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	44,4		
Average value of the 2 areas F comparing print V3:	46,6		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	2,2	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3) — **MAGENTA**

Test print A1				
Color values 1 6 A F	1	6	A	F
after 50 pages	85,8	73,5	61,9	47
Color values 1 6 A F	1	6	A	F
The biggest deviation	1,5	3,5	4,2	2,3
Comparing print V1				
Color values 1 6 A F	1	6	A	F
after 50 pages	88,3	75	62,3	47,8

Color values 1 6 A F	1	6	A	F
The biggest deviation	0,8	2,5	2,2	1,4
Result determination	1	6	A	F
Difference ΔL≤8	0,7	1	2	0,9
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 MAGENTA

Color values 1 6 A F	1	6	A	F
after 50 pages	85,8	72,6	61,5	47
Color values 1 6 A F	1	6	A	F
The biggest deviation	2,7	3,5	4,1	3

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	88,9	73,9	61,7	47,4
Color values 1 6 A F	1	6	A	F
The biggest deviation	0,8	2,5	2,5	1,3
Result determination	1	6	A	F
Difference ΔL≤8	2	1	1,6	1,7
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 MAGENTA

Color values 1 6 A F	1	6	A	F
after 50 pages	86,2	71,2	60,9	45,4
Color values 1 6 A F	1	6	A	F
The biggest deviation	2,6	3,2	5,2	1,8

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	88,2	74	61,7	47,4
Color values 1 6 A F	1	6	A	F
The biggest deviation	1,7	2,9	2,7	1,4
Result determination	1	6	A	F
Difference ΔL≤8	0,9	0,3	2,5	0,4
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesition
Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes
If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)
Are the color diferences in between the acceptable parameters (pattern B2-B5) ΔE≤8 ? Yes
If not: Describe deviation

Checking the background (5.6.6)
Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes
If not: Describe deviation

Checking the ghosting (5.6.7)
Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes
If not: Describe deviation

Checking toner miscibility (5.6.8)
Is the toner miscibility given? N/A
If not: Describe deviation

OVERALL RESULT: **Passed**

Manufacturer (trade mark):	**PRPS**	Type/Model OEM:	TN326Y
Lot/Part number:	***4236876***	Toner color(s):	**YELLOW**
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	3500		
Test device:	E73444A5J184060 / E73444A5J184051 / E73444C5J197444	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test climate:			
Temperature:	23	Relative humidity:	47
Deviations of the determined test conditions			
Tester 1):	Aleksandar Kojic	Test location 2):	**SERBIA**
Test date:	**22/04/2016**		

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation		Charge/Serial number
1	3500	Yes		Sample 1
2	3501	Yes		Sample 2
3	3501	Yes	We use for A1 the	Sample 3
4	3501	Yes	MAX, for A2 the	Sample 4
5	3502	Yes	MEDIAN and for A3 the	Sample 5
6	3503	Yes	MIN value of the list at	Sample 6
7	3500	Yes	left	Sample 7
8	3501	Yes		Sample 8
9	3503	Yes		Sample 9

Comparing Sample (B)	Type	Used for valuation		Charge/Serial number
1	3500	Yes/no	Yes	OEM Sample/Spec
2	3500	Yes/no	Yes	OEM Sample/Spec
3	3500	Yes/no	Yes	OEM Sample/Spec
4		Yes/no		
5		Yes/no		

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?	Yes/no	Yes
If there are no information of the AMES test in the EG Safety Data Sheet		
Is there a test report about the AMES test of the used toner?	Yes/no	Not Aplicable
If not: Description	All MSDSs mention Ames test	

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?	Yes/no	Yes
Is the interaction between printer and toner module acceptable?	Yes/no	Yes
If not: Description		

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?	Yes/no	Yes
If not: Describe fault		

Checking the yield number (5.5) **YELLOW**

	1	2	3	Average (Ā or V)
Yield A: (A1+A2+A3)/3= Ā	3503	3501	3500	3501
Yield V: (V1+V2+V3)/3=V	3500	3500	3500	3500
Alternative:				
Yield A: Result of test after ISO/IEC 19752 Ā				
Reference to the test protocol:				
Test date:				
Yield V: Result of test after ISO/IEC 19752 V				
Reference to the test protocol:				
Test date:				
Result: EZ=Ā/V				1,00

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	82,8		
Average value of the 2 areas F comparing print V1:	86,1		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	3,3	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	83		
Average value of the 2 areas F comparing print V2:	85,6		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	2,6	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	81,6		
Average value of the 2 areas F comparing print V3:	85,5		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	3,9	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3) **YELLOW**

Test print A1				
Color values 1 6 A F	1	6	A	F
after 50 pages	90	89,5	86,5	83,8
Color values 1 6 A F	1	6	A	F
The biggest deviation	0,8	0,9	0,9	1,8
Comparing print V1				
Color values 1 6 A F	1	6	A	F
after 50 pages	92,1	90,8	88,6	85,9

Color values 1 6 A F	1	6	A	F
The biggest deviation	2	0,7	0,9	0,8
Result determination	1	6	A	F
Difference ΔL≤8	1,2	0,2	0	1
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 YELLOW

Color values 1 6 A F	1	6	A	F
after 50 pages	90,7	89,2	86,4	83,5
Color values 1 6 A F	1	6	A	F
The biggest deviation	0,8	0,6	0,9	1,4
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	92,2	90,4	88,2	85,4
Color values 1 6 A F	1	6	A	F
The biggest deviation	0,6	0,6	0,9	0,9
Result determination	1	6	A	F
Difference ΔL≤8	0	0	0	0,5
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 YELLOW

Color values 1 6 A F	1	6	A	F
after 50 pages	90,8	88,9	85,8	83
Color values 1 6 A F	1	6	A	F
The biggest deviation	0,9	0,7	1	2,4
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	91,4	90,6	88,4	85,9
Color values 1 6 A F	1	6	A	F
The biggest deviation	0,5	0,3	0,4	1,1
Result determination	1	6	A	F
Difference ΔL≤8	0,4	0,4	0,6	1,3
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesition
Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes
If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)
Are the color diferences in between the acceptable parameters (pattern B2-B5) ΔE≤8 ? Yes
If not: Describe deviation

Checking the background (5.6.6)
Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes
If not: Describe deviation

Checking the ghosting (5.6.7)
Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes
If not: Describe deviation

Checking toner miscibility (5.6.8)
Is the toner miscibility given? N/A
If not: Describe deviation

OVERALL RESULT: **Passed**