



Manufacturer (trade mark):	PRPS	Type/Model OEM:	C13S051099
Lot/Part number:	4241757	Toner color(s):	Drum Section - no
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	20000		
Test device:	FGHZ084237 / JGHZ084237 / N/A	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test climate:			
Temperature:	23	Relative humidity:	48
Deviations of the determined test conditions			
Tester 1):	0	Test location 2):	SERBIA
Test date:	10/10/2014		

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation	Charge/Serial number
1 21450		Yes	Sample 1
2 21515		Yes	Sample 2
3 21851		Yes	We use for A1 the
4 21365		Yes	MAX, for A2 the
5 20820		Yes	MEDIAN and for A3 the
6 20478		Yes	MIN value of the list at
7 20693		Yes	left
8 20478		Yes	Sample 7
9 21454		Yes	Sample 8
		Yes	Sample 9
Comparing Sample (B)	Type	Used for valuation	Charge/Serial number
1 20000		Yes/no	Yes
2 20000		Yes/no	Yes
3 20000		Yes/no	Yes
4		Yes/no	
5		Yes/no	

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner? Yes/no **Yes**

If there are no information of the AMES test in the EG Safety Data Sheet

Is there a test report about the AMES test of the used toner? Yes/no **Not Aplicable**

If not: Description **All MSDSs mention Ames test**

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original? Yes/no **Yes**

Is the interaction between printer and toner module acceptable? Yes/no **Yes**

If not: Description

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted? Yes/no **Yes**

If not: Describe fault

Checking the yield number (5.5)

Drum Section - no ISO

	1	2	3	Average ($\bar{A}$ or $\bar{V}$)
Yield A: $(A1+A2+A3)/3=\bar{A}$	21851	21365	20478	21231
Yield V: $(V1+V2+V3)/3=\bar{V}$	20000	20000	20000	20000

Alternative:

Yield A: Result of test after ISO/IEC 19752 $\bar{A}$	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 $\bar{V}$	
Reference to the test protocol:	
Test date:	
Result: $EZ=\bar{A}/\bar{V}$	1,06

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)

Drum Section - no ISO

Test print A1				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V1				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 Drum Section - no ISO

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 Drum Section - no ISO

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesion

Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes

If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)Are the color differences in between the acceptable parameters (pattern B2-B5) $\Delta E \leq 8$? Yes

If not: Describe deviation

Checking the background (5.6.6)

Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes

If not: Describe deviation

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes

If not: Describe deviation

Checking toner miscibility (5.6.8)

Is the toner miscibility given? N/A

If not: Describe deviation

OVERALL RESULT: Passed