



Manufacturer (trade mark):	PRPS	Type/Model OEM:	TK-580K
Lot/Part number:	4223012	Toner color(s):	BLACK
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	3500	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test device:	Q521107835 / Q521515530 / Q520Y01272	Relative humidity:	40
Test climate:	Temperature: 24	Test location 2):	SERBIA
Deviations of the determined test conditions	Tester 1): Aleksandar Kojic	Test date:	09/07/2015

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation	Charge/Serial number
1	4356	Yes	Sample 1
2	5182	Yes	Sample 2
3	3838	Yes	Sample 3
4	3675	Yes	Sample 4
5	4091	Yes	Sample 5
6	3937	Yes	Sample 6
7	4125	Yes	Sample 7
8	4205	Yes	Sample 8
9	3850	Yes	Sample 9

Comparing Sample (B)	Type	Used for valuation	Charge/Serial number
1	3500	Yes/no	OEM Sample/Spec
2	3500	Yes/no	OEM Sample/Spec
3	3500	Yes/no	OEM Sample/Spec
4		Yes/no	
5		Yes/no	

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner? Yes/no **Yes**

If there are no information of the AMES test in the EG Safety Data Sheet

Is there a test report about the AMES test of the used toner? Yes/no **Not Aplicable**

If not: Description **All MSDSs mention Ames test**

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original? Yes/no **Yes**

Is the interaction between printer and toner module acceptable? Yes/no **Yes**

If not: Description

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted? Yes/no **Yes**

If not: Describe fault

Checking the yield number (5.5)

BLACK

	1	2	3	Average (\bar{A} or \bar{V})
Yield A: $(A1+A2+A3)/3=\bar{A}$	5182	4091	3675	4316
Yield V: $(V1+V2+V3)/3=\bar{V}$	3500	3500	3500	3500

Alternative:

Yield A: Result of test after ISO/IEC 19752 \bar{A}	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 \bar{V}	
Reference to the test protocol:	
Test date:	
Result: $EZ=\bar{A}/\bar{V}$	1,23

Is the expected yield (EZ) reached?	Yes	No	Not Aplicable
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)

BLACK

Test print A1				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V1				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 BLACK

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 BLACK

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesion

Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes

If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)

Are the color differences in between the acceptable parameters (pattern B2-B5) $\Delta E \leq 8$? Yes

If not: Describe deviation

Checking the background (5.6.6)

Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes

If not: Describe deviation

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes

If not: Describe deviation

Checking toner miscibility (5.6.8)

Is the toner miscibility given? N/A

If not: Describe deviation

OVERALL RESULT: Passed



Manufacturer (trade mark):	PRPS	Type/Model OEM:	TK-580C
Lot/Part number:	4223029	Toner color(s):	CYAN
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	2800		
Test device:	Q521107835 / Q521515530 / Q520Y01272	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test climate:			
Temperature:	24	Relative humidity:	40
Deviations of the determined test conditions			
Tester 1):	Aleksandar Kojic	Test location 2):	SERBIA
Test date:	09/07/2015		

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation	Charge/Serial number
1	4657	Yes	Sample 1
2	4607	Yes	Sample 2
3	5741	Yes We use for A1 the	Sample 3
4	5600	Yes MAX, for A2 the	Sample 4
5	5630	Yes MEDIAN and for A3 the	Sample 5
6	3947	Yes MIN value of the list at	Sample 6
7	4580	Yes left	Sample 7
8	4715	Yes	Sample 8
9	4503	Yes	Sample 9

Comparing Sample (B)	Type	Used for valuation	Charge/Serial number
1	2800	Yes/no Yes	OEM Sample/Spec
2	2800	Yes/no Yes	OEM Sample/Spec
3	2800	Yes/no Yes	OEM Sample/Spec
4		Yes/no	
5		Yes/no	

OEM data taken from OEMs own
ISO19752 or ISO19798 declarations of
yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner? Yes/no Yes

If there are no information of the AMES test in the EG Safety Data Sheet

Is there a test report about the AMES test of the used toner? Yes/no Not Aplicable

If not: Description All MSDSs mention Ames test

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original? Yes/no Yes

Is the interaction between printer and toner module acceptable? Yes/no Yes

If not: Description

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted? Yes/no Yes

If not: Describe fault

Checking the yield number (5.5)

CYAN

	1	2	3	Average (\bar{A} or \bar{V})
Yield A: $(A1+A2+A3)/3 = \bar{A}$	5741	4657	3947	4782
Yield V: $(V1+V2+V3)/3 = \bar{V}$	2800	2800	2800	2800

Alternative:

Yield A: Result of test after ISO/IEC 19752 \bar{A}

Reference to the test protocol:

Test date:

Yield V: Result of test after ISO/IEC 19752 \bar{V}

Reference to the test protocol:

Test date:

Result: $EZ = \bar{A}/\bar{V}$

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)

CYAN

Test print A1				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V1				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 CYAN

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 CYAN

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesion

Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes

If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)Are the color differences in between the acceptable parameters (pattern B2-B5) $\Delta E \leq 8$? Yes

If not: Describe deviation

Checking the background (5.6.6)

Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes

If not: Describe deviation

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes

If not: Describe deviation

Checking toner miscibility (5.6.8)

Is the toner miscibility given? N/A

If not: Describe deviation

OVERALL RESULT: Passed



Manufacturer (trade mark):	PRPS	Type/Model OEM:	TK-580M
Lot/Part number:	4223036	Toner color(s):	MAGENTA
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	2800	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test device:	Q521107835 / Q521515530 / Q520Y01272	Relative humidity:	40
Test climate:	Temperature: 24	Test location 2):	SERBIA
Deviations of the determined test conditions	Tester 1): Aleksandar Kojic	Test date:	09/07/2015

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation	Charge/Serial number
1 4249		Yes	Sample 1
2 4355		Yes	Sample 2
3 4813		Yes We use for A1 the	Sample 3
4 4190		Yes MAX, for A2 the	Sample 4
5 4463		Yes MEDIAN and for A3 the	Sample 5
6 4121		Yes MIN value of the list at	Sample 6
7 4240		Yes left	Sample 7
8 4309		Yes	Sample 8
9 4010		Yes	Sample 9
Comparing Sample (B)	Type	Used for valuation	Charge/Serial number
1 2800		Yes/no Yes	OEM Sample/Spec
2 2800		Yes/no Yes	OEM Sample/Spec
3 2800		Yes/no Yes	OEM Sample/Spec
4		Yes/no	
5		Yes/no	

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner? Yes/no **Yes**

If there are no information of the AMES test in the EG Safety Data Sheet

Is there a test report about the AMES test of the used toner? Yes/no **Not Aplicable**

If not: Description **All MSDSs mention Ames test**

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original? Yes/no **Yes**

Is the interaction between printer and toner module acceptable? Yes/no **Yes**

If not: Description

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted? Yes/no **Yes**

If not: Describe fault

Checking the yield number (5.5)

MAGENTA

	1	2	3	Average (\bar{A} or \bar{V})
Yield A: $(A1+A2+A3)/3 = \bar{A}$	4813	4249	4010	4357
Yield V: $(V1+V2+V3)/3 = \bar{V}$	2800	2800	2800	2800

Alternative:

Yield A: Result of test after ISO/IEC 19752 \bar{A}	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 \bar{V}	
Reference to the test protocol:	
Test date:	
Result: $EZ = \bar{A}/\bar{V}$	1,56

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)

MAGENTA

Test print A1				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V1				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 MAGENTA

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 MAGENTA

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesion

Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes

If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)Are the color differences in between the acceptable parameters (pattern B2-B5) $\Delta E \leq 8$?

Yes

If not: Describe deviation

Checking the background (5.6.6)

Is the background smudge between the acceptable parameters (pattern B1-B5)?

Yes

If not: Describe deviation

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)?

Yes

If not: Describe deviation

Checking toner miscibility (5.6.8)

Is the toner miscibility given?

N/A

If not: Describe deviation

OVERALL RESULT: Passed



Manufacturer (trade mark):	PRPS	Type/Model OEM:	TK-580Y
Lot/Part number:	4223043	Toner color(s):	YELLOW
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	2800	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test device:	Q521107835 / Q521515530 / Q520Y01272	Relative humidity:	40
Test climate:	Temperature: 24	Test location 2):	SERBIA
Deviations of the determined test conditions	Tester 1): Aleksandar Kojic	Test date:	09/07/2015

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation	Charge/Serial number
1 4037		Yes	Sample 1
2 3620		Yes	Sample 2
3 4703		Yes	We use for A1 the
4 4513		Yes	MAX, for A2 the
5 4822		Yes	MEDIAN and for A3 the
6 3506		Yes	MIN value of the list at
7 4217		Yes	left
8 4006		Yes	Sample 7
9 4112		Yes	Sample 8
		Yes	Sample 9
Comparing Sample (B)	Type	Used for valuation	Charge/Serial number
1 2800		Yes/no	Yes
2 2800		Yes/no	Yes
3 2800		Yes/no	Yes
4		Yes/no	
5		Yes/no	

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?	Yes/no	Yes
If there are no information of the AMES test in the EG Safety Data Sheet		
Is there a test report about the AMES test of the used toner?	Yes/no	Not Aplicable
If not: Description	All MSDSs mention Ames test	

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?	Yes/no	Yes
Is the interaction between printer and toner module acceptable?	Yes/no	Yes
If not: Description		

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?	Yes/no	Yes
If not: Describe fault		

Checking the yield number (5.5)

YELLOW

	1	2	3	Average (\bar{A} or \bar{V})
Yield A: $(A1+A2+A3)/3=\bar{A}$	4822	4112	3506	4147
Yield V: $(V1+V2+V3)/3=\bar{V}$	2800	2800	2800	2800

Alternative:

Yield A: Result of test after ISO/IEC 19752 \bar{A}	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 \bar{V}	
Reference to the test protocol:	
Test date:	
Result: $EZ=\bar{A}/\bar{V}$	1,48

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)

YELLOW

Test print A1	1	6	A	F
Color values 1 6 A F after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V1	1	6	A	F
Color values 1 6 A F after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 YELLOW

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 YELLOW

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesion

Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes
 If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)

Are the color differences in between the acceptable parameters (pattern B2-B5) $\Delta E \leq 8$? Yes
 If not: Describe deviation

Checking the background (5.6.6)

Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes
 If not: Describe deviation

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes
 If not: Describe deviation

Checking toner miscibility (5.6.8)

Is the toner miscibility given? N/A
 If not: Describe deviation

OVERALL RESULT: Passed