

## ISO/IEC 19752 Declaration of Yield

For Monochrome Toner Laser Cartridges



**Description:** Monochrome: Lexmark MS811 Extra High Yield

### Monochrome

Average Continuous  
Composite Crtg Yields

**PRPS PN:** 4241825  
**OEM Equiv.:** 52D2X00  
**OEM Yield Spec.:** 45000

**K**  
49930

### Page Yield Information:

Color	Yield	Standard	90% Lower	90% Upper	Printer 1	Printer 1	Printer 1	Printer 2	Printer 2	Printer 2	Printer 3	Printer 3	Printer 3
	Average	Deviation	Confidence	Confidence	Test 1	Test 2	Test 3	Test 1	Test 2	Test 3	Test 1	Test 2	Test 3
Black/Monochrome	50881	1522	49937	51825	51455	51675	50020	51655	52765	52809	48904	49638	49008

**Dates of Test:** **Start Date** 09/11/2016 **End Date** 21/03/2017

**Printer Serial Number:** **Printer 1** 40635C6604MBB **Printer 2** 40635C6604MLY **Printer 3** 40635C6604MLN

**Average Conditions of test T °C / %RH:** 25 °C 42 %

Computer model: PC  
Software used/Driver version: PCL 6  
Operating system: Windows 7 32-bit  
Printer model: HP M 506  
Version of PDF Reader: Adobe Reader 11  
Power (off/on) Everyday: Yes  
Number of Cartridges sets Used in Testing: 9  
Number of Cartridges sets Used in Calculations: 9  
Shake Procedure Used? When aplicable,at 1st and 2nd fade  
Print Mode: Continuous  
Number of Printers Used in Testing: 3  
Media Used: A4  
Paper Weight: 80 gsm

### Brief Technical information

All Products with dates of release after the ISO standards 19752 (for monochrome crtgs) and 19798 (for color crtgs) have been tested follo wing these same standards. For other products this type of analysis has only been made when major changes to configurations has been done in any of the manufacturing locations.

Please note:

These products are not related or affiliated with any of the above trade marks referenced in models descriptions. These trademarks are only mentioned for a clear identification of the remanufactured product tested.