Manufacturer (trade mark):	**PRPS**	Type/Model OEM:	CLT-K406S/ELS
Lot/Part number:	*4229700*	Toner color(s):	**BLACK**
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	1500		
Test device:	Z6Y4BJEC6000X7Y / Z6Y4BJAD90005GY / Z6Y4BJAD70002MD	Take over value of existing test protocol : (box)	Yes, from ISO19798
Test climate:			
Temperature:	22	Relative humidity:	44
Deviations of the determined test conditions			
Tester 1):	0	Test location 2):	**SERBIA**
Test date:	**11/04/2015**		

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation		Charge/Serial number
1	1512	Yes		Sample 1
2	1623	Yes		Sample 2
3	1604	Yes	We use for A1 the	Sample 3
4	1715	Yes	MAX, for A2 the	Sample 4
5	1689	Yes	MEDIAN and for A3 the	Sample 5
6	1652	Yes	MIN value of the list at	Sample 6
7	1639	Yes	left	Sample 7
8	1578	Yes		Sample 8
9	1504	Yes		Sample 9

Comparing Sample (B)	Type	Used for valuation		Charge/Serial number
1	1500	Yes/no	Yes	OEM Sample/Spec
2	1500	Yes/no	Yes	OEM Sample/Spec
3	1500	Yes/no	Yes	OEM Sample/Spec
4		Yes/no		
5		Yes/no		

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?	Yes/no	Yes
If there are no information of the AMES test in the EG Safety Data Sheet		
Is there a test report about the AMES test of the used toner?	Yes/no	Not Aplicable
If not: Description	All MSDSs mention Ames test	

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?	Yes/no	Yes
Is the interaction between printer and toner module acceptable?	Yes/no	Yes
If not: Description		

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?	Yes/no	Yes
If not: Describe fault		

Checking the yield number (5.5) — BLACK

	1	2	3	Average (Ā or V)
Yield A: (A1+A2+A3)/3= Ā	1715	1623	1504	1614
Yield V: (V1+V2+V3)/3=V	1500	1500	1500	1500

Alternative:

Yield A: Result of test after ISO/IEC 19752 Ā		
Reference to the test protocol:		
Test date:		
Yield V: Result of test after ISO/IEC 19752 V		
Reference to the test protocol:		
Test date:		
Result: EZ=Ā/V		1,08

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3) — BLACK

Test print A1

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V1

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference ∆L≤8	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 BLACK

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Result determination	1	6	A	F
Difference ∆L≤8	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 BLACK

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Result determination	1	6	A	F
Difference ∆L≤8	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesition

Test process: visual (tape method):

Is the resistance in between the acceptable parameters?   Yes

If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)

Are the color diferences in between the acceptable
parameters (pattern B2-B5) ∆E≤8 ?   Yes

If not: Describe deviation

Checking the background (5.6.6)

Is the background smudge between the acceptable
parameters (pattern B1-B5)?   Yes

If not: Describe deviation

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the
acceptable parameters (pattern B2-B5)?   Yes

If not: Describe deviation

Checking toner miscibility (5.6.8)

Is the toner miscibility given?   N/A

If not: Describe deviation

OVERALL RESULT: **Passed**

Manufacturer (trade mark):	**PRPS**	Type/Model OEM:	CLT-C406S/ELS
Lot/Part number:	*4229717*	Toner color(s):	**CYAN**

Main application: To be used on the relevant printers according to remanufacturer instructions

Intended yield: 1000

Test device: Z6Y4BJEC6000X7Y / Z6Y4BJAD90005GY / Z6Y4BJAD70002MD

Take over value of existing test protocol : (box) Yes, from ISO19798

Test climate:

Temperature:	22	Relative humidity:	44

Deviations of the determined test conditions

Tester 1):	0	Test location 2):	**SERBIA**
Test date:	**11/04/2015**		

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation		Charge/Serial number
1	1145	Yes		Sample 1
2	1087	Yes		Sample 2
3	1023	Yes	We use for A1 the	Sample 3
4	1047	Yes	MAX, for A2 the	Sample 4
5	1100	Yes	MEDIAN and for A3 the	Sample 5
6	1085	Yes	MIN value of the list at	Sample 6
7	1089	Yes	left	Sample 7
8	1136	Yes		Sample 8
9	1125	Yes		Sample 9

Comparing Sample (B)	Type	Used for valuation		Charge/Serial number
1	1000	Yes/no	Yes	OEM Sample/Spec
2	1000	Yes/no	Yes	OEM Sample/Spec
3	1000	Yes/no	Yes	OEM Sample/Spec
4		Yes/no		
5		Yes/no		

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?	Yes/no	Yes

If there are no information of the AMES test in the EG Safety Data Sheet

Is there a test report about the AMES test of the used toner?	Yes/no	Not Aplicable

If not: Description All MSDSs mention Ames test

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?	Yes/no	Yes
Is the interaction between printer and toner module acceptable?	Yes/no	Yes

If not: Description

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?	Yes/no	Yes

If not: Describe fault

Checking the yield number (5.5)   CYAN

	1	2	3	Average (Ā or V)
Yield A: (A1+A2+A3)/3= Ā	1145	1089	1023	1086
Yield V: (V1+V2+V3)/3=V	1000	1000	1000	1000

Alternative:

Yield A: Result of test after ISO/IEC 19752 Ā	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 V	
Reference to the test protocol:	
Test date:	
Result: EZ=Ā/V	1,09

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)   CYAN

Test print A1

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V1

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 CYAN

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 CYAN

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesition

Test process: visual (tape method):

Is the resistance in between the acceptable parameters?	Yes
If not: Describe deviation	

Checking the grey page/color uniformity (5.6.5)

Are the color diferences in between the acceptable parameters (pattern B2-B5) $\Delta E \leq 8$?	Yes
If not: Describe deviation	

Checking the background (5.6.6)

Is the background smudge between the acceptable parameters (pattern B1-B5)?	Yes
If not: Describe deviation	

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)?	Yes
If not: Describe deviation	

Checking toner miscibility (5.6.8)

Is the toner miscibility given?	N/A
If not: Describe deviation	

OVERALL RESULT: Passed

Manufacturer (trade mark):	**PRPS**	Type/Model OEM:	CLT-M406S/ELS
Lot/Part number:	*4229724*	Toner color(s):	**MAGENTA**
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	1000		
Test device:	Z6Y4BJEC6000X7Y / Z6Y4BJAD90005GY / Z6Y4BJAD70002MD	Take over value of existing test protocol : (box)	Yes, from ISO19798
Test climate:			
Temperature:	22	Relative humidity:	44
Deviations of the determined test conditions			
Tester 1):	0	Test location 2):	**SERBIA**
Test date:	**11/04/2015**		

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation		Charge/Serial number
1	1147	Yes		Sample 1
2	1115	Yes		Sample 2
3	1178	Yes	We use for A1 the	Sample 3
4	1136	Yes	MAX, for A2 the	Sample 4
5	1105	Yes	MEDIAN and for A3 the	Sample 5
6	1009	Yes	MIN value of the list at	Sample 6
7	1046	Yes	left	Sample 7
8	1086	Yes		Sample 8
9	1048	Yes		Sample 9

Comparing Sample (B)	Type	Used for valuation		Charge/Serial number
1	1000	Yes/no	Yes	OEM Sample/Spec
2	1000	Yes/no	Yes	OEM Sample/Spec
3	1000	Yes/no	Yes	OEM Sample/Spec
4		Yes/no		
5		Yes/no		

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?	Yes/no	Yes
If there are no information of the AMES test in the EG Safety Data Sheet		
Is there a test report about the AMES test of the used toner?	Yes/no	Not Aplicable
If not: Description	All MSDSs mention Ames test	

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?	Yes/no	Yes
Is the interaction between printer and toner module acceptable?	Yes/no	Yes
If not: Description		

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?	Yes/no	Yes
If not: Describe fault		

Checking the yield number (5.5)   MAGENTA

	1	2	3	Average (Ā or V)
Yield A: (A1+A2+A3)/3= Ā	1178	1105	1009	1097
Yield V: (V1+V2+V3)/3=V	1000	1000	1000	1000
Alternative:				
Yield A: Result of test after ISO/IEC 19752 Ā				
Reference to the test protocol:				
Test date:				
Yield V: Result of test after ISO/IEC 19752 V				
Reference to the test protocol:				
Test date:				
Result: EZ=Ā/V				1,10

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)   MAGENTA

Test print A1

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V1

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Result determination	1	6	A	F
Difference ΔL≤8	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 MAGENTA

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Result determination	1	6	A	F
Difference ΔL≤8	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 MAGENTA

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Result determination	1	6	A	F
Difference ΔL≤8	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesition
Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes
If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)
Are the color diferences in between the acceptable parameters (pattern B2-B5) ΔE≤8 ? Yes
If not: Describe deviation

Checking the background (5.6.6)
Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes
If not: Describe deviation

Checking the ghosting (5.6.7)
Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes
If not: Describe deviation

Checking toner miscibility (5.6.8)
Is the toner miscibility given? N/A
If not: Describe deviation

OVERALL RESULT: **Passed**

Manufacturer (trade mark):	**PRPS**	Type/Model OEM:	CLT-Y406S/ELS
Lot/Part number:	*4229731*	Toner color(s):	**YELLOW**

Main application: To be used on the relevant printers according to remanufacturer instructions

Intended yield: 1000

Test device: Z6Y4BJEC6000X7Y / Z6Y4BJAD90005GY / Z6Y4BJAD70002MD

Take over value of existing test protocol : (box) Yes, from ISO19798

Test climate:

Temperature: 22   Relative humidity: 44

Deviations of the determined test conditions

Tester 1): 0   Test location 2): **SERBIA**

Test date: **11/04/2015**

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)		Type	Used for valuation		Charge/Serial number
	1	1178	Yes		Sample 1
	2	1169	Yes		Sample 2
	3	1090	Yes	We use for A1 the	Sample 3
	4	1058	Yes	MAX, for A2 the	Sample 4
	5	1112	Yes	MEDIAN and for A3 the	Sample 5
	6	1136	Yes	MIN value of the list at	Sample 6
	7	1158	Yes	left	Sample 7
	8	1147	Yes		Sample 8
	9	1169	Yes		Sample 9

Comparing Sample (B)		Type	Used for valuation		Charge/Serial number
	1	1000	Yes/no	Yes	OEM Sample/Spec
	2	1000	Yes/no	Yes	OEM Sample/Spec
	3	1000	Yes/no	Yes	OEM Sample/Spec
	4		Yes/no		
	5		Yes/no		

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?   Yes/no Yes

If there are no information of the AMES test in the EG Safety Data Sheet

Is there a test report about the AMES test of the used toner?   Yes/no Not Aplicable

If not: Description All MSDSs mention Ames test

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?   Yes/no Yes

Is the interaction between printer and toner module acceptable?   Yes/no Yes

If not: Description

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?   Yes/no Yes

If not: Describe fault

Checking the yield number (5.5)   YELLOW

	1	2	3	Average (Ā or V)
Yield A: (A1+A2+A3)/3= Ā	1178	1147	1058	1128
Yield V: (V1+V2+V3)/3=V	1000	1000	1000	1000

Alternative:

Yield A: Result of test after ISO/IEC 19752 Ā	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 V	
Reference to the test protocol:	
Test date:	
Result: EZ=Ā/V	1,13

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than Δ≤5 for Monochrom	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference ΔE≤18 for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)   YELLOW

Test print A1

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V1

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Result determination	1	6	A	F
Difference ΔL≤8	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 YELLOW

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Result determination	1	6	A	F
Difference ΔL≤8	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 YELLOW

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Comparing print V2

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0

Result determination	1	6	A	F
Difference ΔL≤8	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesition
Test process: visual (tape method):

Is the resistance in between the acceptable parameters?	Yes
If not: Describe deviation	

Checking the grey page/color uniformity (5.6.5)
Are the color diferences in between the acceptable parameters (pattern B2-B5) ΔE≤8 ?	Yes
If not: Describe deviation	

Checking the background (5.6.6)
Is the background smudge between the acceptable parameters (pattern B1-B5)?	Yes
If not: Describe deviation	

Checking the ghosting (5.6.7)
Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)?	Yes
If not: Describe deviation	

Checking toner miscibility (5.6.8)
Is the toner miscibility given?	N/A
If not: Describe deviation	

OVERALL RESULT: **Passed**