ISO/IEC 19752 Declaration of Yield

For Monochrome Toner Laser Cartridges

Description: Monochrome: Samsung ML-2010



Monochrome

PRPS PN: 629524

OEM Equiv.: ML-2010D3/ELS

529524

OFNA Wield Connection 2000

OEM Yield Spec.: 3000

Average Continuous Composite Crtg Yields

K

3410

Page Yield Information:

Brief Technical information

	Yield	Standard	90% Lower	90% Upper	Printer 1	Printer 1	Printer 1	Printer 2	Printer 2	Printer 2	Printer 3	Printer 3	Printer 3
Color	Average	Deviation	Confidence	Confidence	Test 1	Test 2	Test 3	Test 1	Test 2	Test 3	Test 1	Test 2	Test 3
Black/Monochrome	3540	194	3420	3660	3325	3260	3470	3615	3520	3680	3413	3846	3730

Start Date End Date

Dates of Test: 04/09/2014 12/12/2014

 Printer 1
 Printer 2
 Printer 3

 Printer Serial Number:
 3A37BKAP326240W
 4621BKBP508697N
 BKEY9117687

Average Conditions of test T ºC / %RH:

22 ºC 44 %

Computer model: PC

Software used/Driver version: PCL 6

Operating system: Windows 7 32-bit

Printer model: HP M 506

Version of PDF Reader: Adobe Reader 11

Power (off/on) Everyday: Yes

Number of Cartridges sets Used in Testing: $\,9\,$

Number of Cartridges sets Used in Calculations: 9

Shake Procedure Used? When aplicable, at 1st and 2nd fade

Print Mode: Continuous

Number of Printers Used in Testing: 3

Media Used: A4

Paper Weight: 80 gsm

All Products with dates of release after the ISO standards 19752 (for monochrome crtgs) and 19798 (for color crtgs) have been tested following these same standards. For other products this type of analysis has only been made when major changes to configurations has been done in any of the manufacturing locations.

Please note:

These products are not related or affiliated with any of the above trade marks referenced in models descriptions. These trademarks are only mentioned for a clear identification of the remanufactured product tested.