ISO/IEC 19752 Declaration of Yield

For Monochrome Toner Laser Cartridges

Description: Monochrome: Samsung ML-3310



Р	RPS PN:	4229625							Average Continuous Composite Crtg Yields							
OEM Equiv.:		MLT-D205L/ELS						к								
OEM Yield Spec.:		5000	5000				5270									
Pa	ge Yield	Information:														
	Yield	Standard	90% Lower	90% Upper	Printer 1	Printer 1	Printer 1	Printer 2	Printer 2	Printer 2	Printer 3	Printer 3	Printer 3			
Color	Average	Deviation	Confidence	Confidence	Test 1	Test 2	Test 3	Test 1	Test 2	Test 3	Test 1	Test 2	Test 3	ſ		
Black/Monochrome	5464	298	5279	5649	5320	5213	6023	5452	5320	5136	5812	5269	5630			
		_	Start	Date	End Date	nd Date						Computer model: PC Software used/Driver version: PCL 6				
Dates of Test:			12/03/2013		25/09/2013					Operating system: Windows 7 32-bit						
		<u> </u>					•				Printer model: HP M 506					
			Printer 1		Printer 2		Printer 3				Version of PDF Reader: Adobe Reader 11					
Printer Serial Number:			Z5H7BABC100710K		Z5H7BAFZB00539T		Z5H7BADB801430T				Power (off/on) Everyday: Yes					
· · · · · · · · · · · · · · · · · · ·											Number of Cartridges sets Used in Testing: 9					
Average Conditions of test T °C / %RH: 22 °C 43 %										Number of Cartridges sets Used in Calculations: 9						
													Shake Pi	ocedure Used? When aplicable, at 1st and 2nd fade		
														Print Mode: Continuous		
												Number of Printers Used in Testing: 3				
Brief Technical information										Media Used: A4						
														Paper Weight: 80 gsm		

All Products with dates of release after the ISO standards 19752 (for monochrome crtgs) and 19798 (for color crtgs) have been tested follo wing these same standards. For other products this type of analysis has only been made when major changes to configurations has been done in any of the manufacturing locations.

Please note:

These products are not related or affiliated with any of the above trade marks referenced in models descriptions. These trademarks are only mentioned for a clear identification of the remanufactured product tested.