

# Hazardous Cupboards



## Sizes Available

### Floor Versions:

1800Hx900Wx460Dmm - 3 shelves - 14-litre sump capacity.  
 1800Hx1200Wx460Dmm - 3 shelves - 18-litre sump capacity.  
 1200Hx900Wx460Dmm - 2 shelves - 14-litre sump capacity.  
 900Hx460Wx460Dmm - 1 shelf - 7-litre sump capacity.  
 900Hx900Wx460Dmm - 1 shelf - 14-litre sump capacity.  
 700Hx350Wx300Dmm - 1 shelf - 3-litre sump capacity.  
 700Hx900Wx460Dmm - 1 shelf - 14-litre sump capacity.

### Mobile Versions:

1040Hx900Wx460Dmm - 1 shelf - no sump fitted.  
 840Hx900Wx460Dmm - 1 shelf - no sump fitted.

### Floor Chest Versions:

610Hx1170Wx460Dmm - no shelf - 20-litre sump capacity.  
 510Hx610Wx340Dmm - no shelf - 7-litre sump capacity.

### Wall-Mounted Version:

570Hx850Wx255Dmm - 1 shelf - no sump fitted.



## Paint Finish

A three-stage pre-treatment and phosphate coating are applied.  
 Carcass and doors are powder-coated with one coat of epoxy polyester full gloss powder, stoved at 180deg, including our germ guard anti-bacterial compound.  
 The product is powder-coated - Truflow yellow.



## Cleaning & Maintenance

Clean paint work periodically with warm soapy water or foaming cleaner. Oil hinges and lock sparingly as required with a light oil (3in1 or similar).



[www.qmp.uk.com](http://www.qmp.uk.com)



01384 899800



[sales@qmp.uk.com](mailto:sales@qmp.uk.com)

# Hazardous Cupboards



## Cupboard Construction

### General Construction:

- 0.7mm mild steel, pop riveted carcass construction.
- Integral liquid-tight sump fitted at the bottom of the cupboard (*except wall-mounted cupboard*).
- Door aperture has return bends to eliminate open gaps.
- Delivered as a fully assembled unit.
- Warning/hazardous labels supplied.
- Reaction to Fire Classification EN 13501-1 – supporting documents are available from our sales or marketing team.
- Fitted with "no snag" 2-point locking mechanism.
- Adjustable spill-retaining galvanised shelves for superior spill management with a UDL of 50KG.

### Floor Chest Construction:

- Material: 1.5mm mild steel.
- Fully welded integrated sump & angled lid to discourage article placement.
- Fully welded construction with 2 no. welded 2.5" butt hinges.
- Connected to the carcass with 4.8mm pop rivets.
- Fitted with restraint to prevent lid from falling back.
- Supplied with hasp and staple (padlock not supplied).



## Replacement Locks & Spare Keys

Replacement locks and keys are available from QMP.

Replacement keys are available from Fast Key Ltd

[www.fastkeys.co.uk](http://www.fastkeys.co.uk) - [sales@fastkeys.co.uk](mailto:sales@fastkeys.co.uk).



## 5 Day Delivery

All sizes are available on our 5-day delivery service, except our Floor Chest Cupboards. This is a manufactured-to-order item and will be on an extended lead-time.



Our live chat satisfaction rating,  
based on user feedback



[www.qmp.uk.com](http://www.qmp.uk.com)



01384 899800



[sales@qmp.uk.com](mailto:sales@qmp.uk.com)

