



Staff Locker Sizes Available:

<u>Height</u>	<u>Width</u>	<u>Depth</u>
1800mm	450mm	450mm

Door Description:

1 Compartment

Locker Construction:

- 0.7mm mild steel, pop riveted carcass construction
- Top shelf.
- Top shelf for storage with a central divider for separation with 3 shelves, 1 full length to the left of the locker with 3 small shelves at the right side of the locker
- Delivered assembled
- Pre-drilled carcass for nesting Locker together
- Fitted with standard master cam locks with 2,000 differs
- Reaction to Fire Classification EN 13501-1 – documents available

Locker Door Construction:

- A door stiffener is spot welded vertically in the centre of the door, the door is attached by pop rivets to the right hand side of the carcase with two 38mm butt hinges and fitted with 10 disc key operated cam lock. Alternatively, swivel latch locks (to accept padlock supplied by others) can be specified.

Paint Finish:

- Three stage pre-treatment and phosphate coating
- Carcass and doors powder coated with one coat Epoxy Polyester Full gloss powder, stoved at 180 deg. C. including Germ Guard antibacterial compound
- Carcass powder coated with RAL 7035 Light Grey

Door Colour Options:

Red	RAL 3003
Green	RAL 6024
Light Blue	RAL 5012
Dark Blue	RAL 5017
Light Grey	RAL 7035
Yellow	RAL 1018

Cleaning & Maintenance:

- Clean paint work periodically with warm soapy water or Foaming cleaner
- Oil hinges and lock sparingly as required with a light oil (3in1 or similar)

Replacement Locks & Spare Keys:

- Replacement locks available from:- **QMP LTD, Timmis Road, Lye, Stourbridge, West Midlands, DY9 7BQ, Tel: +44 (0) 1384 899800, Website: www.qmp.uk.com, Email: sales@qmp.uk.com**
- Spare / replacement keys for the cupboard are available from: **Fast Keys Ltd, Pilot Close, 3 Fulmar Way, Wickford, SS11 8YW, Tel: 01268 562592, Website: www.fastkeys.co.uk, Email: sales@fastkeys.co.uk**