

Steel Splash Lockers



Sizes & Compartments Available

Sizes:

1800Hx300Wx300Dmm

1800Hx300Wx450Dmm

Door Compartment Options:

1 Compartment

2 Compartments

3 Compartments

4 Compartments

Internal Compartment Sizes:

1800Hx300Wx300Dmm

1 Compartment - 1698Hx245Wx275Dmm

2 Compartments - 830Hx245Wx275Dmm

3 Compartments - 548Hx245Wx275Dmm

4 Compartments - 408Hx245Wx275Dmm

1800Hx300Wx450Dmm

1 Compartment - 1698Hx245Wx430Dmm

2 Compartments - 830Hx245Wx430Dmm

3 Compartment - 548Hx245Wx430Dmm

4 Compartments - 408Hx245Wx430Dmm



Paint Finish

A three-stage pre-treatment and phosphate coating are applied.

Carcass and doors are powder-coated with one coat of epoxy polyester full gloss powder, stoved at 180 deg, including our germ guard anti-bacterial compound.

The carcass is powder-coated - Light Grey RAL 7035.

Doors are powder-coated with a choice of Red RAL 3003, Green RAL 6024, Light Grey RAL 7035, Light Blue RAL 5012, Dark Blue RAL 5017 & Yellow RAL 1018.



www.qmp.uk.com



01384 899800



sales@qmp.uk.com

Steel Splash Lockers



Cleaning & Maintenance

Clean paint work periodically with warm soapy water or foaming cleaner. Oil hinges and lock sparingly as required with a light oil (3in1 or similar).



Locker Construction

General Construction:

- 0.7mm zinc coated steel, pop riveted carcass construction.
- Corner uprights 1.5mm zinc coated steel.
- Rust-resisting galvanised shelves.
- Delivered as a fully assembled unit.
- Pre-drilled carcass for nesting lockers together to complete a run/bank.
- Fitted with moist-resistant standard master cam locks with 2,000 differs.
- Single compartment locker fitted with top shelf and coat hook.
- Two-tier lockers fitted with coat hook in each compartment.
- Reaction to Fire Classification EN 13501-1 – supporting documents are available from our sales or marketing team.

Locker Door Construction:

- Material: 1.2mm Zintec Steel. The hinge is attached by pop rivets to the door and uprights on the right-hand side of the carcass, Three 62mm zinc plated butt hinges are fitted to single door locker and 2, 3 & 4 comp doors are fitted with two 62mm zinc plated butt hinges, All are fitted with 10 disc key operating a moisture resistant cam lock.



Replacement Locks & Spare Keys

Replacement locks and keys are available from QMP. Replacement keys are available from Fast Key Ltd. www.fastkeys.co.uk - sales@fastkeys.co.uk.



Our live chat satisfaction rating,
based on user feedback



Delivery

All sizes and compartment options are manufactured-to-order item and will be on an extended lead-time.



www.qmp.uk.com



01384 899800



sales@qmp.uk.com

Standard Lockers



www.qmp.uk.com



01384 899800



sales@qmp.uk.com