

MAXIM[®]

Ultrashield 25 25% Floor Finish

Features:

- High Solids - Requires Fewer Coats / Less Labor**
- Durable, Non-Yellowing**
- Excellent Off-the-Mop Gloss**
- Easy to Maintain**

Description

Designed for the professional floor crew that needs a finish that will require less coats and still give the high gloss demanded in today's markets. This product uses a special polymer, resin, wax ratio to provide superior initial gloss with unsurpassed durability. As little as 2 coats are needed for most applications. Finish dries to a clear film that will not yellow over time.

Directions

For floor finishing:

- 1 Thoroughly strip floor according to stripper label instructions, and allow to dry completely.
- 2 Use a mop or applicator to apply 2 - 5 coats of finish. Allow 30 - 45 minutes of drying time between coats.
- 3 For maintenance, dust mop or damp mop as needed.
- 4 For restoration, damp mop thoroughly with floor cleaner, and buff or burnish with spray buff or mop-on restorer.

For concrete, terrazzo, marble or granite:

- 1 Apply two coats of floor sealer according to sealer label instructions.
- 2 Use a mop or applicator to apply 2 - 5 coats of finish. Allow 30 - 45 minutes of drying time between coats.
- 3 Maintain and restore as above.

Recommended pads for buffing or burnishing:

- 175 - 1500 RPM: Soft White or Red Pad
- 1500+ RPM: White, Champagne, or Light Natural Pad



Applications

For regular stripping / buffing in:

- > Schools and hospitals
- > Airports
- > Offices

Specifications

| | |
|---------------------|---------------------|
| Color | White |
| Fragrance | Characteristic |
| pH Range | 8.0 - 8.5 |
| Dilution | RTU |
| Density | 8.60 |
| Non-volatile solids | 25% |
| Coverage | 2000 sq. ft. / gal. |

Packaging

| | |
|------------|-----------|
| 4/1 gallon | 122500-41 |
| 5 gallon | 122500-05 |
| 55 gallon | 122500-55 |