

# MAXIM®

## Non-Ammoniated Floor Stripper

### Features:

**Aggressive Stripper**  
**Low Odor, Non-Ammoniated**  
**Fast-Acting and Economical**

### Description

A professional strength stripper designed for the removal of tough-to-strip finishes and sealers. A powerful, fast acting stripper that emulsifies most finishes on contact, reducing normal soak times and removing multiple layers of finish with fewer passes.

### Directions

*Asphalt tile and rubber flooring could be affected by stripping solutions in high concentrations. Pre-test in a hidden location.*

#### For use on water-based floor finishes:

- ① Starting with the edges of the room, use a mop to apply liberal amounts of solution uniformly to floor.
- ② Let solution soak for 2 - 3 minutes. Allow more time for heavier build-ups. DO NOT allow solution to dry on floors.
- ③ Scrub with a stiff brush, or machine scrub using a black pad.
- ④ Pick up the solution with a clean mop, wet vac, or autoscrubber.
- ⑤ Mop up any tracks left behind by autoscrubbers before they dry. Detail mop with clean water.
- ⑥ Rinse thoroughly with a clean mop and water.
- ⑦ Let floor dry completely before applying floor finish.

#### Dilutions:

- ① *For normal stripping:* Use 26 oz. per gallon of water (1:5).
- ② *For heavier build-ups:* Use 64 oz. per gallon of water (1:2).



### Applications

#### Floor finish stripper for:

> Most water-based floor finishes

### Specifications

Color ..... Colorless  
 Fragrance ..... None  
 pH Range ..... > 13.0  
 Dilution ..... 26- 64 oz. / gal.  
 Density ..... 8.53  
 Coverage ..... 200 sq. ft. / diluted gallon

### Packaging

4/1 gallon	110600-41
5 gallon	110600-05
55 gallon	110600-55