

Non-Butyl Heavy Foaming Degreaser

Features:

High Foaming Formula Clings to Vertical Surfaces Penetrates and Loosens Soils

Description

This labor-saving product forms a thick, stable foam that clings to vertical surfaces when applied through a "foam gun" apparatus. A longer contact time will allow this product to easily remove grease, oil, fat, dirt, and grime from virtually all washable surfaces.

Versatile and economical, this product is also an effective cleaner/ degreaser when applied by more conventional means such as trigger sprayer, mop or pressure sprayer.

Directions

For foaming applications:

- Dilution requirements will vary depending on the type of foaming device, water temperature, amount and type of soil, desired contact time, etc.
- 2 For best results, experiment with different dilutions to determine which provides the most stable foam with your foaming equipment.
- **3** For most devices, optimum foam production is at 2 oz. of product per gallon of water.
- Adjustments in product concentration may then be made based on cleaning requirements and desired product usage.

For normal soaming and cleaning:

Use 2 oz. of product per gallon of water.

For heavier soils:

erything Clean

- 1 Use up to 6 oz. of product per gallon of water.
- 2 Apply foam liberally to all soiled surfaces and allow sufficient time for foam to penetrate, loosen, emulsify, and dissolve soils.
- **3** Rinse thoroughly with potable water.
- Rinsing under high pressure dramatically enhances results.



Applications

Ideal for:

- > Removing grease, dirt, and grime
- > Foaming applications
- > Cleaning heavier soils

Specifications

Color	Red
Fragrance	None
pH Range	12.5- 13.0
Dilution	2 - 6 oz./gal.
Density	

Packaging

4/1 gallon	245000-41
55 gallon	245000-55



Contact your Account Representative for more information

■ 140 Private Brand Way, Athens, TN 37303 | 800.467.6294 | fax: 423.337.3369 | midlabinc.com