

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0



BUILDING TRUST



Print Date 16.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Everbuild Stick 2 Instant Spray Contact Adhesive

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company
Site 41
Knowsthorpe Way
Cross Green Industrial Estate
Leeds
West Yorkshire LS9 0SW
United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

1.4 Emergency telephone number

Emergency telephone number : 0044 113 240 3456 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2

H315: Causes skin irritation.

Eye irritation, Category 2

H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0

Print Date 16.12.2020



BUILDING TRUST



Signal word	:	Danger	
Hazard statements	:	H222 H229 H315 H319 H336 H412	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.
Precautionary statements	:	P101 P102	If medical advice is needed, have product container or label at hand. Keep out of reach of children.
		Prevention:	
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P211	Do not spray on an open flame or other ignition source.
		P251	Do not pierce or burn, even after use.
		P271	Use only outdoors or in a well-ventilated area.
		Storage:	
		P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
		Disposal:	
		P501	Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0

Print Date 16.12.2020



BUILDING TRUST



acetone	67-64-1 200-662-2 01-2119471330-49-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 10 - < 20
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Not Assigned 931-254-9; 927-510-4 921-024-6 265-151-9 01-2119475514-35-XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
Substances with a workplace exposure limit :			
petroleum gases, liquefied	68476-85-7 270-704-2	Flam. Gas 1; H220	>= 25 - < 40

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Excessive lachrymation
Erythema
Dermatitis
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects

Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0



BUILDING TRUST



Print Date 16.12.2020

Causes serious eye irritation.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0

Print Date 16.12.2020



BUILDING TRUST



section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
petroleum gases, liquefied	68476-85-7	TWA	1.000 ppm 1.750 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if LPG contains more than 0.1% of buta-1,3-diene.			
		STEL	1.250 ppm 2.180 mg/m ³	GB EH40
acetone	67-64-1	TWA	500 ppm 1.210 mg/m ³	2000/39/EC
	Further information: Indicative			
		TWA	500 ppm 1.210 mg/m ³	GB EH40
		STEL	1.500 ppm 3.620 mg/m ³	GB EH40

*The above mentioned values are in accordance with the legislation in effect at the date of the re-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0



BUILDING TRUST



Print Date 16.12.2020

lease of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers).
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor (Type A) and particulate filter
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
P1: Inert material; P2, P3: hazardous substances
Ensure adequate ventilation, especially in confined areas.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : aerosol
Colour : amber
Odour : characteristic
Odour Threshold : No data available
- pH : 7
- Melting point/range / Freezing point : No data available
Boiling point/boiling range : No data available
- Flash point : -60 °C
- Evaporation rate : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0



BUILDING TRUST



Print Date 16.12.2020

Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	13 %(V)
Lower explosion limit / Lower flammability limit	:	0,6 %(V)
Vapour pressure	:	34,6637 hPa
Relative vapour density	:	No data available
Density	:	0,84 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable
Explosive properties	:	No data available
Oxidizing properties	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0



BUILDING TRUST



Print Date 16.12.2020

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Not classified based on available information.

Components:

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): 20.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0



BUILDING TRUST



Print Date 16.12.2020

Not classified based on available information.

STOT - single exposure

Not classified based on available information.
May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.
Not classified based on available information.

Aspiration toxicity

Not classified based on available information.
Not classified based on available information.

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

Components:

acetone:

Toxicity to fish : LC50 (Fish): > 5.000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 12,700 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 530
plants mg/l
Exposure time: 96 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0

Print Date 16.12.2020



BUILDING TRUST



12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

ADR : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2
IMDG : 2.1
IATA : 2.1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0



BUILDING TRUST



Print Date 16.12.2020

14.4 Packing group

ADR

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

International Chemical Weapons Convention (CWC) : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0



BUILDING TRUST



Print Date 16.12.2020

Schedules of Toxic Chemicals and Precursors
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : None of the components are listed (= > 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors
Acquisition, introduction, possession or use of the explosive precursor by the general public is subject to reporting obligations. : acetone (ANNEX II)

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 50 %

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 50 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Other regulations:

75/324/EEC

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0

Print Date 16.12.2020



BUILDING TRUST



SECTION 16: Other information

Full text of H-Statements

- H220 : Extremely flammable gas.
- H225 : Highly flammable liquid and vapour.
- H304 : May be fatal if swallowed and enters airways.
- H315 : Causes skin irritation.
- H319 : Causes serious eye irritation.
- H336 : May cause drowsiness or dizziness.
- H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

- Aquatic Chronic : Long-term (chronic) aquatic hazard
- Asp. Tox. : Aspiration hazard
- Eye Irrit. : Eye irritation
- Flam. Gas : Flammable gases
- Flam. Liq. : Flammable liquids
- Skin Irrit. : Skin irritation
- STOT SE : Specific target organ toxicity - single exposure
- 2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
- GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
- 2000/39/EC / TWA : Limit Value - eight hours
- GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
- GB EH40 / STEL : Short-term exposure limit (15-minute reference period)
- ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
- CAS : Chemical Abstracts Service
- DNEL : Derived no-effect level
- EC50 : Half maximal effective concentration
- GHS : Globally Harmonized System
- IATA : International Air Transport Association
- IMDG : International Maritime Code for Dangerous Goods
- LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
- LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
- MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
- OEL : Occupational Exposure Limit
- PBT : Persistent, bioaccumulative and toxic
- PNEC : Predicted no effect concentration
- REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
- SVHC : Substances of Very High Concern
- vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Classification procedure:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Instant Spray Contact Adhesive

Revision Date 16.12.2020

Version 6.0

Print Date 16.12.2020



BUILDING TRUST



Aerosol 1	H222, H229	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GB / EN