

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2



BUILDING TRUST



Print Date 03.01.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Stick2 Rapid Epoxy Syringe/Tube Resin (A)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company
Site 41
Knowsthorpe Way
Cross Green Industrial Estate
Leeds
West Yorkshire LS9 0SW
United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

1.4 Emergency telephone number

Emergency telephone number : 0044 113 240 3456 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Category 2 H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2



BUILDING TRUST



Print Date 03.01.2020

Signal word	:	Warning	
Hazard statements	:	H315 H317 H319 H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
Precautionary statements	:	P101 P102	If medical advice is needed, have product container or label at hand. Keep out of reach of children.
		Prevention:	
		P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
		P273	Avoid release to the environment.
		P280	Wear protective gloves/ eye protection/ face protection.
		Disposal:	
		P501	Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

- reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Additional Labelling

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6 500-033-5 01-2119456619-26-XXXX	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	≥ 80

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2



BUILDING TRUST



Print Date 03.01.2020

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire- : Do not allow run-off from fire fighting to enter drains or water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2

Print Date 03.01.2020



BUILDING TRUST



fighting courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2

Print Date 03.01.2020



BUILDING TRUST



Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (0,4 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : No special measures required.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2



BUILDING TRUST



Print Date 03.01.2020

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform
respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : yellow

Odour : irritating

Odour Threshold : No data available

pH : No data available

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 150 °C
Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 0,01 hPa

Relative vapour density : No data available

Density : ca. 1,16 g/cm³ (20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2



BUILDING TRUST



Print Date 03.01.2020

Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20,5 mm ² /s (40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20.000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2



BUILDING TRUST



Print Date 03.01.2020

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l
aquatic invertebrates Exposure time: 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Country GB 100000012919

8 / 13

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2

Print Date 03.01.2020



BUILDING TRUST



Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 20 01 27* paint, inks, adhesives and resins containing dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

ADR : UN 3082
IMDG : UN 3082
IATA : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
((reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight > 1100))

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2



BUILDING TRUST



Print Date 03.01.2020

N.O.S.
(reaction product: bisphenol A-(epichlorhydrin) epoxy resin
(number average molecular weight > 1100))

IATA : Environmentally hazardous substance, liquid, n.o.s.
((reaction product: bisphenol A-(epichlorhydrin) epoxy resin
(number average molecular weight > 1100))

14.3 Transport hazard class(es)

ADR : 9

IMDG : 9

IATA : 9

14.4 Packing group

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous Dangerous Goods

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous Dangerous Goods

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2

Print Date 03.01.2020



BUILDING TRUST



Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)
Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High
Concern for Authorisation (Article 59). : None of the components are listed
(=> 0.1 %).

REACH - List of substances subject to authorisation
(Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that de-
plete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-
lutants : Not applicable

REACH - Restrictions on the manufacture, placing on
the market and use of certain dangerous substances,
preparations and articles (Annex XVII) : Not applicable

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma-
jor-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds
(VOCV)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial
emissions (integrated pollution prevention and control)
Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data
Sheet, then it is described in this subsection.

Health, safety and environ- : Environmental Protection Act 1990 & Subsidiary Regulations
mental regulation/legislation Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or Control of Substances Hazardous to Health Regulations

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2

Print Date 03.01.2020



BUILDING TRUST



mixture: (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL : Occupational Exposure Limit
PBT : Persistent, bioaccumulative and toxic
PNEC : Predicted no effect concentration
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC : Substances of Very High Concern
vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Skin Irrit. 2 H315
Eye Irrit. 2 H319
Skin Sens. 1 H317

Classification procedure:

Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019

Version 1.2



BUILDING TRUST



Print Date 03.01.2020

Aquatic Chronic 2

H411

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GB / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1

Print Date 03.01.2020



BUILDING TRUST



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Stick2 Rapid Epoxy Metal Hardener (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company
Site 41
Knowsthorpe Way
Cross Green Industrial Estate
Leeds
West Yorkshire LS9 0SW
United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

1.4 Emergency telephone number

Emergency telephone number : 0044 113 240 3456 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1



BUILDING TRUST



Print Date 03.01.2020

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements :

EUH071 Corrosive to the respiratory tract.

Precautionary statements :

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

- m-phenylenebis(methylamine)
- m-cresol
- Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1



BUILDING TRUST



Print Date 03.01.2020

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	68410-23-1 614-452-7 01-2119972323-38-0000	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 5 - < 10
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319	>= 5 - < 10
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 5 - < 10
m-cresol	108-39-4 203-577-9	Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314	>= 5 - < 10

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1



BUILDING TRUST



Print Date 03.01.2020

If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort
Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.

Risks : Health injuries may be delayed.
corrosive effects
sensitising effects

Harmful if swallowed.
May cause an allergic skin reaction.
Causes serious eye damage.
Corrosive to the respiratory tract.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1

Print Date 03.01.2020



BUILDING TRUST



6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1

Print Date 03.01.2020



BUILDING TRUST



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
Wear eye/face protection.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (0,4 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : No special measures required.

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : white
- Odour : characteristic
- Odour Threshold : No data available
- pH : No data available
- Melting point/range / Freezing point : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1



BUILDING TRUST



Print Date 03.01.2020

Boiling point/boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	19,9983 hPa
Relative vapour density	:	No data available
Density	:	ca. 1,4 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20,5 mm ² /s (40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1



BUILDING TRUST



Print Date 03.01.2020

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Components:

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1.620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

m-cresol:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg
Method: Converted acute toxicity point estimate

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg
Method: Converted acute toxicity point estimate

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1



BUILDING TRUST



Print Date 03.01.2020

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Corrosive to the respiratory tract.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines:

Toxicity to fish (Chronic toxicity) : LC50: 1 - 10 mg/l
Exposure time: 96 d
Species: Oncorhynchus mykiss (rainbow trout)

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h

12.2 Persistence and degradability

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1

Print Date 03.01.2020



BUILDING TRUST



12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

- ADR : UN 2735
IMDG : UN 2735

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019



Version 1.1

Print Date 03.01.2020

IATA : UN 2735

14.2 UN proper shipping name

ADR : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

IMDG : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

IATA : Polyamines, liquid, corrosive, n.o.s.

14.3 Transport hazard class(es)

ADR : 8

IMDG : 8

IATA : 8

14.4 Packing group

ADR

Packing group : II
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

IMDG

Packing group : II
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo aircraft) : 855
Packing instruction (LQ) : Y840
Packing group : II
Labels : Corrosives

IATA (Passenger)

Packing instruction (passenger aircraft) : 851
Packing instruction (LQ) : Y840
Packing group : II
Labels : Corrosives

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1

Print Date 03.01.2020



BUILDING TRUST



Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)
Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High
Concern for Authorisation (Article 59). : None of the components are listed
(=> 0.1 %).

REACH - List of substances subject to authorisation
(Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that de-
plete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-
lutants : Not applicable

REACH - Restrictions on the manufacture, placing on
the market and use of certain dangerous substances,
preparations and articles (Annex XVII) : Not applicable

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma-
jor-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds
(VOCV)
Volatile organic compounds (VOC) content: < 0,01 %
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial
emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content:
9,99 %, 139,87 g/l
VOC content excluding water

If other regulatory information applies that is not already provided elsewhere in the Safety Data
Sheet, then it is described in this subsection.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019

Version 1.1

Print Date 03.01.2020



BUILDING TRUST



Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H311 : Toxic in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL : Occupational Exposure Limit
PBT : Persistent, bioaccumulative and toxic
PNEC : Predicted no effect concentration
REACH : Regulation (EC) No 1907/2006 of the European Parliament

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Stick2 Rapid Epoxy Metal Hardener (B)

Revision Date 21.06.2019



BUILDING TRUST



Version 1.1

Print Date 03.01.2020

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern
vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4	H302
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 3	H412

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GB / EN