

# Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 11

Loctite Super Glue Mini Dose

SDS No.: 590326 V001.4 Revision: 06.02.2023 printing date: 16.05.2023 Replaces version from: 26.07.2022

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

## 1.1. Product identifier

Loctite Super Glue Mini Dose

**1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use: Super glue

## 1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

## **1.4.** Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY-Email: technical.services@henkel.co.uk

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

| Classification (CLP):                            |            |
|--|------------|
| Skin irritation                                  | Category 2 |
| H315 Causes skin irritation.                     |            |
| Serious eye irritation                           | Category 2 |
| H319 Causes serious eye irritation.              |            |
| Specific target organ toxicity - single exposure | Category 3 |
| H335 May cause respiratory irritation.           |            |
| Target organ: respiratory tract irritation       |            |

#### 2.2. Label elements

Label elements (CLP):

| Hazard pictogram:        |  |
|--------------------------|--|
| Contains                 | Ethyl 2-cyanoacrylate  |
| Signal word:             | Warning  |
| Hazard statement:        | H315 Causes skin irritation.<br>H319 Causes serious eye irritation.<br>H335 May cause respiratory irritation.  |
| Supplemental information | EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.   |
| Precautionary statement: | <ul> <li>P261 Avoid breathing vapors.</li> <li>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P302+P352 IF ON SKIN: Wash with plenty of soap and water.</li> <li>P501 Dispose of contents/container in accordance with national regulation.</li> </ul> |

#### 2.3. Other hazards

None if used properly.

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components<br>CAS-No.<br>EC Number<br>REACH-Reg No.       | Concentration | Classification   | Specific Conc. Limits, M-<br>factors and ATEs | Add.<br>Information |
|---|---------------|--|---|---------------------|
| Ethyl 2-cyanoacrylate<br>7085-85-0<br>230-391-5<br>01-2119527766-29 | 85- 100 %     | Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Skin Irrit. 2, H315 | STOT SE 3; H335; C >= 10 %                    |                     |

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

General information: In case of adverse health effects seek medical advice.

#### Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin.

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

Eye contact:

If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

#### Ingestion:

Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media: carbon dioxide, foam, powder, water spray jet, fine water spray

## Extinguishing media which must not be used for safety reasons:

High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

#### 5.3. Advice for firefighters

#### Wear protective equipment.

Wear self-contained breathing apparatus.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Danger of slipping on spilled product. Ensure adequate ventilation.

Avoid contact with skin and eyes.

#### **6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

## 6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust). Dispose of contaminated material as waste according to Section 13.

## 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Open and handle container with care. Avoid skin and eye contact. Ensure that workrooms are adequately ventilated.

Hygiene measures: Do not eat, drink or smoke while working. Wash hands before work breaks and after finishing work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly sealed. Avoid moisture. For optimum shelf live store in original containers under refrigerated conditions at 2°C to 8°C. Store in a cool, well-ventilated place. Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

### 7.3. Specific end use(s)

Super glue

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### **Occupational Exposure Limits**

#### Valid for

Great Britain

| Ingredient [Regulated substance] | ррт | mg/m <sup>3</sup> | ~ 1                 | Short term exposure limit category / Remarks | Regulatory list |
|----------------------------------|-----|-------------------|---------------------|--|-----------------|
| Ethyl 2-cyanoacrylate            | 0,3 | 1,5               | Short Term Exposure | 15 minutes                                   | EH40 WEL        |
| 7085-85-0                        |     |                   | Limit (STEL):       |  |                 |
| [ETHYL CYANOACRYLATE]            |     |                   |                     |  |                 |

#### **Occupational Exposure Limits**

Valid for <sup>T</sup>reland

|  | re | lar |
|--|----|-----|
|  |    |     |

| Ingredient [Regulated substance]  | ррт | mg/m <sup>3</sup> | Value type                           | Short term exposure limit<br>category / Remarks | Regulatory list |
|---|-----|-------------------|--------------------------------------|---|-----------------|
| Ethyl 2-cyanoacrylate<br>7085-85-0<br>[ETHYL 2-CYANOACRYLATE; ETHYL<br>CYANOACRYLATE] | 1   |                   | Short Term Exposure<br>Limit (STEL): | 15 minutes                                      | IR_OEL          |
| Ethyl 2-cyanoacrylate<br>7085-85-0<br>[ETHYL 2-CYANOACRYLATE; ETHYL<br>CYANOACRYLATE] | 0,2 |                   | Time Weighted Average<br>(TWA):      |   | IR_OEL          |

## **Derived No-Effect Level (DNEL):**

| Name on list                       | Application<br>Area   | Route of<br>Exposure | Health Effect                               | Exposure<br>Time | Value      | Remarks |
|------------------------------------|-----------------------|----------------------|---|------------------|------------|---------|
| Ethyl 2-cyanoacrylate<br>7085-85-0 | Workers               | Inhalation           | Long term<br>exposure - local<br>effects    |                  | 9,25 mg/m3 |         |
| Ethyl 2-cyanoacrylate<br>7085-85-0 | Workers               | Inhalation           | Long term<br>exposure -<br>systemic effects |                  | 9,25 mg/m3 |         |
| Ethyl 2-cyanoacrylate<br>7085-85-0 | General population    | Inhalation           | Long term<br>exposure - local<br>effects    |                  | 9,25 mg/m3 |         |
| Ethyl 2-cyanoacrylate<br>7085-85-0 | General<br>population | Inhalation           | Long term<br>exposure -<br>systemic effects |                  | 9,25 mg/m3 |         |

#### **Biological Exposure Indices:**

None

#### 8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation. Combination filter: ABEKP (EN 14387) This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374. material thickness > 0.4 mm

Perforation time > 30 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection: Goggles which can be tightly sealed. Protective eye equipment should conform to EN166.

Skin protection: Suitable protective clothing Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

| Physical state        | liquid  |
|-----------------------|---|
| Delivery form         | liquid  |
| Colour                | colourless, slightly yellowish                            |
| Odor                  | pungent   |
| Melting point         | Not applicable, Product is a liquid                       |
| Initial boiling point | $> 150 \ ^{\circ}C \ (> 302 \ ^{\circ}F)$ Supplier method |
| Flammability          | Currently under determination                             |
| Explosive limits      | Currently under determination                             |
|                       |   |

| Flash point<br>Auto-ignition temperature<br>Decomposition temperature | 80 °C (176 °F); Supplier method<br>Currently under determination<br>Not applicable, Substance/mixture is not self-reactive, no<br>organic peroxide and does not decompose under foreseen |
|---|--|
|   | conditions of use  |
| pH  | Not applicable, Product reacts with water.   |
| Viscosity (kinematic)   | Currently under determination  |
| Viscosity, dynamic  | 30 - 60 mPa.s no method  |
| (; 25 °C (77 °F))   |  |
| Solubility (qualitative)  | Insoluble  |
| (20 °C (68 °F); Solvent: Water)                                       |  |
| Partition coefficient: n-octanol/water                                | Not applicable   |
|   | Mixture  |
| Vapour pressure   | Currently under determination  |
| Density   | 0,55 - 1,55 g/cm3 Supplier method  |
| (20 °C (68 °F))   |  |
| Relative vapour density:  | Currently under determination  |

**9.2.** Other information

Particle characteristics

Other information not applicable for this product

Currently under determination Not applicable Product is a liquid

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

## 10.2. Chemical stability

Stable under recommended storage conditions.

## 10.3. Possibility of hazardous reactions

See section reactivity

#### **10.4.** Conditions to avoid None if used for intended purpose.

**10.5. Incompatible materials** 

See section reactivity.

10.6. Hazardous decomposition products None known.

# **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances<br>CAS-No.    | Value<br>type | Value         | Species | Method  |
|------------------------------------|---------------|---------------|---------|---|
| Ethyl 2-cyanoacrylate<br>7085-85-0 | LD50          | > 5.000 mg/kg | rat     | equivalent or similar to OECD Guideline 423 (Acute Oral toxicity) |

#### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances  | Value | Value         | Species | Method   |
|-----------------------|-------|---------------|---------|--|
| CAS-No.               | type  |               |         |  |
| Ethyl 2-cyanoacrylate | LD50  | > 2.000 mg/kg | rabbit  | equivalent or similar to OECD Guideline 402 (Acute |
| 7085-85-0             |       |               |         | Dermal Toxicity)                                   |

#### Acute inhalative toxicity:

No data available.

#### Skin corrosion/irritation:

Bonds skin in seconds. Considered to be of low toxicity: acute dermal LD50 (rabbit)>2000mg/kg Due to polymerisation at the skin surface allergic reaction is unlikely to occur

| Hazardous substances<br>CAS-No.    | Result                 | Exposure<br>time | Species | Method   |
|------------------------------------|------------------------|------------------|---------|--|
| Ethyl 2-cyanoacrylate<br>7085-85-0 | slightly<br>irritating | 24 h             | rabbit  | equivalent or similar to OECD Guideline 404 (Acute<br>Dermal Irritation / Corrosion) |

#### Serious eye damage/irritation:

Liquid product will bond eyelids. In a dry atmosphere (RH<50%) vapours may cause irritation and lachrymatory effect

| Hazardous substances<br>CAS-No.    | Result     | Exposure<br>time | Species | Method   |
|------------------------------------|------------|------------------|---------|--|
| Ethyl 2-cyanoacrylate<br>7085-85-0 | irritating |                  | rabbit  | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

#### **Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances<br>CAS-No.    | Result          | Test type          | Species    | Method        |
|------------------------------------|-----------------|--------------------|------------|---------------|
| Ethyl 2-cyanoacrylate<br>7085-85-0 | not sensitising | Skin sensitisation | guinea pig | not specified |

## Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | Result   | Type of study /<br>Route of | Metabolic<br>activation / | Species | Method                        |
|---------------------------------|----------|-----------------------------|---------------------------|---------|-------------------------------|
|                                 |          | administration              | Exposure time             |         |                               |
| Ethyl 2-cyanoacrylate           | negative | bacterial reverse           | with and without          |         | equivalent or similar to OECD |
| 7085-85-0                       | -        | mutation assay (e.g         |                           |         | Guideline 471 (Bacterial      |
|                                 |          | Ames test)                  |                           |         | Reverse Mutation Assay)       |
| Ethyl 2-cyanoacrylate           | negative | in vitro mammalian          | with and without          |         | OECD Guideline 473 (In vitro  |
| 7085-85-0                       | -        | chromosome                  |                           |         | Mammalian Chromosome          |
|                                 |          | aberration test             |                           |         | Aberration Test)              |
| Ethyl 2-cyanoacrylate           | negative | mammalian cell              | with and without          |         | OECD Guideline 476 (In vitro  |
| 7085-85-0                       | -        | gene mutation assay         |                           |         | Mammalian Cell Gene           |
|                                 |          |                             |                           |         | Mutation Test)                |

## Carcinogenicity

No data available.

## **Reproductive toxicity:**

No data available.

## STOT-single exposure:

No data available.

## **STOT-repeated exposure:**

No data available.

#### Aspiration hazard:

No data available.

## 11.2 Information on other hazards

not applicable

# **SECTION 12: Ecological information**

## General ecological information:

Do not empty into drains, soil or bodies of water.

## 12.1. Toxicity

Toxicity (Fish):

No data available.

## Toxicity (Daphnia):

No data available.

## Chronic toxicity to aquatic invertebrates

No data available.

## Toxicity (Algae):

No data available.

#### Toxicity to microorganisms

No data available.

## 12.2. Persistence and degradability

| Hazardous substances               | Result                     | Test type | Degradability | Exposure | Method  |
|------------------------------------|----------------------------|-----------|---------------|----------|---|
| CAS-No.                            |                            |           |               | time     |   |
| Ethyl 2-cyanoacrylate<br>7085-85-0 | not readily biodegradable. | aerobic   | 57 %          | 28 d     | OECD Guideline 301 D (Ready<br>Biodegradability: Closed Bottle<br>Test) |

## 12.3. Bioaccumulative potential

No data available.

## 12.4. Mobility in soil

| Hazardous substances<br>CAS-No.    | LogPow | Temperature | Method                                |
|------------------------------------|--------|-------------|---------------------------------------|
| Ethyl 2-cyanoacrylate<br>7085-85-0 | 0,776  | 22 °C       | EU Method A.8 (Partition Coefficient) |

## 12.5. Results of PBT and vPvB assessment

| Hazardous substances<br>CAS-No.    | PBT / vPvB  |
|------------------------------------|---|
| Ethyl 2-cyanoacrylate<br>7085-85-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

## 12.6. Endocrine disrupting properties

not applicable

## 12.7. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Product disposal: Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code 080409

# **SECTION 14: Transport information**

| 14.1. | UN numbe      | UN number or ID number   |  |  |  |  |
|-------|---------------|--|--|--|--|--|
|       | ADR           | Not dangerous goods  |  |  |  |  |
|       | RID           | Not dangerous goods  |  |  |  |  |
|       | ADN           | Not dangerous goods  |  |  |  |  |
|       | IMDG          | Not dangerous goods  |  |  |  |  |
|       | IATA          | 3334   |  |  |  |  |
| 14.2. | UN proper     | shipping name  |  |  |  |  |
|       | ADR           | Not dangerous goods  |  |  |  |  |
|       | RID           | Not dangerous goods  |  |  |  |  |
|       | ADN           | Not dangerous goods  |  |  |  |  |
|       | IMDG          | Not dangerous goods  |  |  |  |  |
|       | IATA          | Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)                            |  |  |  |  |
| 14.3. | Transport     | hazard class(es)   |  |  |  |  |
|       | ADR           | Not dangerous goods  |  |  |  |  |
|       | RID           | Not dangerous goods  |  |  |  |  |
|       | ADN           | Not dangerous goods  |  |  |  |  |
|       | IMDG          | Not dangerous goods  |  |  |  |  |
|       | IATA          | 9  |  |  |  |  |
| 14.4. | Packing group |  |  |  |  |  |
|       | ADR           | Not dangerous goods  |  |  |  |  |
|       | RID           | Not dangerous goods  |  |  |  |  |
|       | ADN           | Not dangerous goods  |  |  |  |  |
|       | IMDG          | Not dangerous goods  |  |  |  |  |
|       | IATA          | Ш  |  |  |  |  |
| 14.5. | Environme     | ental hazards  |  |  |  |  |
|       | ADR           | not applicable   |  |  |  |  |
|       | RID           | not applicable   |  |  |  |  |
|       | ADN           | not applicable   |  |  |  |  |
|       | IMDG          | not applicable   |  |  |  |  |
|       | IATA          | not applicable   |  |  |  |  |
| 14.6. | Special pre   | cautions for user  |  |  |  |  |
|       | ADR           | not applicable   |  |  |  |  |
|       | RID           | not applicable   |  |  |  |  |
|       | ADN           | not applicable   |  |  |  |  |
|       | IMDG          | not applicable   |  |  |  |  |
|       | IATA          | Primary packs containing less than 500ml are unregulated by this mode of transport |  |  |  |  |
|       |               | and may be shipped unrestricted.   |  |  |  |  |
| 14.7. | Maritime t    | ransport in bulk according to IMO instruments                                      |  |  |  |  |
|       | not applicat  | ble  |  |  |  |  |

# SECTION 15: Regulatory information

No information available:

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):Not applicablePrior Informed Consent (PIC) (Regulation (EU) No 649/2012):Not applicablePersistent organic pollutants (Regulation (EU) 2019/1021):Not applicable

#### 15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

## **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

| ED:         | Substance identified as having endocrine disrupting properties                           |
|-------------|--|
| EU OEL:     | Substance with a Union workplace exposure limit  |
| EU EXPLD 1: | Substance listed in Annex I, Reg (EC) No. 2019/1148                                      |
| EU EXPLD 2  | Substance listed in Annex II, Reg (EC) No. 2019/1148                                     |
| SVHC:       | Substance of very high concern (REACH Candidate List)                                    |
| PBT:        | Substance fulfilling persistent, bioaccumulative and toxic criteria                      |
| PBT/vPvB:   | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very |
|             | bioaccumulative criteria   |
| vPvB:       | Substance fulfilling very persistent and very bioaccumulative criteria                   |

#### **Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

#### Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.