

Page 1/10

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 109

Revision: 10.09.2020

1.1 Product identifier	
	® DECO SPRAY PAINT RAL VARIOUS COLOURS 400 ML
No further relevant in Sector of Use SU21 Consumer use	d uses of the substance or mixture and uses advised against formation available. s: Private households / general public / consumers
Product category PC Process category PROC7 Industrial sp PROC11 Non indust	rial spraying
	bstance / the mixture Paint
1.5 Details of the sup Manufacturer/Suppli MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolveg The Netherlands Tel: +31 (0)561 6944	a
Fax: +31 (0)561 6944 e-mail: msds@nl.mot	411
<i>Further information</i> <i>1.4 Emergency teleph</i> +31 (0)561-694400 (0	
UK: NPIS National P	oisons Information Centre Tel: +44 0344 892 0111
SECTION 2. U.	ands identification
	ards identification
	the substance or mixture ing to Regulation (EC) No 1272/2008
🔨 💞 🔪 flame	
<u>y</u> jume	
\checkmark	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
\checkmark	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
\checkmark	29 Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation.

(Contd. on page 2) GB Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 109

Revision: 10.09.2020

GB

Trade name: MOTIP® DECO SPRAY PAINT RAL VARIOUS COLOURS 400 ML

Hazard p	contd. of page
$\mathbf{\Lambda}$	
()	
\sim	\mathbf{V}
GHS02	GHS07
Signal w	ord Danger
Hazard-a	letermining components of labelling:
acetone	
Hydroca	rbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
	tatements
H222-H2	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precauti	onary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P410+P4	412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents / container in accordance with regional regulations.
Addition	al information:
	Repeated exposure may cause skin dryness or cracking.
	of explosive mixtures possible without sufficient ventilation.
	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or
	mist.
2.3 Other	r hazards
Results of	f PBT and vPvB assessment

- suus of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes,cyclics, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	12.5-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<12.5%

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 109

Revision: 10.09.2020

Trade name: MOTIP® DECO SPRAY PAINT RAL VARIOUS COLOURS 400 ML

	Contd. of page 2)
isobutane	10-<12.5%
🚸 Flam. Gas 1A, H220	
Press. Gas (Comp.), H280	
titanium dioxide	<2.5%
& Carc. 2, H351	
strontium(II) 2-ethylhexanoate	≤ 0.5%
🚸 Repr. 2, H361	
Eye Dam. 1, H318	
Acute Tox. 4, H302; Skin Irrit. 2, H315	
Oleic acid, compound with (Z)-N-octadec-9-enylpropane-	≤ 0.5%
1,3-diamine (2:1)	
🔇 🕹 STOT RE 2, H373	
Aquatic Acute 1, H400 (M=10); Aquatic Chronic 2, H411	
N Skin Irrit. 2, H315; Eye Irrit. 2, H319	
	isobutane ♦ Flam. Gas 1A, H220 Press. Gas (Comp.), H280 titanium dioxide ♦ Carc. 2, H351 strontium(II) 2-ethylhexanoate ♦ Repr. 2, H361 ► Eye Dam. 1, H318 ↑ Acute Tox. 4, H302; Skin Irrit. 2, H315 Oleic acid, compound with (Z)-N-octadec-9-enylpropane- 1,3-diamine (2:1) × ♦ STOT RE 2, H373 ♦ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 2, H411

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -

*

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Keep away from ignition sources.
 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB

Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 109

Revision: 10.09.2020

(Contd. of page 3)

Trade name: MOTIP® DECO SPRAY PAINT RAL VARIOUS COLOURS 400 ML

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- **Requirements to be met by storerooms and receptacles:** Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

· Storage class: 2 B

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

- 67-64-1 acetone
- WEL Short-term value: 3620 mg/m³, 1500 ppm
 - Long-term value: 1210 mg/m³, 500 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Avoid contact with the eyes.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3
• **Protection of hands:**



Protective gloves

(Contd. on page 5)

GB

Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 109

Revision: 10.09.2020

Trade name: MOTIP® DECO SPRAY PAINT RAL VARIOUS COLOURS 400 ML

(Contd. of page 4)

• *Material of gloves Butyl rubber, BR*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

• *Penetration time of glove material Butyl rubber gloves with a thickness of 0.4 mm are resistant to:*

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

• Eye protection:



*

Tightly sealed goggles

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and c	hemical properties	
· General Information		
· Appearance:		
Form:	Aerosol	
Colour:	Different according to colouring	
· Odour:	Solvent-like	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range	: Not applicable, as aerosol.	
· Flash point:	Not applicable, as aerosol.	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Explosive properties:	Not determined.	
· Explosion limits:		
Lower:	0.6 Vol %	
Upper:	13 Vol %	
· Vapour pressure at 20 °C (68 °F):	3500 hPa (2625.2 mm Hg)	
• Density at 20 •C (68 •F):	0.8 g/cm ³ (6.7 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
		(Contd. on page

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 109

Revision: 10.09.2020

Trade name: MOTIP® DECO SPRAY PAINT RAL VARIOUS COLOURS 400 ML

		(Contd. of page 5)
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	83.0 %	
VOC (EC)		
	629.0 g/l	
· VOC-EU%	82.98 %	
· Solids content:	17.0 %	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification: 67-64-1 acetone

×

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)

Inhalative LC50/4h 76 mg/l (rat)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral	LD50	>5000 mg/kg (rat)

Dermal LD50 > 3000 mg/kg (rab)

Inhalative LC50/4h > 4951 mg/m3 (rat)

 2457-02-5 strontium(II) 2-ethylhexanoate

 Oral
 LD50
 2043 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rat)

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

 \cdot Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)

⁻ GB

Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 109

Revision: 10.09.2020

Trade name: MOTIP® DECO SPRAY PAINT RAL VARIOUS COLOURS 400 ML

(Contd. of page 6)

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12. Each	la ai a al is	formation
SECTION 12: Ecol	ogicai ii	ijormation

· 12.1 Toxicity

• Aquatic toxicity:

67-64-1 acetone

LC50/96h 8300 mg/l (fish)

EC50/96h 7200 mg/l (algae)

LC50 / 48 h 8450 mg/l (crustacean (water flea))

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- \cdot Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

- *PBT:* Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

- 14.1 UN-Number		
· ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
·IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	
· 14.3 Transport hazard class(es) · ADR		
· Class	2 5F Gases.	

Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 109

Revision: 10.09.2020

Trade name: MOTIP® DECO SPRAY PAINT RAL VARIOUS COLOURS 400 ML

	(Contd. of page
Label	2.1
IMDG, IATA	
Class Label	2.1 2.1
14.4 Packing group ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Gases.
EMS Number:	F- D , S - U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre
	Category A. For AEROSOLS with a capacity above 1 litre
	Category B. For WASTE AEROSOLS: Category C, Clear
Sugregation Code	of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre
Segregation Code	Soby For AEROSOLS with a maximum capacity of 1 title Segregation as for class 9. Stow "separated from" class 1
	except for division 1.4.
	<i>For AEROSOLS with a capacity above 1 litre:</i>
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Annex II	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0 Not normitted as Excepted Quantity
Transport category	Not permitted as Excepted Quantity 2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

2

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 109

Revision: 10.09.2020

(Contd. of page 8)

Trade name: MOTIP® DECO SPRAY PAINT RAL VARIOUS COLOURS 400 ML

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t• Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57
- None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: msds@nl.motipdupli.com
- Abbreviations and acronyms:
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 109

Revision: 10.09.2020

Trade name: MOTIP® DECO SPRAY PAINT RAL VARIOUS COLOURS 400 ML

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 • * **Data compared to the previous version altered.** (Contd. of page 9)