

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Version number 115 Printing date 10.02.2021 Revision: 17.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MOTIP® QUICK START 500 ML
- · Article number: 090405
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC0 Other

PC14 Metal surface treatment products

· Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Auxiliary
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400 Fax: +31 (0)561 694411

e-mail: msds@nl.motipdupli.com

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1



STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 10.02.2021 Version number 115 Revision: 17.12.2019

Trade name: MOTIP® QUICK START 500 ML

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

· Signal word Danger

· Hazard-determining components of labelling:

diethyl ether pentane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

\cdot Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 60-29-7 EINECS: 200-467-2 Index number: 603-022-00-4 Reg.nr.: 01-2119535785-29	diethyl ether Flam. Liq. 1, H224 Acute Tox. 4, H302; STOT SE 3, H336	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane	12.5-<20%

GB

Printing date 10.02.2021 Version number 115 Revision: 17.12.2019

Trade name: MOTIP® QUICK START 500 ML

		(Contd. of page 2)
CAS: 109-66-0	pentane	12.5-<20%
EINECS: 203-692-4 Index number: 601-006-00-1 Reg.nr.: 01-2119459286-30	 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336 	
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<12.5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane Flam. Gas IA, H220 Press. Gas (Comp.), H280	10-<12.5%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

· Additional information: For the wording of the listed hazard phrases refer to section 16.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textbf{4.3 Indication of any immediate medical attention and special treatment needed}$

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- \cdot 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB

Printing date 10.02.2021 Version number 115 Revision: 17.12.2019

Trade name: MOTIP® QUICK START 500 ML

(Contd. of page 3)

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- \cdot 7.3 *Specific end use(s) No further relevant information available.*

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

60-29-7 diethyl ether

WEL Short-term value: 620 mg/m³, 200 ppm Long-term value: 310 mg/m³, 100 ppm

109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

- · Protection of hands: Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection: Not required.

 Printing date 10.02.2021
 Version number 115
 Revision: 17.12.2019

Trade name: MOTIP® QUICK START 500 ML

(Contd. of page 4)

0.1 Information on basic physical and of	hamiaal proparties	
9.1 Information on basic physical and chemical properties General Information		
Appearance:		
Form:	Aerosol	
Colour:	Clear	
Odour:	Ether-like	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	: Not applicable, as aerosol.	
Flash point:	Not applicable, as aerosol.	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	170 °C (338 °F)	
Decomposition temperature:	Not determined.	
Explosive properties:	Not determined.	
Explosion limits:		
Lower:	1.4 Vol %	
Upper:	36 Vol %	
Vapour pressure at 20 °C (68 °F):	3500 hPa (2625.2 mm Hg)	
Density at 20 °C (68 °F):	0.6 g/cm³ (5 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity: Dynamic: Not determined.		
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	99.6 %	
VÕC (EC)		
, ,	630.4 g/l	
VOC-EU%	99.58 %	
Solids content:	0.0 %	
	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

Printing date 10.02.2021 Version number 115 Revision: 17.12.2019

Trade name: MOTIP® QUICK START 500 ML

(Contd. of page 5)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
60-29-7 di	60-29-7 diethyl ether		
Oral	LD50	855-2352 mg/kg (rat)	
Dermal	LD50	>20000 mg/kg (rab)	
Inhalative	LC50/4 h	73000 mg/m3 (rat)	
109-66-0 р	109-66-0 pentane		
Oral	LD50	>5000 mg/kg (rat)	
Inhalative	LC50/4h	25.3 mg/l (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

	· Aquatic toxicity:				
	60-29-7 diethyl ether				
	EC50 (24h)	165 mg/l (daphnia magna)			
	EC50	5600 mg/l (Photobacterium phosphoreum) EC50 / 15 min			
	LC50/48h	48 h 2840 mg/l (Leuciscus idus)			
	109-66-0 pentane				
	EC50 / 48 h	h 9.7 mg/l (daphnia magna)			
	EC50/96h 4.26 mg/l (fish)				
LC50/96h 4.26 mg/l (fish)					

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- $\cdot \textbf{12.4 Mobility in soil} \ \textit{No further relevant information available}.$
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

(Contd. on page 7)

 Printing date 10.02.2021
 Version number 115
 Revision: 17.12.2019

Trade name: MOTIP® QUICK START 500 ML

(Contd. of page 6)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
$\cdot ADR$	1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
·ADR	
· Class	2 5F Gases.
· Label	2.1
· Class	2.1
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 li
	Category A. For AEROSOLS with a capacity above 1 la Category B. For WASTE AEROSOLS: Category C, Cle
	of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 li

except for division 1.4.

(Contd. on page 8)

Printing date 10.02.2021 Version number 115 Revision: 17.12.2019

Trade name: MOTIP® QUICK START 500 ML

	(Contd. of page
	For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Anne	ex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot ADR$	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H224 Extremely flammable liquid and vapour.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: R&D legislation and regulatory advisor

(Contd. on page 9)

Printing date 10.02.2021 Version number 115 Revision: 17.12.2019

Trade name: MOTIP® QUICK START 500 ML

(Contd. of page 8)

· Contact: msds@nl.motipdupli.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 1: Flammable liquids – Category 1

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity - Category 4

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.

CD