

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 12

SDS No.: 550577

V002.1 Revision: 23.03.2022

printing date: 21.01.2023

Replaces version from: 09.12.2021

Loctite Superglue Perfect / Creative Pen

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite Superglue Perfect / Creative Pen

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Super glue

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation.

Target organ: respiratory tract irritation

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains Ethyl 2-cyanoacrylate

Signal word: Warning

Hazard statement: H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Supplemental information EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of

children.

Precautionary statement:

Prevention

P261 Avoid breathing vapors.

Precautionary statement: P3

Response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

Precautionary statement:

Disposal

P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration >= 0.1% and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M- factors and ATEs | Add. Information |
|---|---------------|--|---|---------------------|
| Ethyl 2-cyanoacrylate 7085-85-0 230-391-5 01-2119527766-29 | 80- < 100 % | Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 | STOT SE 3; H335; C >= 10 % | |

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin.

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

Eye contact:

If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

Ingestion:

Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Danger of slipping on spilled product.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Open and handle container with care.

Avoid skin and eye contact.

Ensure that workrooms are adequately ventilated.

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Storage at 2 to 8°C is recommended.

Refer to Technical Data Sheet

Keep container tightly sealed and store in a frost free place.

Store in a cool, dry place.

Temperatures between 0 °C and + 30 °C

7.3. Specific end use(s)

Super glue

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | V 1 | Short term exposure limit category / Remarks | Regulatory list |
|----------------------------------|-----|-------------------|--------------------------------------|--|-----------------|
| Ethyl 2-cyanoacrylate 7085-85-0 | 0,3 | 1,5 | Short Term Exposure Limit (STEL): | 15 minutes | EH40 WEL |
| [ETHYL CYANOACRYLATE] | | | Z (5122). | | |

Occupational Exposure Limits

Valid for

Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|--------------------------------------|--|-----------------|
| Ethyl 2-cyanoacrylate 7085-85-0 [ETHYL 2-CYANOACRYLATE; ETHYL CYANOACRYLATE] | 1 | | Short Term Exposure Limit (STEL): | 15 minutes | IR_OEL |
| Ethyl 2-cyanoacrylate 7085-85-0 [ETHYL 2-CYANOACRYLATE; ETHYL CYANOACRYLATE] | 0,2 | | Time Weighted Average (TWA): | | IR_OEL |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|------------------------------------|-----------------------|----------------------|---|------------------|------------|---------|
| Ethyl 2-cyanoacrylate 7085-85-0 | | | | 9,25 mg/m3 | | |
| Ethyl 2-cyanoacrylate 7085-85-0 | Workers | Inhalation | Long term exposure - systemic effects | | 9,25 mg/m3 | |
| Ethyl 2-cyanoacrylate 7085-85-0 | General population | Inhalation | Long term exposure - local effects | | 9,25 mg/m3 | |
| Ethyl 2-cyanoacrylate 7085-85-0 | General population | Inhalation | Long term exposure - systemic effects | | 9,25 mg/m3 | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Combination filter: ABEKP (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374. material thickness > 0.4 mm

Perforation time > 30 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eve protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid
Delivery form gel
Colour colourless
Odor irritating

Initial boiling point > 149 °C (> 300.2 °F) Flash point 80 - 93 °C (176 - 199.4 °F)

pH Not applicable, Product reacts with water.

Viscosity, dynamic 18.000,00 - 40.000,00 mPa.s LCT STM 10; Viscosity

(BROOKFIELD WITH HELIPATH; Brookfield

Instrument: RVT; 25 °C (77 °F); speed of rotation: 20 min-1; Spindle No: TC)

Solubility (qualitative) Polymerises in presence of water.

Vapour pressure < 0,2 mm hg;no method Vapour pressure < 26,7 Pa;no method Vapour pressure < 700 mbar;no method

(50 °C (122 °F))

Density 1,05 g/cm3 no method

(20 °C (68 °F))

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

General toxicological information:

Persons suffering from allergic reactions to acrylates should avoid contact with the product.

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---------------------------------|---------------|---------------|---------|---|
| Ethyl 2-cyanoacrylate 7085-85-0 | LD50 | > 5.000 mg/kg | rat | equivalent or similar to OECD Guideline 423 (Acute Oral toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Species | Method |
|-----------------------|-------|---------------|---------|--|
| CAS-No. | type | | | |
| Ethyl 2-cyanoacrylate | LD50 | > 2.000 mg/kg | rabbit | equivalent or similar to OECD Guideline 402 (Acute |
| 7085-85-0 | | | | Dermal Toxicity) |

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

Bonds skin in seconds. Considered to be of low toxicity: acute dermal LD50 (rabbit)>2000mg/kg Due to polymerisation at the skin surface allergic reaction is unlikely to occur

| Hazardous substances | Result | Exposure | Species | Method |
|-----------------------|------------|----------|---------|--|
| CAS-No. | | time | | |
| Ethyl 2-cyanoacrylate | slightly | 24 h | rabbit | equivalent or similar to OECD Guideline 404 (Acute |
| 7085-85-0 | irritating | | | Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

Liquid product will bond eyelids. In a dry atmosphere (RH<50%) vapours may cause irritation and lachrymatory effect

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|------------------------------|------------|---------------|---------|--|
| Ethyl 2-cyanoacrylate | irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye |
| 7085-85-0 | | | | Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|---------------------------------|-----------------|--------------------|------------|---------------|
| Ethyl 2-cyanoacrylate | not sensitising | Skin sensitisation | guinea pig | not specified |
| 7085-85-0 | | | | |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|---------------------------------|----------|--|--|---------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Ethyl 2-cyanoacrylate 7085-85-0 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Ethyl 2-cyanoacrylate 7085-85-0 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |

| | | adiminstration | Exposure time | |
|-----------------------|----------|---------------------|------------------|-------------------------------|
| Ethyl 2-cyanoacrylate | negative | bacterial reverse | with and without | equivalent or similar to OECD |
| 7085-85-0 | | mutation assay (e.g | | Guideline 471 (Bacterial |
| | | Ames test) | | Reverse Mutation Assay) |
| Ethyl 2-cyanoacrylate | negative | in vitro mammalian | with and without | OECD Guideline 473 (In vitro |
| 7085-85-0 | | chromosome | | Mammalian Chromosome |
| | | aberration test | | Aberration Test) |
| Ethyl 2-cyanoacrylate | negative | mammalian cell | with and without | OECD Guideline 476 (In vitro |
| 7085-85-0 | | gene mutation assay | | Mammalian Cell Gene |
| | | | | Mutation Test) |
| | | | | |
| Carcinogenicity | | | | |
| No data available. | | | | |
| | | | | |

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure::

No data available.

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

No data available.

Toxicity (Daphnia):

No data available.

Chronic toxicity to aquatic invertebrates

No data available.

Toxicity (Algae):

No data available.

Toxicity to microorganisms

No data available.

12.2. Persistence and degradability

| Hazardous substances | Result | Test type | Degradability | Exposure | Method |
|---------------------------------|----------------------------|-----------|---------------|----------|---|
| CAS-No. | | | | time | |
| Ethyl 2-cyanoacrylate 7085-85-0 | not readily biodegradable. | aerobic | 57 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|------------------------------------|--------|-------------|---------------------------------------|
| Ethyl 2-cyanoacrylate 7085-85-0 | 0,776 | 22 °C | EU Method A.8 (Partition Coefficient) |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|------------------------------------|---|
| Ethyl 2-cyanoacrylate 7085-85-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code 080409

SECTION 14: Transport information

14.1. UN number

ADR Not dangerous goods
RID Not dangerous goods
ADN Not dangerous goods
IMDG Not dangerous goods

IATA 3334

14.2. UN proper shipping name

ADR Not dangerous goods
RID Not dangerous goods
ADN Not dangerous goods
IMDG Not dangerous goods

IATA Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)

14.3. Transport hazard class(es)

ADR Not dangerous goods
RID Not dangerous goods
ADN Not dangerous goods
IMDG Not dangerous goods

IATA 9

14.4. Packing group

ADR Not dangerous goods
RID Not dangerous goods
ADN Not dangerous goods
IMDG Not dangerous goods

IATA III

14.5. Environmental hazards

ADR not applicable
RID not applicable
ADN not applicable
IMDG not applicable
IATA not applicable

14.6. Special precautions for user

ADR not applicable

RID not applicable ADN not applicable IMDG not applicable

IATA Primary packs containing less than 500ml are unregulated by this mode of transport

and may be shipped unrestricted.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

No information available:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):

Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable

Not applicable

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

ED: Substance identified as having endocrine disrupting properties

EU OEL: Substance with a Union workplace exposure limit
EU EXPLD 1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2 Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC: Substance of very high concern (REACH Candidate List)
PBT: Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

Annex - Exposure Scenarios:

Exposure Scenarios for ethyl 2-cyanoacrylate can be downloaded under the following link: https://mysds.henkel.com/index.html#/appSelection