

## Safety data sheet according to 1907/2006/EC, Article 31

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **PLASTI-KOTE® T&S 25606 PLASTIC PRIMER 6UC 400 ML**

Article number: 440.0025606.076

1.2 Relevant identified uses of the substance or mixture and uses advised against  
No further relevant information available.

#### Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

#### Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Preparation

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

Nederland

Tel : +31 (0)561 694400

Fax: +31 (0)561 694411

e-mail: info@nl.motipdupli.com

Further information obtainable from: Department Product Safety

#### 1.4 Emergency telephone number:

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.09.2020

Version number 54

Revision: 17.12.2019

**Trade name: PLASTI-KOTE® T&S 25606 PLASTIC PRIMER 6UC 400 ML**

(Contd. of page 1)

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02    GHS07    GHS09

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

· **Hazard statements**

H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*

H315 *Causes skin irritation.*

H336 *May cause drowsiness or dizziness.*

H411 *Toxic to aquatic life with long lasting effects.*

· **Precautionary statements**

P101 *If medical advice is needed, have product container or label at hand.*

P102 *Keep out of reach of children.*

P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*

P211 *Do not spray on an open flame or other ignition source.*

P251 *Do not pierce or burn, even after use.*

P260 *Do not breathe spray.*

P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*

P501 *Dispose of contents / container in accordance with regional regulations.*

· **Additional information:**

*Buildup of explosive mixtures possible without sufficient ventilation.*

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	50-<75%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-<50%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32-xxxx	xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.09.2020

Version number 54

Revision: 17.12.2019

**Trade name: PLASTI-KOTE® T&S 25606 PLASTIC PRIMER 6UC 400 ML**

(Contd. of page 2)

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

**Trade name: PLASTI-KOTE® T&S 25606 PLASTIC PRIMER 6UC 400 ML**

(Contd. of page 3)

### SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**115-10-6 dimethyl ether**

WEL	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm Long-term value: 766 mg/m <sup>3</sup> , 400 ppm
-----	---

**xylene**

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
-----	--

· **Ingredients with biological limit values:**

**xylene**

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Protection of hands:**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min  
Butyl acetate: 60 min  
Ethyl acetate: 170 min  
Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.09.2020

Version number 54

Revision: 17.12.2019

Trade name: **PLASTI-KOTE® T&S 25606 PLASTIC PRIMER 6UC 400 ML**· **Eye protection:** Not required.

(Contd. of page 4)

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

##### · Appearance:

· <b>Form:</b>	Aerosol
· <b>Colour:</b>	Colourless
· <b>Odour:</b>	Solvent-like
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

##### · Change in condition

· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Initial boiling point and boiling range:</b>	Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** >200 °C (>392 °F)

· **Decomposition temperature:** Not determined.

· **Explosive properties:** Not determined.

##### · Explosion limits:

· <b>Lower:</b>	0.6 Vol %
· <b>Upper:</b>	26.2 Vol %

· **Vapour pressure at 20 °C (68 °F):** 4000 hPa (3000.2 mm Hg)

· **Density at 20 °C (68 °F):** 0.7 g/cm<sup>3</sup> (5.8 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

##### · Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

##### · Viscosity:

· <b>Dynamic:</b>	Not determined.
· <b>Kinematic:</b>	Not determined.

##### · Solvent content:

· <b>Organic solvents:</b>	99.0 %
· <b>VOC (EC)</b>	---
	699.9 g/l
· <b>VOC-EU%</b>	98.99 %

· **Solids content:** 0.9 %

· **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

#### · 10.2 Chemical stability

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.09.2020

Version number 54

Revision: 17.12.2019

Trade name: **PLASTI-KOTE® T&S 25606 PLASTIC PRIMER 6UC 400 ML**

(Contd. of page 5)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rab)
Inhalative	LC50 / 4h	>25.2 mg/l (rat)

##### xylene

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29000 mg/m <sup>3</sup> (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC50 / 48 h	3 mg/l (daphnia magna)
EC50 / 72 h	30-100 mg/l (algae)
LC50 / 96 h	11.4 mg/l (fish)

##### 115-10-6 dimethyl ether

EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50 / 96 h	>4000 mg/l (fish)

##### xylene

EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish

(Contd. on page 7)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.09.2020

Version number 54

Revision: 17.12.2019

**Trade name: PLASTI-KOTE® T&S 25606 PLASTIC PRIMER 6UC 400 ML**

(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

20 01 13*	solvents
15 01 04	metallic packaging

- **Uncleaned packaging:**
- **Recommendation:**  
Disposal must be made according to official regulations.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material.  
Buildup of explosive mixtures possible without sufficient ventilation.

**SECTION 14: Transport information**

- **14.1 UN-Number**  
· **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**  
· **ADR** 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS  
· **IMDG** AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane), MARINE POLLUTANT  
· **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



- **Class** 2 5F Gases.
- **Label** 2.1

· **IMDG**



- **Class** 2.1

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.09.2020

Version number 54

Revision: 17.12.2019

Trade name: **PLASTI-KOTE® T&S 25606 PLASTIC PRIMER 6UC 400 ML**

(Contd. of page 7)

· **Label** 2.1· **IATA**· **Class** 2.1· **Label** 2.1· **14.4 Packing group**· **ADR, IMDG, IATA** not regulated· **14.5 Environmental hazards:**· **Marine pollutant:** Symbol (fish and tree)· **Special marking (ADR):** Symbol (fish and tree)· **14.6 Special precautions for user** Warning: Gases.· **Hazard identification number (Kemler code):** -· **EMS Number:** F-D,S-U· **Stowage Code** SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

Code: E0

Not permitted as Excepted Quantity

· **Transport category** 2· **Tunnel restriction code** D· **IMDG**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

GB

(Contd. on page 9)



**Trade name: PLASTI-KOTE® T&S 25606 PLASTIC PRIMER 6UC 400 ML**

(Contd. of page 8)

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **National regulations:**

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.09.2020

Version number 54

Revision: 17.12.2019

**Trade name: PLASTI-KOTE® T&S 25606 PLASTIC PRIMER 6UC 400 ML**

*Flam. Liq. 2: Flammable liquids – Category 2*  
*Flam. Liq. 3: Flammable liquids – Category 3*  
*Acute Tox. 4: Acute toxicity - dermal – Category 4*  
*Skin Irrit. 2: Skin corrosion/irritation – Category 2*  
*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*  
*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*  
*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*  
*Asp. Tox. 1: Aspiration hazard – Category 1*  
*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

· **\* Data compared to the previous version altered.**

(Contd. of page 9)

-GB-