



SAFETY DATA SHEET

HIGH TEMPERATURE ADHESIVE FIRE CEMENT - FIREBRAND BROWN

Page: 1

Compilation date: 12/04/2018

Revision date: 23/05/2018

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HIGH TEMPERATURE ADHESIVE FIRE CEMENT - FIREBRAND BROWN

CAS number: Mixture

EINECS number: Mixture

Product code: FF210 FF211

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants. PROC21: Low energy manipulation of substances bound in materials and/or articles ERC5: Industrial use resulting in inclusion into or onto a matrix

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd
Waterloo Road
London
NW2 7TX
UK
United Kingdom

Tel: +44 (0)20 8450 4666

Fax: +44 (0)20 8452 2008

Email: enquiries@minkon.co.uk

1.4. Emergency telephone number

Emergency tel: 44 (0)20 8450 4666 (Hours 09:00 - 17:00 Mon to Fri)
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Dam. 1: H318; Skin Irrit. 2: H315

Most important adverse effects: Causes skin irritation. Causes serious eye damage.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H318: Causes serious eye damage.

Hazard pictograms: GHS05: Corrosion



[cont...]

SAFETY DATA SHEET

HIGH TEMPERATURE ADHESIVE FIRE CEMENT - FIREBRAND BROWN

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call POISON CENTER/doctor.

P321: Specific treatment (see instructions on this label)

2.3. Other hazards

Other hazards: Alkaline Solution. Irritating to skin. Risk of serious damage to eyes.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

RAW MATERIAL - NA SILICATE SOLUTION, MR = 1.6 - 2.6 - REACH registered number(s): 01-211944872531

215-687-4	1344-09-8	-	Skin Irrit. 2: H315; Eye Dam. 1: H318	10-30%
-----------	-----------	---	---------------------------------------	--------

Contains: Alkaline Silicate Glass Solution.

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Remove contact lenses In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: The eyes may water profusely. There may be irritation and pain. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]

SAFETY DATA SHEET

HIGH TEMPERATURE ADHESIVE FIRE CEMENT - FIREBRAND BROWN

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

[cont...]

SAFETY DATA SHEET

HIGH TEMPERATURE ADHESIVE FIRE CEMENT - FIREBRAND BROWN

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

Hazardous ingredients:

RAW MATERIAL - NA SILICATE SOLUTION, MR = 1.6 - 2.6

Type	Exposure	Value	Population	Effect
DNEL	Oral	0.80 mg/kg bw/d	Consumers	Systemic
DNEL	Dermal	1.59 mg/kg bw/d	Workers	Systemic
DNEL	Dermal	0.80 mg/kg bw/d	Consumers	Systemic
PNEC	Fresh water	7.5 mg/l	-	-
PNEC	Marine water	1 mg/l	-	-
PNEC	Microorganisms in sewage treatment	348 mg/l	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Gloves (alkali-resistant).

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Brown or Black

Odour: Odourless

Evaporation rate: Slow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Binder soluble in water/filler insoluble

Viscosity: Viscous

Relative density: 2.0 - 3.0

pH: >11.5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

[cont...]

SAFETY DATA SHEET

HIGH TEMPERATURE ADHESIVE FIRE CEMENT - FIREBRAND BROWN

Page: 5

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: Not applicable.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RAT	LD50	1600-3200	mg/kg

Hazardous ingredients:

RAW MATERIAL - NA SILICATE SOLUTION, MR = 1.6 - 2.6

DERMAL	RAT	LD50	>5000	mg/kg
ORAL	RAT	LD50	3400	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: The eyes may water profusely. There may be irritation and pain. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]

SAFETY DATA SHEET

HIGH TEMPERATURE ADHESIVE FIRE CEMENT - FIREBRAND BROWN

Page: 6

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

RAW MATERIAL - NA SILICATE SOLUTION, MR = 1.6 - 2.6

Daphnia magna	48H EC50	1700	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	1108	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Contaminated containers must be completely emptied. Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

SAFETY DATA SHEET

HIGH TEMPERATURE ADHESIVE FIRE CEMENT - FIREBRAND BROWN

Page: 7

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H318: Causes serious eye damage.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.