

WG7550

A LOW- MAINTENANCE A3 COLOUR MFP FOR HIGH-SPEED PRODUCTION AND COST- EFFECTIVE SMB USE



Low-maintenance inkjet printer with A3 multifunctionality. A small footprint and wireless connectivity make this printer the perfect fit for small offices. High-speed productivity is supported by easy user maintenance, simplified by fewer replaceable parts, high-yield consumables and easy set-up.



- Enjoy excellent versatility thanks to A3 colour copy, print and scan functions
- Meet busy workloads with exceptionally high print speeds of up to 80ppm (300 dpi draft)
- Boost productivity and deliver scanned documents quickly with the ADF function
- Cut wasteful down time thanks to a maximum paper supply of 2,250 sheets (including optional cassette) and high-yield XL black and colour ink cartridges
- Integrate into your workflow with wired and wireless LAN connections. Connect to the Wi-Fi or print direct from smartphones or tablets with Mopria (Android), Apple AirPrint or the Canon PRINT Business mobile app
- Transfer scans to and print direct from a USB
- Save crucial office space with a smaller footprint and multifunctionality
- Reduce reliance on service teams - fewer replacement parts and smooth and easy recovery from paper jams allow easy user maintenance
- Operate with ease using the intuitive 5-inch colour touchscreen with on-screen keyboard
- Reduce power consumption - the printer uses just TEC 1.4kwh in sleep mode
- Enjoy faster printing with simpler maintenance with a fixed FINE Line Head, which spans the entire page width
- Produce professional documents with a sharp black pigment ink
- Work towards sustainable goals - the WG7550 is partly built with recycled plastic

PRODUCT RANGE



WG7550F



WG7550



WG7540

TECHNICAL SPECIFICATIONS

WG7550

PRINTER	
MAXIMUM PRINTING RESOLUTION	1200 x 1200dpi
PRINT HEAD/ INK	
Type	Line Head w/FINE Technology
Ink Tank	Black/Cyan/Magenta/Yellow
Ink Tank Series (EUR)	PGI-7500
Estimated Page Yield	XL = 20,000 pages BK XL - 16,500 pages C/M/Y
PRINT SPEED	
Document : Col, B/W ¹ Simplex, General Mode (600dpi), Cassette 1	Up to 50ppm
Document : Col, B/W ² Simplex, Office Document Mode (300dpi), Cassette 1	Up to 80ppm
Document : Col, B/W ¹ Duplex, General Mode (600dpi), Cassette 1	Up to 25 ppm
Document : Col, B/W ³ FPOT Ready/simplex, Cassette 1	Approx. 6.5 sec
Document : Col, B/W ³ FPOT Sleep/simplex, Cassette 1	Approx. 12.5 sec
MAXIMUM MEDIA SIZE (WXL)	
Default setting of Long Paper is OFF ¹ This is supported by firmware 1.0 or 1.1	Cassette : 297 x 431.8 mm (11.7"x17") Multi-Purpose Tray: 330.2 mm x 482.6 mm (13"x19") ⁴
SUPPORTED MEDIA SIZE ¹ Depending on regions, custom size specification may be different. Please refer to "Maximum Media Size".	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11x17, 12x18, SRA3, 13x19, K8, K16, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal), 4x6", 5x7", 8x10", 10x12", 13x19", COM10, Monarch, ISO-C5, DL, Custom size (Up to 330.2mm x 711.2mm or 330.2 mm x 482.6 mm)
PRINTING MARGIN	
Bordered Printing	Top, Bottom, Left, Right: 4mm each ¹⁵
Bordered Auto Duplex Printing	
SUPPORTED MEDIA TYPE AND SIZE PER CASSETTE -CASSETTE 1:	
Thin Paper (52-63g/m ²) Plain Paper (64-105g/m ²) Thick Paper (106-220g/m ²) Colored Paper (64-82g/m ²) Recycled Paper (64-105g/m ²) Bond Paper (83-99g/m ²)	A5, A4, B5, Statement, Executive, Letter, K16, G-Letter
Envelope (75-105g/m ²) Canon Matte Photo Paper Label (118-185g/m ²)	COM10, Monarch, ISO-C5, DL Not Available Not Available
SUPPORTED MEDIA TYPE AND SIZE PER CASSETTE -CASSETTE 2, 3:	
Thin Paper (52-63g/m ²) Plain Paper (64-105g/m ²) Thick Paper (106-220g/m ²) Colored Paper (64-82g/m ²) Recycled Paper (64-105g/m ²) Bond Paper (83-99g/m ²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11x17, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal)
Envelope (75-105g/m ²) Canon Matte Photo Paper Label (118-185g/m ²)	Not Available Not Available Not Available
SUPPORTED MEDIA TYPE AND SIZE PER CASSETTE -CASSETTE 4:	
¹ Cassette 2 & 3 support thick paper (106-220g/m ²) but cassette 4 supports 106-163g/m ² only	
Thin Paper (52-63g/m ²) Plain Paper (64-105g/m ²) Thick Paper (106-163g/m ²) Colored Paper (64-82g/m ²) Recycled Paper (64-105g/m ²) Bond Paper (83-99g/m ²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11x17, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal)

Envelope (75-105g/m ²)	Not Available
Canon Matte Photo Paper Label (118-185g/m ²)	Not Available Not Available
SUPPORTED MEDIA TYPE AND SIZE -MULTI-PURPOSE TRAY:	
Thin Paper (60-63g/m ²) Plain Paper (64-105g/m ²) Thick Paper (106-256g/m ²) Colored Paper (64-82g/m ²) Recycled Paper (64-105g/m ²) Bond Paper (83-99g/m ²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11x17, 12x18, SRA3, 13x19K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal), 4x6
Envelope (75-105g/m ²) Canon Matte Photo Paper Label (118-185g/m ²)	COM10, Monarch, ISO-C5, DL 4x6", 5x7", 8x10", 10x12", A4/LTR, A3, 13x19" A4, B4, Letter
PAPER CASSETTE CAPACITY (80G/M²)	
Cassette 1, 2, 3, 4 Multi-Purpose Tray	550 sheets 50 sheets
MAXIMUM OUTPUT TRAY CAPACITY (80G/M²)	A3: 100 sheets, A4/LTR:250 sheets
SUPPORTED MEDIA TYPE FOR DOUBLE SIDE PRINTING	
Type	Thin Paper, Thick Paper, Plain Paper, Colored Paper, Recycled Paper, Bond Paper
Size/Weight	A5 - 12x18", 52-220g/m ²
PRINT HEAD ALIGNMENT	Automatic Adjustment
SCAN ¹⁶	
SCANNER TYPE	Flatbed & ADF
SCANNER SENSOR	CISx2 sensors
DUPLEX SCANNING	Available (Single Pass)
OPTICAL RESOLUTION ¹⁷	600 x 600 dpi
SELECTABLE RESOLUTION ¹⁸	9600 x 9600 dpi
SCANNING BIT DEPTH (INPUT/OUTPUT)	
Grayscale	10bit/8bit
Color	30bit/24bit (RGB10bit/8bit each)
SCANNING SPEED ¹⁹	
Document(ADF) : Simplex Col	Approx. 40 ipm
Document(ADF) : Simplex B/W	Approx. 40 ipm
Document(ADF) : Duplex Col	Approx. 65 ipm
Document(ADF) : Duplex B/W	Approx. 65 ipm
MAXIMUM PAPER CAPACITY (80G/M²)	100 sheets
MAXIMUM DOCUMENT SIZE	
Flatbed	A3/ 11"x17"
ADF	A3/ 11"x17"
COPY	
MAXIMUM DOCUMENT SIZE	A3/ 11"x17"
SUPPORTED MEDIA SIZE	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11x17, 12x18, SRA3, 13x19, K8, K16, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal), 4x6", 5x7", 8x10", 10x12", 13x19", COM10, Monarch, ISO-C5, DL, Custom size (Up to 330.2mm x 711.2mm or 330.2 mm x 482.6 mm)
COPY EXPOSURE	9 Levels
COPY SPEED ²⁰	
Document (A4/LTR) Canon Original Method/ Simplex	50 ppm (Col, B/W)
FIRST-COPY-OUT TIME ²¹	
Document : Color sFCOT/Simplex	Approx. 5.8 sec
MAGNIFICATION	25-400% (1% Increments)
MULTIPLE COPY	Up to 999 copies

TECHNICAL SPECIFICATIONS

WG7550

SEND COMMUNICATION PROTOCOL	FTP (TCP/IP), SMB (TCP/IP), SMTP
MAXIMUM DOCUMENT SIZE	(Same as Copy function)
ADDRESS BOOK	300 addresses
SEND RESOLUTION	204dpi x 196 dpi, 300dpi x 300dpi
FILE FORMAT	
Single Page	TIFF (MMR), PDF, JPEG
Multi-Pages	TIFF (MMR), PDF
NETWORK	
WIRED LAN	
Network Type	1000 Base-T/ 100Base-TX/ 10Base-T
Data Rate	1Gbps(1000Mbps)/100Mbps/10Mbps
WIRELESS LAN	
Network Type	IEEE 802.11 b/g/n
Frequency Band	2.4 GHz
Range	Indoor 50m ¹⁴
Security	Infrastructure Mode: 128 (104)/ 64 (40) bit WEP, WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES) Access Point Mode; WPA2-PSK (AES-CCMP)
DIRECT CONNECTION (WIRELESS LAN)	Available
OPERATING SYSTEM	
Supported Operating Systems	Windows: Windows 7 - Starter / Home Basic / Home Premium / Professional / Enterprise / Ultimate Windows 8.1 - 8.1 / Pro / Enterprise Windows 10 - Home / Pro / Enterprise Windows Server 2008 - Standard (x86/x64) / Enterprise Edition (x86/x64) / Datacenter (x86/x64) Windows Server 2008 R2 Windows Server 2012 Windows Server 2012 R2 Windows Server 2016 Mac: V10.16.0: OS10.8 to 10.13 (incompatible with 10.14) V10.17.0: OS10.8 to 10.14 (incompatible with 10.15)
PRINTING SOLUTIONS	
CANON PRINT BUSINESSB102:G116	Available
CANON PRINT SERVICE MOPRIA	Available
APPLE AIR PRINT	Available ¹⁴
GOOGLE CLOUD PRINT	Available ¹⁴
NFC	NOT Available
MEDIA DIRECT PRINT (USB MEMORY)	
Compatible Format	USB 2.0 compatible
File Format	JPEG/TIFF/PDF
OTHERS	
OPERATION PANEL	
Display	LCD (5.0 inch/TFT color)
Language	35 Languages Selectable: Japanese/English/ German/ French/Italian/Spanish/Dutch/Portuguese/Norwegian/ Swedish/Danish/Finnish/Russian/Czech/Hungarian/ Polish/Slovene/Turkish/Greek/Simplified Chinese/ Traditional Chinese/Korean/Slovak/Estonian/Latvian/ Lithuanian/Romanian/Bulgarian/Croatian/Catalan/ Arabic/Malay/Basque/Thai/Vietnamese
INTERFACE	
USB Port for USB Memory	USB 2.0 Hi-Speed
USB Port for PC	USB 2.0 Hi-Speed
For Phone	Available
For Phone Line	Available
FINISHING OPTIONS	
-	
OPERATING ENVIRONMENT¹⁵	Temperature: 5 to 35C (41 to 96F) Humidity: 20 to 90% RH (w/o condensation)

RECOMMENDED OPERATING ENVIRONMENT¹⁵	Temperature: 15 to 30C (59 to 86F) Humidity: 20 to 85% RH (w/o condensation)
POWER	AC 100-240V 50/60Hz
POWER CONSUMPTION	
Copy/Print ¹⁶	Approx. 110W
Ready ¹⁶	Approx. 55W
Sleep ¹⁶	Approx. 1.9W
Off ¹⁶	Approx. 0.1W
Maximum Power Consumption	Approx. 300W
TEC (TYPICAL ELECTRICITY CONSUMPTION)¹⁷	Approx. 1.25kWh/week
ENVIRONMENTAL REGULATION	Energy Star*, Blue Angel*, Eco Mark*, EPEAT* *To be officially announced
DUTY CYCLE	100,000 pages
RECOMMENDED MONTHLY PRINTING VOLUME	1,000 to 5,000 pages
DIMENSION (WXDXH)	
Standard Configuration (WxDxH)	560mm(W) x 590mm(D) x 880mm(H) 22.1"(W) x 23.3"(D) x 34.7"(H)
With Optional Pedestal (WxDxH)	588mm(W) x 590mm(D) x 1,133mm(H) 23.2"(W) x 23.3"(D) x 44.7"(H)
Maximum Space (WxDxH)	925mm(W)x1,208mm(D) x 1,487mm(H) 36.5"(W) x 47.6"(D) x 58.6"(H) (*ADF is opened to 60°)
WEIGHT (INC. PRINT HEAD)	Approx. 81.5kg (Approx. 179.1lb)
(OPTIONAL) CASSETTE FEEDING UNIT CF10 (CASSETTE 3, 4)	
MEDIA SIZE	Refer to "Supported Media Type and Size per Cassette 3, 4:" above.
MEDIA WEIGHT	
MEDIA CAPACITY	
Power	Supplied from Main Unit
DIMENSION/WEIGHT	560mm x 590mm x 253 mm (WxDxH) 22.1"(W) x 23.3"(D) x 10.0"(H), Approx. 19kg, Approx. 41.2lb

FOOTNOTES

- Print Speed is based on ISO/IEC 24734. Measured in default mode (General Mode: 600dpi) and calculated by Canon original methodology.
Print speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc.
- Print Speed is based on ISO/IEC 24734. Measured in fast mode (Office Document Mode: 300dpi) and calculated by Canon original methodology.
Print speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc.
- Print Speed (FPOT) is based on ISO/IEC17629. Print speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc.
- With Custom setting, cassette 1 supports 90.0 x 190.0 mm to 216.0 x 297.0 mm, cassette 2, 3 and 4 supports 139.7 x 210.0 mm to 297.0 x 431.8 mm
- Depending on the driver software, this margin varies.
- TWAIN driver (ScanGear) is based on TWAIN Specifications V 1.6.
- Optical Resolution is based on ISO/IEC 14473. This is the maximum sampling rate when scanning the original.
- When scanning in high resolution, scanning area size may be limited.
- Average copy time from ADF. Set the original on ADF and measure time from pushing the scanning button to output the copied paper.
- Copy Speed is based on Canon original Method. With Canon original chart, execute the continuous copy and calculate copy pages per minute.
- First-Copy-Out Time is based on ISO/IEC 29183.
- Data transfer speed is measured in default mode with Canon original FAX testing chart. Actual speed varies depending on content of document, receiving settings at the destination, transfer line status and etc.
- Fax memory is measured with Canon original FAX testing chart. This number varies depending on the available memory size, content of document and etc.
- Some early stage units may require firmware update to make Air Print available.
- Print quality might be lower depending on the operating environment.
- Reference value measured by Canon original method based on operation modes in International ENERGY STAR Program. Depending on your environment, this may vary.
- Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program.

Specifications may be changed without notice.



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2019