

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : PURELL® SURFACE SANITISING WIPES (FDSUL485)

Product code : TSB66.

1.2. Relevant identified uses of the substance or mixture and uses advised against Antibacterial surfaces wipes

1.3. Details of the supplier of the safety data sheet

Registered company name : GOJO Luxembourg SARL. Address : 1 rue jean piret.L-2350 .Luxembourg.LUXEMBOURG. Telephone : +33 (0)1 60 95 49 00. Fax : +33 (0)1 60 95 49 49. frregulatoryteam@gojo.fr

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net. http://echa.europa.eu/fr/support/helpdesks/national-helpdesks/list-of-national-helpdesks

Other emergency numbers

Ireland, Éire : Ireland National Poisons Information Centre: +353 1 8092166 Ísland : Iceland Poison Information Centre: +354 525 111, +354 543 2222 Malta : Medicines & Poisons Info Office2545 6508 United Kingdom : NHS 111

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Biocidal mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02	GHS07	
Signal Word :		
DANGER		
Hazard statemen	ts :	
H225		Highly flammable liquid and vapour.
H319		Causes serious eye irritation.
Precautionary sta	atements - Prevention	:
P210		Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautionary sta	atements - Response :	
P305 + P351 + F	2338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313		If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Identification	(EC) 1272/2008	Note	%
CAS: 64-17-5	GHS07, GHS02	[1]	50 <= x % < 100
EC: 200-578-6	Dgr		
REACH: 01-2119457610-43	Flam. Liq. 2, H225		
	Eye Irrit. 2, H319		
ETHANOL			
INDEX: 603-117-00-0	GHS02, GHS07	[1]	2.5 <= x % < 10
CAS: 67-63-0	Dgr		
EC: 200-661-7	Flam. Liq. 2, H225		
REACH: 01-2119457558-25	Eye Irrit. 2, H319		
	STOT SE 3, H336		
PROPAN-2-OL			

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

- In the event of a fire, use :
- carbon dioxide (CO2)
- powder
- foam
- dry sand

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Remove and wash contaminated clothing before re-using.

Fire prevention :

Handle in well-ventilated areas.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically non-conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAR	TXXA	OTEL	0.11		0.1	1
CAS	TWA :	STEL:	Ceiling :	Definition :	Criteria :	4
64-17-5	200	1000 ppm		A3		-
67-63-0	200 ppm	400 ppm		A4; BEI		
- Germany - AGW (-	
CAS	VME :	VME :	Excess	Notes		
64-17-5		200 ppm 380 mg/m ³		$4(\hat{I}^{TM}\hat{I}^{TM})$		
67-63-0		200 ppm 500 mg/m ³		2(II)		
- Belgium (Arrêté d	· · · · · · · · · · · · · · · · · · ·	014):		1		7
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5	1000 ppm 1907 mg/m ³					
67-63-0	200 ppm 500 mg/m ³	400 ppm 1000 mg/m ³				
- Denmark (2008) :	,			1	_	
Stof	TWA	VSTEL	Loftvaerdi	Anm		
64-17-5	1000 ppm 1900 mg/m ³					
67-63-0	200 ppm				-	
- France (INRS - EI	490 mg/m ³	⊥ 87) ·				
CAS	VME-ppm :	VME-mg/m3	VLE-ppm :	VLE-mg/m3 :	Notes ·	TMP No :
64-17-5	1000	1900	5000	9500	-	84
67-63-0	-	-	400	980	-	84
	1 201() -		100	700		
- Finland (HTP-värd CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	1
64-17-5	1 WA : 1000 ppm	1300 ppm	Ceiling :	Definition :	Criteria :	-
04-17-3	1900 ppin 1900 mg/m ³	2500 mg/m^3				
- Spain (Instituto Na			en el Trabajo ()	 NSHT) 2017)		
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	1
64-17-5	I WA :	1.000 ppm		s		-
67-63-0	200 ppm	1910 mg/m ³ 400 ppm		VLB®. s		-
	500 mg/m ³	1000 mg/m ³		VLD®. 3		
- Greece (90/1999)		ampi	G 11			7
CAS	TWA:	STEL:	Ceiling :	Definition :	Criteria :	_
64-17-5		1000 ppm 1900 mg/m3				
67-63-0		400 ppm 980 mg/m3	500 ppm 1225 mgm/3			
- Ireland (Code of p						٦
CAS	TWA:	STEL :	Ceiling :	Definition :	Criteria :	_
64-17-5		1000 ppm				_
67-63-0 - Latvia (Regulation	200 ppm	400 ppm				
CAS	TWA:	STEL :	Ceiling :	Definition :	Critoria :	Г
64-17-5	1 wA : 1000 mg/m3	SIEL.	Cennig .	Demition :	Criteria :	-
67-63-0	350 mg/m3	600 mg/m3				-
- Lithuania (HN 23	:2001) :					_
CAS	TWA:	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5	500 ppm 1000 mg/m ³	1000 ppm 1900 mg/m ³				
67-63-0	150 ppm	250 ppm				1
NI (37.11.1.1	350 mg/m ³	600 mg/m ³		<u> </u>	2010	
- Norway (Veilednin						7
CAS	TWA:	STEL :	Ceiling :	Definition :	Criteria :	-
64-17-5	500 ppm 950 mg/m ³					
67-63-0	100 ppm 245 mg/m ³					
L		1	1	1	1	_

- Netherlands / MAG	C-waarde (10 de	cember 2014) :			
CAS	TWA:	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	260 mg/m ³	1900 mg/m ³		Huid	
67-63-0	250 ppm	-	-	-	-
- Poland (Dz. U. z 2	018 r. poz. 917,	1000 i 1076) :			
CAS	TWA:	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1900 mg/m ³				
67-63-0	900 mg/m ³	1200 mg/m ³			
- Czech Republic (R	Legulation No. 3	61/2007):			
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 mg/m ³	3000 mg/m ³		Ι	
67-63-0	500 mg/m ³	1000 mg/m ³		Ι	
- Slovakia (Règleme	ent 300/2007, 47	1/2011 23/11/2	2011):		
CAS	TWA:	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	500 ppm	1 000 ppm			
	960 mg/m ³	1 920 mg/m ³			
67-63-0	200 ppm	400 ppm			
	500 mg/m ³	1 000 mg/m ³			
- Slovenia (Uradni I					
CAS	TWA:	STEL :	Ceiling :	Definition :	Criteria :
64-17-5		1000 ppm		Y	
		1900 mg/m ³			
67-63-0		200 ppm		Y. BAT	
		500 mg/m ³			
- Switzerland (SUV	/				7
CAS	VME	VLE	Valeur plafond		_
64-17-5	500 ppm	1000 ppm		SSC	
(7 (2)	960 mg/m ³	1920 mg/m ³		D. 66.6	_
67-63-0	200 ppm	400 ppm		B SSC	
	500 mg/m ³	1000 mg/m ³			
- Sweden (AFS 201			1		1
CAS	TWA:	STEL:	Ceiling :	Definition :	Criteria :
64-17-5	500 ppm	1000 ppm		V	
(7.(2.0	1000 mg/m ³	1900 mg/m ³		V	
67-63-0	150 ppm 350 mg/m ³	250 ppm 600 mg/m ³		v	
- Romania (Hotarâre		CTEL .	Celline	D.C. H.	Cuitouia
CAS 64-17-5	TWA :	STEL:	Ceiling :	Definition :	Criteria :
04-17-5	1000 ppm 1900 mg/m3	5000 ppm 9500 mg/m3			
67-63-0	81 ppm	203 ppm			
07-03-0	200 mg/m3	500 mg/m3			
- UK / WEL (Workt	0	e	05 2011) ·	l	1
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1 WA : 1000 ppm	- ppm	Cennig :	Deminion :	
04-17-5	1920 mg/m ³	- mg/m ³			
67-63-0	400 ppm	500 ppm			
	999 mg/m ³	1250 mg/m ³			
- Bulgare		<u></u>	1		1
Identification	TWA	STEL	Ceiling	Notations	7
64-17-5	1000 mg/m3	SILL	Coning	1 1010115	-
67-63-0	980 mg/m3	1225 mg/m3			-
- Estonie			1	L	
Identification	Piirnorm	Luhiajalise	Piirnormi lagi	Markused	7
lacititication		kokkupuute		markuseu	
		piirnorm			
64-17-5	500 ppm	1000 ppm			1
	1000 mg/m3	1900 mg/m3			
(= (2)	150 ppm	250 ppm			1
67-63-0	1 JU ppm	250 ppm			
67-63-0	350 mg/m3	600 mg/m3			

- Hongrie				
Megnevezes	AK-ertek	CK- ertek	MK- ertek	Megjegyzesek
64-17-5	1900 mg/m3	7600 mg/m3		
67-63-0	500 mg/m3	2000 mg/m3		b. i
- Croatia				
Identification	TWA	STEL	Ceiling	Notations
64-17-5	1000 ppm			F
	1900 mg/m ³			
67-63-0	400 ppm	500 ppm		F. Xi
	999 mg/m ³	1250 mg/m ³		

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Body protection

Work clothing worn by personnel shall be laundered regularly.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :	
Physical state :	Fluid liquid.
Color:	colourless
Odour:	alcoholic
Important health, safety and environmental information	
pH :	8.25 +/- 0.75.
	Slightly basic.
Boiling point/boiling range :	>35°C
Flash Point :	22.10 °C.
Vapour pressure (50°C) :	Not relevant.
Density :	0.854 - 0.874
Water solubility :	Dilutable.
These data refer to the impregnation solution.	
9.2. Other information	

2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat

- flames and hot surfaces
- frost

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2020).

14.1. UN number

3175

14.2. UN proper shipping name

UN3175=SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C

(ethanol, propan-2-ol)

E2

A46

PURELL® SURFACE SANITISING WIPES (FDSUL485) - TSB66

14.3. Transport hazard class(es)





14.4. Packing group

Π

14.5. Environmental hazards

14.6. Special precautions for user

4.1

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	4.1	F1	II	4.1	40	1 kg	216 274 601	E2	2	Е
										_
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage	Segregation	
								Handling		
	4.1	-	II	1 kg	F-A, S-I	216 274	E2	Category B	-	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	4.1	-	II	445	15 kg	448	50 kg	A46	E2	

5 kg

Y441 For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

II

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)

- Container information: No data available.

- Particular provisions :

No data available.

- Labelling for biocidal products (Regulation 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC)

•				
	Name	CAS	%	Product-type
	ETHANOL	64-17-5	660.10 g/kg	02
				04

Product-type 2 : Disinfectants and algaecides not intended for direct application to humans or animals.

Product-type 4 : Food and feed area.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
------	-------------------------------------

- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.