PM BP 045 BLACK - BP 159

Date: 05/06/2019 Page 1/10 Revision: N°2 (19/04/2019)

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: PM BP 045 BLACK

Product code: BP 159.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Ink for PAPER MATE & REYNOLDS: 045

1.3. Details of the supplier of the safety data sheet

Registered company name: Newell Rubbermaid UK Limited.

Address: Halifax Ave - Fradley Park .WS 13 8SS.Lichfield Staffordshire.United Kingdom.

Telephone: +44 (0) 1543447001. Fax:. Aftersales.SERVICE@newellco.com

www.newellbrands.com

1.4. Emergency telephone number: 111.

Association/Organisation: National Poisons Information Service.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:







GHS05

GHS07

GHS09

 $Signal\ Word:$

DANGER

Product identifiers:

603-098-00-9 2-PHENOXYETHANOL EC 265-449-9 C.I. SOLVENT BLACK 46 603-057-00-5 BENZYL ALCOHOL

EC 235-741-0 ACIDE PHOSPHORIQUE ESTER D'ETHYL-2-HEXYLE

Hazard statements:

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

Version : N°13 (05/06/2019) Newell Rubbermaid UK Limited

PM BP 045 BLACK - BP 159

Date: 05/06/2019 Page 2/10

Revision: N°2 (19/04/2019)

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements - General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash ... thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response:

P302 + P352 IF ON SKIN: Wash with plenty of water/...

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/...

P321 Specific treatment (see ... on this label).

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

Precautionary statements - Storage:

P405 Store locked up.

Precautionary statements - Disposal:

P501 Dispose of contents/container to ...

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) \geq 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

Identification	(EC) 1272/2008	Note	%
INDEX: 603-098-00-9	GHS07	[1]	25 <= x % < 50
CAS: 122-99-6	Wng		
EC: 204-589-7	Acute Tox. 4, H302		
REACH: 01-2119488943-21	Eye Irrit. 2, H319		
2-PHENOXYETHANOL			
CAS: 65113-55-5	GHS05, GHS09, GHS07		25 <= x % < 50
EC: 265-449-9	Dgr		
	Skin Sens. 1, H317		
C.I. SOLVENT BLACK 46	Eye Dam. 1, H318		
	STOT SE 3, H335		
	Aquatic Acute 1, H400		
	M Acute = 1		
	Aquatic Chronic 1, H410		
	M Chronic = 1		

Version: N°13 (05/06/2019) Newell Rubbermaid UK Limited

PM BP 045 BLACK - BP 159

Date: 05/06/2019 Page 3/10

Revision: N°2 (19/04/2019)

INDEX: 603-057-00-5	GHS07	[1]	10 <= x % < 25
CAS: 100-51-6	Wng		
EC: 202-859-9	Acute Tox. 4, H332		
REACH: 01-2119492630-38	Acute Tox. 4, H302		
BENZYL ALCOHOL			
CAS: 12645-31-7	GHS05		0 <= x % < 2.5
EC: 235-741-0	Dgr		
REACH: 01-2119896587-13	Skin Corr. 1C, H314		
ACIDE PHOSPHORIQUE ESTER			
D'ETHYL-2-HEXYLE			

(Full text of H-phrases: see section 16)

Information on ingredients:

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation:

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)

PM BP 045 BLACK - BP 159

Date: 05/06/2019 Page 4/10

Revision: N°2 (19/04/2019)

- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention:

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid eye contact with this mixture at all times.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Version : N°13 (05/06/2019) Newell Rubbermaid UK Limited

PM BP 045 BLACK - BP 159

Date: 05/06/2019 Page 5/10

Revision: N°2 (19/04/2019)

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME:	VME:	Excess	Notes
122-99-6		20 ppm		2(I)
		110 mg/m ³		Í
100-51-6		5 ppm		2(I)
		22 mg/m³		

- Finland (HTP-värden 2016):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
122-99-6	20 ppm	50 ppm			
	II0 mg/m ³	290 mg/m ³			
100-51-6	10 ppm				
	45 mg/m ³				

- Latvia (Regulation No. 325/2007):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
100-51-6	5 mg/m3				

- Lithuania (HN 23:2001):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
100-51-6	5 mg/m³			O	

- Poland (2014):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
122-99-6	230 mg/m ³				
100-51-6	240 mg/m ³				

- Czech Republic (Regulation No. 361/2007):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
100-51-6	40 mg/m ³	80 mg/m ³			

- Slovenia (Uradni List, 04/06/2015) :

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
122-99-6		20 ppm		K, Y	
		110 mg/m ³			

-	Bul	lgar
---	-----	------

Daigare				
Identification	TWA	STEL	Ceiling	Notations
100-51-6	5 mg/m3			

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

PM BP 045 BLACK - BP 159

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Date: 05/06/2019 Page 6/10

Revision: N°2 (19/04/2019)

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Recommended properties:

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

- A1 (Brown)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information:

Physical state: Fluid liquid.

Important health, safety and environmental information

pH: 6.50 .

 $\begin{tabular}{ll} Neutral. \\ Boiling point/boiling range: & Not relevant. \\ Flash Point: & 101.00 \, ^{\circ}C. \\ \end{tabular}$

Explosive properties, lower explosivity limit (%): 1.3 Explosive properties, upper explosivity limit (%): 13.0

Vapour pressure (50°C): Not relevant.

Density: 1.1
Water solubility: Insoluble.
Viscosity: 8500 mPas
Melting point/melting range: Not relevant.
Self-ignition temperature: Not relevant.
Decomposition point/decomposition range: Not relevant.

9.2. Other information

No data available.

PM BP 045 BLACK - BP 159

Date: 05/06/2019 Page 7/10

Revision: N°2 (19/04/2019)

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Harmful if swallowed.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

May cause an allergic reaction by skin contact.

11.1.1. Substances

Acute toxicity:

ACIDE PHOSPHORIQUE ESTER D'ETHYL-2-HEXYLE (CAS: 12645-31-7)

Oral route: LD50 = 3000 mg/kg

Species: Rat (recommended by the CLP)

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12: ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

ACIDE PHOSPHORIQUE ESTER D'ETHYL-2-HEXYLE (CAS: 12645-31-7)

Fish toxicity : LC50 > 250 mg/l

Species: Leuciscus idus Duration of exposure: 48 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

PM BP 045 BLACK - BP 159

12.2. Persistence and degradability

12.2.1. Substances

ACIDE PHOSPHORIQUE ESTER D'ETHYL-2-HEXYLE (CAS: 12645-31-7)

Biodegradability: no degradability data is available, the substance is considered as not degrading quickly.

Date: 05/06/2019 Page 8/10 Revision: N°2 (19/04/2019)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws):

WGK 2: Hazardous for water.

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

3082

14.2. UN proper shipping name

UN3082=ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es)

- Classification:



9

14.4. Packing group

Ш

Version : N°13 (05/06/2019) Newell Rubbermaid UK Limited

PM BP 045 BLACK - BP 159

Date: 05/06/2019 Page 9/10

Revision: N°2 (19/04/2019)

14.5. Environmental hazards

- Environmentally hazardous material:



14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	9	M6	III	9	90	5 L	274 335 375 601	E1	3	-

Not subject to this regulation if $Q \le 51/5 \text{ kg}$ (ADR 3.3.1 - DS 375)

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	9	-	III	5 L	F-A,S-F	274 335 969	E1

Not subject to this regulation if $Q \le 51/5$ kg (IMDG 3.3.1 - 2.10.2.7)

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	9	-	III	964	450 L	964	450 L	A97	E1
								A158	
								A197	
	9	-	III	Y964	30 kg G	-	-	A97	E1
								A158	
								A197	

Not subject to this regulation if $Q \le 51/5 \text{ kg}$ (IATA 4.4.4 - DS A197)

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)

- Container information:

The mixture is contained in packaging that does not exceed 125 ml.

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 2: Hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Version : N°13 (05/06/2019) Newell Rubbermaid UK Limited

PM BP 045 BLACK - BP 159

Date: 05/06/2019 Page 10/10

Revision: N°2 (19/04/2019)

Wording of the phrases mentioned in section 3:

Harmful if swallowed. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects.

Abbreviations:

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS05 : Corrosion GHS07 : Exclamation mark GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable.

SVHC: Substances of very high concern.