

Get blazing fast printing speeds, high-volume scanning, and easy management with LaserJet Pro.

This printer is built for maximum productivity with fast speeds and reliable hardware, delivering effortless everyday use from wherever work happens so you can focus more on your business.





Highlights

- Instant Ink for Laser available
- HP Smart app and Smart Adv/Pro
- HP Wolf Pro security
- Automatic two-sided printing standard
- Fast print speed (40 ppm A4)
- High monthly duty cycle (80,000 pages)
- Dual-band WiFi®, Bluetooth® LE, WiFi® Direct
- 50 sheet ADF with single-pass, two-sided scanning



















Maximum productivity.

- Support your dynamic workteam with this high-speed smart printer, ideal for up to 10 users.
- Step up your workflow with HP Pro-class maximum print speed to meet high-demand environments.
- Scan both sides with a single pass. Dual-sided scanning allows your users to get more done in less time.
- Get productivity in the palm of your hand. Print, scan and get time-saving Shortcuts with HP Smart app. ²

Seamless management.

- Centralise print management for your enterprise. HP Web Jetadmin makes it easy with its suite
 of features. 4
- Set up your printers quickly wherever work happens. Cloud connectivity makes it easy for your IT team.
- Access your printers from a single dashboard. Smart Admin guides you through setup and gives IT visibility.³
- Avoid interruptions with Wi-Fi[®] that intelligently looks for the best connection to stay on-line.

HP Wolf Pro Security.

- Get printer security out of the box. Preconfigured settings mean it's ready when you are.
- Set up your printer security from the dashboard. Smart Admin makes IT configuration and monitoring easy. 3
- Add a layer of security. PIN/pull option authenticates your print jobs only when you're present.
- Set configuration policies and validate settings universally with HP Security Manager.⁶

Hassle-free supplies management with Instant Ink.

- Enroll to save on Original HP Toner with Instant Ink. Get toner, delivery and recycling. 7,8,9
- Never run out of toner with Instant Ink for laser.¹⁰
- With Instant Ink, get toner automatically delivered to workers or offices all on one consolidated bill. $^9\,$
- With Instant Ink, you get to select the right plans for each of your printers. Change or cancel at any time.¹¹

Product walkaround

- 1. Designed for workteams of up to 10 users
- 2. Pre-configured security settings
- 3. Walk-up USB
- 4. Automatic 2-sided printing
- 5. Hi-speed USB ports, built-in Gigabit Ethernet
- 6. Print speeds up to 40 ppm (A4), 350-sheet standard paper capacity



Accessories, Supplies and Support

Supplies	W1490A HP 149A Black Original LaserJet Toner Cartridge (Average cartridge yields 2,900 standard pages. Declared yield value in accordance with ISO/IEC 19752.)
	W1490X HP 149X High Yield Black Original LaserJet Toner Cartridge (Average cartridge yields 9,500 standard pages. Declared yield value in accordance with ISO/IEC 19752.)
Accessories	D9P29A HP LaserJet Pro 550-sheet Feeder Tray
Service and Support	U42TZE - HP 3 year Next Business Day Service for LaserJet Pro MFP 410x U42U8PE - HP 1 year Post Warranty Next Business Day Service for LaserJet Pro MFP 410x

Technical specifications

-	
Model	HP LaserJet Pro MFP 4102fdw Printer
Product number	22624F
Functions	Print, copy, scan, fax
Control panel	2.7° Color Touchscreen
Print	
Print technology	Laser Black (A4. normal): Up to 40 ppm: Black (A4. duplex): Up to 34 ipm
Print speed ¹	the state of the s
First page out ²	Black (A4, ready). As fast as 6.3 sec; Black (A4, sleep). As fast as 8.8 sec
Print resolution	Black (best): Fine Lines (1200 x 1200 dpi); Technology: HP FastRes 1200, HP ProRes1 200, Economode
Monthly duty cycle Printer smart software features ³	Up to 80,000 pages A4; Recommended monthly page volume: 750 to 4,000 Auto duplex and booklet printing, N-up printing, collation, watermarks, install printer driver only, Economode for toner savings, accepts a variety of paper sizes and types
Standard print languages	HD PCL 6, HD posterpitrum, re-up printing, roughous water mans, most printer univer only, economic or notice savings, accepts a variety or paper sizes and types. HD PCL 6, HD posterpit level 3 multilation, PDC, MR, Native Office, PWG Raster HD PCL 6, HD posterpitrum, re-up printing, rough and
Fonts and typefaces	RF PLL 6, RF PLG, PD DISSCRIPT EVER 3 emissions, PUT, URT, Native Unite, PWG Naster 8 PLL 6, RF PLG
Print area	or statation true from min Sottom: 4.3 mm, Sottom: 4.3 mm, Left: 4.3 mm, Right: 4.3 mm; Maximum print area: 207.4 x 347.1 mm
Duplex printing	Automatic (default) Automatic (default)
Copy	Automatic Delauto
Copy speed	Black (A4): Up to 38 cpm
	ID Copy, Number of copies, Resize (including 2-Up); Lighter/Darker; Enhancements; Original Size; Binding Margin; Collation; Tray Selection; Two-Sided; Quality (Draft/Normal/Best); Save Current Settings; Restore Factory
Copier specifications	Defaults, Maximum number of copies; Neduce/Enlarge: 25 to 4009
Scan	
Scan speed ⁴	Normal (A4): Up to 29 ppm/46 ipm (b&w), up to 20 ppm/34 ipm (color) :Duplex (A4): Up to 46 ipm (b&w), up to 34 ipm (color)
Scan file format	PDF, JPG, TIFF
Scanner specifications	Scanner type Flatbed, ADF; Scan technology: Contact Image Sensor (CIS); Scan input modes: Front-panel scan, copy, email, or file buttons; HP Scan software; and user application via TWAIN or WIA; Twain version: 2.3;
	Duplex ADF scanning: Ves; Scan size maximum (flatbed, ADF): 216 x 297 mm; Optical scan resolution: Up to 1200 x 1200 dpi
Scanner advanced features	Copy preview
Recommended monthly scan volume	750 to 4000
Scannable area	Maximum media size (flatbed): 216 x 297 mm: Minimum media size (ADF): 102 x 152 mm Maximum media size (ADF): 216 x 356 mm
Bit depth/ Grey scale levels	PRIARIMENT INTEGRAL SIZE (HALDEU), 216 x 297 mm, priminium media size (vior), 102 x 152 mm maximum media size (vior), 216 x 356 mm 24-bit / 256
Fax	24-01(7-230
Fax	Yes, 33.6 kbps
Fax specifications	185, 335, 80,UJS 186, 335, 80,UJS 187, 335, 80,UJS 188, 335, 80,UJS 189, 3
	Auto fax reduction; Auto redultion; Autor edidling; Delayed sending; Fax forwarding; TAM interface; Junk barrier; Districtive in in detection; Cover page; Block fax; Save and load; Fax activity reports; Dial prefix setting. Print fax
Fax smart software features	had for leading, beloyed sending, that for waiting, the waiting
Processor speed	1200 MHz
Connectivity	
Standard	1 Hi-Speed USB 2.0; 1 rear host USB; 1 Front USB port; Gigabit Ethernet LAN 10/100/1000BASE-T network; 802.3az(EEE); 802.11b/g/n / 2.4 / 5 GHZ Wi-Firadio + BLE
Mobile printing capability	HP Smart App; Apple AirPrint™; Mopria™ Certified; Wi-Fi® Direct Printing; Optional ROAM Queue Printing; HP ROAM For Business
Supported nativary protocols	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint ^{IM} , Mopria, IPP Print; Discovery; SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6
Supported network protocols	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download
Network capabilities	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint [™] , Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X
Network capabilities Hard disk	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Statelless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Gertificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X
Network capabilities Hard disk Memory	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X
Network capabilities Hard disk Memory Media handling	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yer (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yer (Stateless Link-Local and via Router, Statefull via DHCP, AutolP, AutolP, Manual), IPv6 Stateless Link-Local and via Router, Statefull via DHCP, AutolP, AutolP, Manual), IPv6 Stateless Link-Local and via Router, Statefull via DHCP, AutolP, AutolP, Manual), IPv6 Stateless Link-Local and via Router, Statefull via DHCP, AutolP, AutolP, Manual), IPv6 Stateless Link-Local and via Router, Statefull via DHCP, AutolP, AutolP, Manual), IPv6 Stateless Link-Local and via Router, Statefull via DHCP, AutolP, AutolP, Manual), IPv6 Stateless Link-Local and via Router, Statefull via DHCP, AutolP, AutolP, AutolP, Manual), IPv6 Stateless Link-Local and via Router, Statefull via DHCP, AutolP, AutolP
Network capabilities Hard disk Memory Media handling Number of paper trays	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB: Maximum: 512 MB Standard: 2; Maximum: 3
Network capabilities Hard disk Memory Media handling	TCP/IP; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint*, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Statelless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels;
Network capabilities Hard disk Memory Media handling Number of paper trays	TCP/IP; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metrio): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (184 x 260 mm); 16K (18
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, PutoIP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB ;Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, roughl); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 74.4 x 50 mm); 16K (191 x 273 mm); 16K
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Japanese Postcard; Double Japan Postcard Rotated; Envelope #10; Envelope Monarch; Envelope B1; Envelope B1; Envelope B1; Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm);
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight	TCP/IP; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download No Standard: 512 MB: Maximum: 512 MB Standard: 512 MB: Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Japanese Postcard; Double Japan Postcard Rotated; Envelope #10; Envelope #10; Envelope #10; Envelope B5; Envelope C5; Envelope D1; Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 273 mm); Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 273 mm); Custom Size; A5-R; 4 x 6 in; B6 (JIS) ADE: Letter; Legal; A4; custom sizes 102 x 152 to 216 x 356 mm Standard Input: 100-sheet tray 1, 250-sheet Automatic Document Feeder (ADF) Standard output: 150-sheet output bin Optional Input: Optional Input: Optional third 550-sheet tray ADF: Standard, 50 sheets Tray 1: 60 to 200 g/m²; tray 2, optional 550-sheet tray 3: 60 to 120 g/m²
Network capabilities Hard disk Memory Media handling Number of paper trays Media size Media handling Media weight Input capacity	TCP/IP; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: S12 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported fuertic): Tray 1: A4, A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (194 x 260 mm); 16K (197 x 273 mm); Bapensee Postcard; Double Japan Postcard Rotated; Envelope B1; Envelope B2; Envelope B1; Env
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media wight Input capacity Output capacity	TCP/IP; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3; 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3; 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 7.7 x 12.5 x 135.5 mm Size; 4 x 6 in; 5 x 8 in; S x 8 in
Network capabilities Hard disk Memory Media handling Number of paper trays Media size Media handling Media weight Input capacity	TCP/IP; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 7.7 x 12.5 x 12.5 x 355.6 mm; Tray 2. 8 Tray 3: A4; A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 2
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems	TCP/IP; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 7.67.2 x 127.5 v 23.5 s mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 7.7 x 12.5 x 355.6 mm; Tray 2. 8 tray 2. 48.5 in; 5 x 8 in; S x 8 in;
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements	TCP/IP; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Statelless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: \$12 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metrio): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported fuertio): Tray 1: 1.4 x, 45; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Businese Postcard; Double Japan Postcard Rotated; Envelope #B1, Envelope #B5, Envelope £5; Envelope £5; Envelope £6; Envel
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateleless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 2.8 Tray 2.8 tray 2.8 tray 3: 46.5 (195.2 x 270 mm); 16K (195.2 x 270 mm); 16K (195.2 x 270 mm); 16K (197.2 x 273 mm); Busease Postcard; Double Japan Postcard Rotated; Envelope B15, Envelope B15, Envelope B25, Envelope
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements	TCP/IP; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Annual), IPv6 (Statelless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: \$12 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metrio): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4, A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (194 x 260 mm); 16K (197 x 273 mm); Busensee Postcard; Double Japan Postcard Rotated; Envelope #B1, Envelope #B1, Envelope B5; Envelope B1, Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Loustom Size; A5-R; 4 x 6 in; B6 (JIS) ADF: Letter; Legal; A4; custom sizes 102 x 152 to 216 x 356 mm Standard input: 100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF) Standard output: 150-sheet output bin Optional input: Option
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible network operating systems Minimum system requirements Software included	TCP/IP; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Annual), IPv6 (Statelless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB: Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 35.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 35.5 mm Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 270 mm); 16K (195 x 273 mm); Boursee Postcard; Double Japan Postcard Rotated; Envelope Honarch; Drevelope B5; Envelope B1; Envelope B1; Envelope B1; Envelope B1; Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 273 mm); Dustom Size; A5-R; 4 x 6 in; B6 (JIS) ADF: Letter; Legal; A4; custom size; 102 x 152 to 216 x 356 mm Standard input: 100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF) Standard output: 150-sheet output bin Optional Input: Optional Input: Optional Tray 1: 50 to 200 g/m²; Tray 1; 23 personal Sto-sheet tray 3: A6; A5; A5; A5; A5; A5; A5; A5; A5; A5; A5
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible network operating systems Minimum system requirements Software included Printer management	TCP/IP; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Annual), IPv6 (Statelless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB: Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 35.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 35.5 mm Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 270 mm); 16K (195 x 273 mm); Boursee Postcard; Double Japan Postcard Rotated; Envelope Honarch; Drevelope B5; Envelope B1; Envelope B1; Envelope B1; Envelope B1; Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 273 mm); Dustom Size; A5-R; 4 x 6 in; B6 (JIS) ADF: Letter; Legal; A4; custom size; 102 x 152 to 216 x 356 mm Standard input: 100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF) Standard output: 150-sheet output bin Optional Input: Optional Input: Optional Tray 1: 50 to 200 g/m²; Tray 1; 23 personal Sto-sheet tray 3: A6; A5; A5; A5; A5; A5; A5; A5; A5; A5; A5
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Ves, via builti-in 10/100/10000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB ;Maximum: 512 MB Standard: 512 MB ;Maximum: 3 Paper (plain, EcoEFFICIENT, Ight, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray: 1: 62 x 127 to 215 9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray: 1: A4: A5: A6; B5 (JIS): Oficio (216 x 240 mm); 16K (195 x 270 mm); 1
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media handling Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W × D × H)	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9 port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print: Discovery: SLR Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCR, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP PW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB: Maximum: 512 MB Standard: 512 MB: Maximum: 512 MB: 512
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight	TCPIP_IPv4_IPv6; Pint: TCP-IP port 9100 Direct Mode, LP0 (raw queue support only), Apple AirPrint**, Mopria, IPP Print; Discovery; SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via bull-tin 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard; 512 MB; Maximum: 512 MB Standard; 512 MB; Maximum: 512 MB; M
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Media handling Media handling Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer dimensions (W x D x H) Printer weight Operating environment	TCPIR IP-4, IP-6; Print; TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple Arbrint* Morpia, IPP Print; Discovery SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (Boott P. Dr.C.P. Autority, Annual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via butti-in 10/100/1000/0006ase-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 512 MB Standard: 2; Maximum: 512 MB, Maximum: 512 MB Standard: 2; Maximum: 512 MB, Maximum: 512 MB Standard: 2; Maximum: 3 Custom (metric): Tray 1: 76.2 x 1.27 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: Ad; A5; A6; B5 (IJS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (194 x 260 mm); 16K (197 x 273 mm); Japanese Postcard; Double Japan Postcard Rotated, Envelope #10; Envelope Monard; Envelope B5; Envelope B1, Custom Size; 4x 6 in 5.5 x 81 in; Statement; Tray 2.8 Tray 3 in; Bot (153.340 mm); 16K (195 x 270 mm); 16K (197 x 273 mm);
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media handling Media weight Input capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions	TCD/IE_PNS_PINS_PINS_TCD-IP_part \$10.0 Direct Mode_LPD (aw queue support only), Apple AirPnire_Mopria, IPP Pinit; Discovery_SUB Bonjour, Web Services Discovery_IP Config. [Pvsl (Boott), DHCP, AutolP, Manual), [Pv6] Sistaleses Link-Local and via Boucher, Stateful via OHPONB, SSL Security and Certificate management: Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog_FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB_Maximum: 512 MB Standard: 2. Maximum: 512 MB, Maximum: 512 MB Paper (plain, EcoEFFCIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 1.27 to 21.59 x 35.5 f. mm; Tray 2, 3: 10.49 x 148.59 to 21.59 x 35.5 f. mm. Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (194 x 260 mm); 16K (195 x 270 mm); 16K (194 x 260 mm); 16K (195 x 270 mm); 16K (195 x 2
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Number of paper trays Media types Media handling Media weight Input capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Storage conditions Acoustics Power	TCMP_IPAG_PING_PING_PING_PING_PING_SEASON_PIPAG_RATE_PING_BOOKE_PING_PING_BOOKE_PING_PING_PING_PING_PING_PING_PING_PING
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Media handling Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions Acoustics	TCP/PE (PM4, EPv6, Print: TCP-IP port 9100 Direct Mode. LPD (raw queue support only), Apple APrint** Mopria, IPP Print Discovery, SLP. Borioux, Web Services Discovery; IP Config (Pv4 (Bool, DHCP, Autolit, Manual), (Pv6 (Stateless Linke Local and via Route), Stateful was Developed. SSLE Security and Certificate management. Management: SNMPV1, SNMPV2, SNMPV3, HTTP/HTTPS, Syslog, ETP FW Download Yes, via built-in 10/100/10008ase-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 2: Maximum: 31 Sandard: 2: Maximum: 31 Paper (plain, EcoFFFCIGEN), Light, beav, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes: labels: Custom (meth): Trip; 1: 762.2 x; 127 to 215.92, 435.6 mm; Trip; 2: 3; 104.9 x; 148.59 to 216.9 x; 355.6 mm; Supported (meth): Trip; 1: 762.2 x; 127 to 215.9 x; 355.6 mm; Trip; 2: 3; 104.9 x; 148.59 to 216.9 x; 355.6 mm; Supported (meth): Trip; 1: 762.2 x; 127 to 215.9 x; 355.6 mm; Trip; 2: 3; 149.5 x; 340 mm): 16K (194.2 x; 260 mm): 16K (194.
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Number of paper trays Media types Media handling Media weight Input capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Storage conditions Acoustics Power	TCP/IP (PM4, IPM6, Print: TCP-IP port 1910) Direct Mode. IPD (raw queue support only), Apple AirPnint**, Mopria, IPP Print Discovery, SLP, Bonjour, Web, Services Discovery, IP Config (PM4 (Bool), DHCP, Autoli, Manual), IPM6 (Stateless Links colar and via Route), Statellul via OHPPO), SCS. Security and Certificate management. Management: SNMPV1, SNMPV2, SNMPV3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/10008ase-TX Ethernet, Gigabit; Auto-crossover Ethernet. Authentication via 802.1X No. Standard: 2 Maximum: 31 Sandard: 2 Maximum: 31 Paper (plain, EcoFFFCIENT), light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough): envelopes: labels: Custom frontfilt Tray: 17: 62 × 127: 02.15.9 x; 35.6 mm; Tray: 2, 3: 104.9 x; 148.59 to 215.9 x; 35.5 mm; Supported (metric), Tray: 1: 64, 45.46; 159; 0ficio (216 x; 340 mm); 16K (195 x; 270 mm)
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Number of paper trays Media types Media handling Media weight Input capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Storage conditions Acoustics Power	TCP/IP IP-04, IP-Ks, Pinist, TCP-IP port 91 (Di Direct Mode, LIP Di Fava quase support only, Apple AirPinist, "Modes and Will be activated and wite Notices, Stateful with EMPCA"), SSIS Security and certificate management: SNMP-VI, SNMP-V2, SNMP-V2, SNMP-V2, PITPIHTTPS, Syslog, FTP FW Download **Nex. via balt-in 10 /1001/100080s-cTX Ethernet, Gigabit, Auto-crossover Ethernet, Authentication via 802.1X **Nex.** **Sandard: 512 MB, **Maximum: 512 MB **Sandard: 2: **Maximum: 3 **Paper [plain, EccEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepr
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media types Media handling Media handling Media weight Input capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology	TCM/PI Pod. (IPAC, Pinnt TCP)-P port 91 (Di Direct Mode, LDD Graw quives support only, Apple AirPrint, Modes, APP Pinit, Discovery, SE, Bonioux, Web Services Discovery ID Configt (IPAC Boott) DHCR, AutoR Manual), IPAC Stateless in Lincolar Card and via Broute, Stateful via Hard-Pols, SS. Security and certificate management: SNMPv1, SNMPv2, SNMPv2, HTTP/HTTPS, Syslog, FT PW Download Ves. via bulls: in 10/100/10008ase-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB, Maximum: 512 MB Standard: 2: Maximum: 3 Paper [plain, EccEFFICIENT, Illight, Peavy, bond, colored, letterhead, preprinted, prepunded, recycled, rough); envelopes; labels; Custom (Impetit), Tray 1: 762 x 127 to 21.5 9 x 355.6 mm; Tray 2. 3: 10.8 9 x 148.5 9 to 21.5 9 x 355.6 mm Supported (Impetito). Tray 1: 764 x 127 to 21.5 9 x 355.6 mm; Tray 2. 3: 10.8 9 x 148.5 9 to 21.5 9 x 355.6 mm Supported (Impetito). Tray 1: 764 x 727 mm); paperse Postcard, Double Japan Postcard Rotated: Envelope #10; Envelope Monard; Envelope #5; Envelope E1; Citis Commisses #10 x 152 to 21.6 x 356 mm; 16K (197 x 273 mm); paperse Postcard; Double Japan Postcard Rotated: Envelope #10; Envelope Monard; Envelope #5; Envelope E1; Citis Commisses #10 x 152 to 21.6 x 356 mm; Tray 1: 6 to 20.0 gm/; tray 2. o Brook #10 x 250 commisses #10 x 152 to 21.6 x 356 mm; Tray 1: 6 to 20.0 gm/; tray 2. o Brook #10 x 250 commisses #10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page *10 x 152 to 21.6 x 356 mm; page
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology Certifications	TOT/IP Port, IP-Sc Print: TDP-IP port 9100 Direct Mode, LPD frow quies support only, Apple AirFrint**, Morphia, IPP Print: Discovery, SLR Banjaur, Web Services Discovery, IP Config Jie All Boot R OHCR, AutoR, Manual), IP-6 (Stateless Linct Coal and via Router Stateful via DelPort), SSL Security and Certificate management, Management; SNMPV, SNMPV2, SNMPV2, SNMPV3, HTTP/HTTPS, Syslog, FTP FW Download Wes, vab built-in 10 f 100 (100 (100 (100 (100 (100 (100
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Media handling Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology Certifications Sustainable impact specifications Country of origin	TOTINE PAL, IPAS, Print: TOP-IP port 910.0 Direct Mode, LPD frow quave support only), Apple AirFrint**, Modria, IPP Print: Discovery, SIR Banipuz, Web Services Discovery, IP Config JiP Al Boodt, DHCR, AutoR, Manual), IPAS (Stateless Linct Coal and via Router Stateful via DHCPAS, SS, Security and Certificate management; SNAPPY, SNAPP
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Number of paper trays Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology Certifications Sustainable impact specifications	TOT/IP Port, IP-Sc Print: TDP-IP port 9100 Direct Mode, LPD frow quies support only, Apple AirFrint**, Morphia, IPP Print: Discovery, SLR Banjaur, Web Services Discovery, IP Config Jie All Boot R OHCR, AutoR, Manual), IP-6 (Stateless Linct Coal and via Router Stateful via DelPort), SSL Security and Certificate management, Management; SNMPV, SNMPV2, SNMPV2, SNMPV3, HTTP/HTTPS, Syslog, FTP FW Download Wes, vab built-in 10 f 100 (100 (100 (100 (100 (100 (100

Footnotes

- ¹ Measured using ISO/IEC 24734 and excludes first set of test documents. For more information, see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- ² Requires the HP Smart app download. For details on local printing requirements see http://www.hp.com/go/mobileprinting. Certain features/software are available in English language only, and differ between desktop and mobile applications. Subscription may be required. Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores. Fax capabilities are for sending a fax only. After 3 months, a monthly fee applies to continue advanced features with HP Smart Pro. For more information, see http://www.hpsmart.com.
- ³ Easy setup and manage Requires use of Smart Admin Dashboard for printer setup and onboarding of users.
- ⁴ HP Web Jetadmin is available for download at no additional charge at hp.com/go/webjetadmin.
- ⁵ Wireless operations are compatible with 2.4 GHz and 5.0 GHz operations only. Learn more at hp.com/go/mobileprinting. Wi-Fi is a registered trademark of Wi-Fi Alliance®. Supports both 5.0 GHz and 2.4 GHz using up to 12 non-overlapping channels vs only 3 non-overlapping channels for 2.4 GHz only. Supports 5.0 GHz band (up to 150 mbps) vs 2.4 GHz band (up to 72.2 mbps). Internet access required and must be purchased separately.
- ⁶ HP JetAdvantage Security Manager must be purchased separately. To learn more, please visit hp.com/go/securitymanager.
- Recycling: Through the HP Planet Partners program (where available), recycled plastics are used as raw material and combined with other materials to help make new Original HP cartridges and other everyday products. For details, see http://www.hp.com/recycle.

 Save up to 50% on toner (mono) Based on monthly subscription cost of HP Instant Ink monochrome toner service 1,500 page plan without purchase of additional sets of pages compared to cost per page to print ISO/IEC 24711
- Save up to 50% on toner (mono) Based on monthly subscription cost of HP Instant Ink monochrome toner service 1,500 page plan without purchase of additional sets of pages compared to cost per page to print ISO/IEC 24711 pages on most in-class, traditional A4 monochrome toner cartridge printers <€494 and MFPs priced <€672 using original standard-capacity integrated cartridges (toner and drum in one cartridge). Average CPP per country used to determine percent savings claim versus CPP for HP Instant Ink. Sale prices not considered for this study. Printers which only use XL cartridges excluded due to non-standard hardware & supplies model. Keypoint Intelligence September 2021 study commissioned by HP, based on publicly available information as of August 18, 2021. Printers selected by market share in IDC Quarterly Hardcopy Peripherals Tracker Final Historical 2021Q2. For details: www.keypointintelligence.com/HPInstantInk.
- 9 Automatic delivery and consolidated bill: Printers require direct connection to the Internet for program participation. Internet access sold separately.
- 10 Never run out: Based on plan usage, Internet connection to eligible HP printer, valid credit/debit card, email address, and delivery service in your geographic area.
- 11 Change or cancel: Change or cancel your plan at any time online. If you decide to cancel your HP Instant Ink you can go back to using HP original Standard or XL cartridges. Plan upgrades are effective immediately and the charges will be applied retrospectively or in the next billing cycle, depending on user choice. Plan downgrades and cancellations are effective after the last day of the current billing period. For full details go to hpinstantink.com/terms.

Technical specifications disclaimers

- ¹ Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- ² Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- ³ Job Storage feature requires a purchase of separate USB flash drive with a minimum of 16 GB capacity.
- ⁴ Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.
- ⁵ Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh).
- ⁶ Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device and 230V for Blue Angel.
- ⁷ For yield information on the cartridge included with your printer, see http://www.hp.com/go/toneryield. Yield values measured in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors.

















