

Part no.:

43128

# 7 Port USB 3.0 Metal Hub

7 additional USB 3.0 ports - perfect for industrial applications





### | DESCRIPTION

- Provides 7 USB 3.0 SuperSpeed ports with data rates up to 5Gbps
- Hard-wearing USB Hub Perfect for industrial applications
- Robust metal housing with high EMC protection and integrated brackets for mounting
- USB bus-powered, or can be externally powered
- 2 year warranty

The Lindy 7 Port USB 3.0 Metal Hub has been designed to provide reliable performance in demanding operational environments. This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this Hub is the ideal solution for use in industrial environments.

Backwards compatibility with USB 2.0/1.1/1.0 means the hub can simultaneously support older USB peripherals or systems that lack USB 3.0 capabilities, extending their lifetime and giving a greater return on investment. The hub also supports MTT technology which guarantees highest possible throughput speed for USB 1.1 devices.

Each port features individual short circuit protection, while the included power supply ensures secure and uninterrupted electricity supply.

## Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.



### **Specifications**

- USB Standard: USB 3.1 Gen 1 / 3.0
- Supported Bandwidth: 5 Gbps
- Chipset: 2 x VL817
- Compatibility: USB Type A equipped computers
- Power Delivery: -
- Special Features: Integrated brackets for mounting, supports Multi TT technology

#### **Connectors**

Inputs: 1 x USB Type B (Female)Outputs: 7 x USB Type A (Female)Power: DC screw connector

### **Physical Properties**

- Dimensions WxDxH: 185x75x20mm (7.28x2.95x0.79in)
- (Fixed) Cable Length: -
- · Housing Material: Metal
- Net Weight: 0.379kg (0.84lb)
- Operating Temperature: 0°C 50°C (32°F -122°F)
- Storage Temperature: -20°C 60°C (-4°F -140°F)
- Humidity: 90% RH (non-condensing)
- Power Requirements: 16VDC 3A
- · Colour: Black

## Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 260x180x70mm (10.24x7.09x2.76in)
- Gross Weight: 0.8kg (1.76lb)
- Warranty (Years): 2
- Product Compliance: CE, FCC, RoHS, REACH & California Proposition 65

### **Package Contents**

- 7 Port USB 3.0 Metal Hub
- 0.8m USB 3.0 Type A to B Cable
- Multi-Country Power Supply (EU, UK, US & AU) with screw type DC connector

## **Purchasing Information**

- No.: 43128
- EAN: 40028884321286