

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811(Contains:2,4-Dimethyl-3-cyclohexen-1-carboxaldehyde, 4-tert-Butylcyclohexyl acetate, Cinnamaldehyde, d-Limonene)

Other identifiers: VA-24-157

Unique Formula Identifier (UFI): WJV0-T07X-500W-D215

1.2 Relevant identified uses of the substance of mixture and uses advised against

Product uses: Air Freshener,For Professional use only.

Uses advised against: Use only for intended applications

1.3 Details of the supplier of the safety data sheet

Company name: Evo Group

Company address: Newland House, Unit 2 Express Way, Tuscany Park, Normanton, UK, WF6 2TZ

Contact: Evo Group

E-Mail address: info@evo-group.co.uk

Company phone: 0844 371 9490

Supplier: EVO Global Holdings Limited

Address: Units 5 & 6 Grants Drive Greenogue Business Park D24 W56C Rathcoole Dublin

Phone: 00 3531 257 2400

1.4 Emergency telephone number

Emergency phone: National Poisons Information Service (Birmingham Centre).
City Hospital.
Dudley Road B18 7QH.
0344 8952 0111
Only for healthcare professionals.

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Classification under Regulation (EC) No 1272/2008

Class and category of danger: Sensitization - Skin Category 1
Hazardous to the Aquatic Environment - Long-term Hazard Category 2
H317, May cause an allergic skin reaction.
H411, Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

2.2 Label elements

Classification under Regulation (EC) No 1272/2008

Signal word: Warning.

Hazard statements: H317, May cause an allergic skin reaction.
H411, Toxic to aquatic life with long lasting effects.

Supplemental Information: EUH208, Contains (Z)-3,4,5,6,6-Pentamethylhept-3-en-2-one, 10-Undecenal, Citral, Eugenol, Geraniol, Isocyclocitral, Linalool, Linalyl acetate, Longifolene, alpha-Pinene, beta-Pinene, omega-Pentadecalactone. May produce an allergic reaction.

Precautionary statements: P280, Wear protective gloves/eye protection/face protection.
P302/352, IF ON SKIN: Wash with plenty of soap and water.
P333/313, If skin irritation or rash occurs: Get medical advice/attention.
P501, Dispose of contents/container to approved disposal site, in accordance with local regulations.

Pictograms:



2.3 Other hazards

Other hazards: Sensitisers declared on a CLP Hazard Label: (Z)-3,4,5,6,6-Pentamethylhept-3-en-2-one, 10-Undecenal, Citral, Eugenol, Geraniol, Isocyclocitral, Linalool, Linalyl acetate, Longifolene, alpha-Pinene, beta-Pinene, omega-Pentadecalactone
Hydrocarbon Concentration %: 1.9000%

Section 3. Composition / information on ingredients

3.2 Mixtures

Contains:

Name	CAS	EC	REACH Registration No.	%	Classification for (CLP) 1272/2008	Specific Conc. Limits, M-factors and ATEs
4-tert-Butylcyclohexyl acetate	32210-23-4	250-954-9	01-2119976286-24-XXXX	1-<5%	Skin Sens. 1B;H317,-	oral: ATE = 3370 mg/kg bw
Benzyl acetate	140-11-4	205-399-7	01-2119638272-42-XXXX	1-<5%	Aquatic Chronic 3; H412,-	oral: ATE = 2490 mg/kg bw

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

d-Limonene	5989-27-5, 138-86-3, 5989-54-8	227-813-5, 205-341-0, 227-815-6	Exempt < 1 Tonne/pa or natural source	1-<5%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1- Aquatic Chronic 3; H226-H304-H315- H317-H400-H412,-	M = 1
Dihydromyrcenol	18479-58-8	242-362-4	01-2119457274-37-XXXX	1-<5%	Skin Irrit. 2-Eye Irrit. 2- STOT SE 3;H315- H319-H336,-	oral: ATE = 3020 mg/kg bw
2,4-Dimethyl-3- cyclohexen-1- carboxaldehyde	68039-49-6	268-264-1		1-<5%	Skin Irrit. 2-Skin Sens. 1B-Aquatic Chronic 2; H315-H317-H411,-	oral: ATE = 2330 mg/kg bw
Tricyclodecenyyl acetate	5413-60-5	226-501-6		1-<5%	Aquatic Chronic 1; H410,-	oral: ATE = 2750 mg/kg bw
(Z)-3,4,5,6,6- Pentamethylhept-3-en- 2-one	81786-73-4	279-822-9		1-<5%	Skin Sens. 1B-Aquatic Chronic 2;H317-H411,-	oral: ATE = 2500 mg/kg bw
Carrageenan	9000-07-1, 2593-40-5	232-524-2		1-<5%	Acute Tox. 4;H312,-	
beta-Pinene	127-91-3	204-872-5	01-2119519230-54-XXXX	0.1-<1%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1- Aquatic Chronic 1; H226-H304-H315- H317-H410,-	M = 1
alpha-Pinene	80-56-8, 7785-26-4	201-291-9	01-2120270305-62-xxxx	0.1-<1%	Flam. Liq. 3-Acute Tox. 4-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1- Aquatic Acute 1- Aquatic Chronic 1; H226-H302-H304- H315-H317-H410,-	M = 1-oral: ATE = 500 mg/kg bw
Linalyl acetate	115-95-7	204-116-4	01-2119454789-19-XXXX	0.1-<1%	Skin Irrit. 2-Skin Sens. 1B;H315-H317,-	
Linalool	78-70-6	201-134-4	01-2119474016-42-XXXX	0.1-<1%	Skin Irrit. 2-Eye Irrit. 2- Skin Sens. 1B;H315- H317-H319,-	oral: ATE = 2790 mg/kg bw
Longifolene	475-20-7	207-491-2		0.1-<1%	Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1- Aquatic Chronic 1; H304-H317-H410,-	M = 1
Citral	5392-40-5	226-394-6	01-2119462829-23-XXXX	0.1-<1%	Skin Irrit. 2-Eye Irrit. 2- Skin Sens. 1;H315- H317-H319,-	
Benzyl benzoate	120-51-4	204-402-9	01-2119976371-33-xxxx	0.1-<1%	Acute Tox. 4-Aquatic Acute 1-Aquatic Chronic 2;H302-H400- H411,-	oral: ATE = 1160 mg/kg bw
16-Hydroxy-7- hexadecenoic acid lactone	123-69-3	204-644-5		0.1-<1%	Aquatic Acute 1- Aquatic Chronic 1; H410,-	M = 10-M = 10
10-Undecenal	112-45-8	203-973-1		0.1-<1%	Skin Sens. 1B-Aquatic Chronic 3;H317-H412,-	
Cinnamaldehyde	104-55-2, 57194-69-1	203-213-9	01-2119935242-45-xxxx	0.1-<1%	Acute Tox. 4-Skin Irrit. 2-Eye Irrit. 2-Skin Sens. 1A-Aquatic Chronic 3;H312-H315- H317-H319-H412,-	dermal: ATE = 1260 mg/kg bw-oral: ATE = 2220 mg/kg bw
Isocyclocitral	1335-66-6, 1423-46-7	215-638-7		0.1-<1%	Skin Irrit. 2-Eye Irrit. 2- Skin Sens. 1B-Aquatic Chronic 3;H315-H317- H319-H412,-	oral: ATE = 3220 mg/kg bw
omega- Pentadecalactone	106-02-5	203-354-6		0.1-<1%	Skin Sens. 1B-Aquatic Chronic 2;H317-H411,-	

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

Eugenol	97-53-0	202-589-1	01-2119971802-33-xxxx	0.1-<1%	Eye Irrit. 2-Skin Sens. 1B;H317-H319,-	oral: ATE = 2500 mg/kg bw
Geraniol	106-24-1	203-377-1	01-2119552430-49-xxxx	0.1-<1%	Skin Irrit. 2-Eye Dam. 1-Skin Sens. 1;H315-H317-H318,-	oral: ATE = 3600 mg/kg bw

Substances with Community workplace exposure limits:

Name	CAS	EC	REACH Registration No.	%	Classification for (CLP) 1272/2008	Specific Conc. Limits, M-factors and ATEs
Citral	5392-40-5	226-394-6	01-2119462829-23-XXXX	0.1-<1%	Skin Irrit. 2-Eye Irrit. 2-Skin Sens. 1;H315-H317-H319,-	
Propylene glycol	57-55-6	200-338-0		5-<10%	-;-,-	
alpha-Pinene	80-56-8, 7785-26-4	201-291-9	01-2120270305-62-xxxx	0.1-<1%	Flam. Liq. 3-Acute Tox. 4-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1; H226-H302-H304-H315-H317-H410,-	M = 1-oral: ATE = 500 mg/kg bw
beta-Pinene	127-91-3	204-872-5	01-2119519230-54-XXXX	0.1-<1%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1; H226-H304-H315-H317-H410,-	M = 1
d-Limonene	5989-27-5, 138-86-3, 5989-54-8	227-813-5, 205-341-0, 227-815-6	Exempt < 1 Tonne/pa or natural source	1-<5%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 3; H226-H304-H315-H317-H400-H412,-	M = 1

Substances that are endocrine disruptors according to Regulation (EU) 2017/2100 or Regulation (EU) 2018/605, greater than 0.1%:

Not Applicable

Substances that are persistent, bioaccumulative and toxic or very persistent and very bioaccumulative, greater than 0.1%:

Not Applicable

Section 4. First-aid measures

4.1 Description of first aid measures

Inhalation:	Remove from exposure site to fresh air, keep at rest, and obtain medical attention.
Eye exposure:	Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.
Skin exposure:	IF ON SKIN: Wash with plenty of soap and water.
Ingestion:	Rinse mouth with water and obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation. Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

7.3 Specific end use(s):

Air Freshener, For Professional use only.: Use in accordance with good manufacturing and industrial hygiene practices.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits:

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

Ingredient	CAS	EC	Description	Value
Citral	5392-40-5	226-394-6	Polish NDS mgm3	27 mg/m ³
			Polish NDSC h mgm3	54 mg/m ³
Propylene glycol	57-55-6	200-338-0	UK WEL Long term ppm	474 ppm
			UK WEL Long term mgm3	150 mg/m ³
			UK WEL Short term ppm	450 ppm
			UK WEL Short term mgm3	30 mg/m ³
			Polish NDS mgm3	100 mg/m ³
alpha-Pinene	80-56-8, 7785-26-4	201-291-9	(CH)-Switzerland_KZGW-Wert 1_mg/m ³	224 mg/m ³
			(CH)-Switzerland_KZGW-Wert 2_ppm	40 ppm
			(CH)-Switzerland_MAK-Wert 1_mg/m ³	112 mg/m ³
			(CH)-Switzerland_MAK-Wert 2_ppm	20 ppm
beta-Pinene	127-91-3	204-872-5	(CH)-Switzerland_KZGW-Wert 1_mg/m ³	224 mg/m ³
			(CH)-Switzerland_KZGW-Wert 2_ppm	40 ppm
			(CH)-Switzerland_MAK-Wert 1_mg/m ³	112 mg/m ³
			(CH)-Switzerland_MAK-Wert 2_ppm	20 ppm

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

d-Limonene	5989-27-5, 138-86-3, 5989-54-8	227-813-5, 205-341-0, 227-815-6	German OEL Long term ppm	5 ppm
			German OEL Long term mgm3	28 mg/m ³
			German OEL Short term mgm3	112 mg/m ³
			(CH)-Switzerland_KZGW-Wert 1_mg/m ³	40 mg/m ³
			(CH)-Switzerland_KZGW-Wert 2_ppm	7 ppm
			(CH)-Switzerland_MAK-Wert 1_mg/m ³	80 mg/m ³
			(CH)-Switzerland_MAK-Wert 2_ppm	14 ppm

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Ensure adequate and ongoing ventilation is maintained in order to prevent build up of excessive vapour and to ensure occupational exposure limits are adhered to. If appropriate, and depending on your patterns and volumes of use, the following engineering controls may be required as additional protective measures: a) Isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under negative air pressure relative to the rest of the plant. b) Employ the use of Personal protective equipment - an approved, properly fitted respirator with organic vapour cartridges or canisters and particulate filters. c) Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures. d) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical State/Colour:	blue Solid
Odour:	Characteristic
Odour threshold:	Not determined
Melting point / freezing point:	Not determined
Boiling point or initial boiling point and boiling range:	> 100 °C
Flammability:	Not determined
Lower and upper explosion limit:	Not determined
Flash point:	> 100 °C
Auto-ignition temperature:	> 200 °C

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

Decomposition temperature:	Not relevant
pH:	Not determined Substance/mixture is non-soluble (in water)
Kinematic viscosity:	Not determined
Solubility:	Not determined
Partition coefficient: n-octanol/water (log value):	Not determined
Vapour pressure:	Not determined
Density and/or relative density:	Not determined
Relative vapour density:	Not determined
Particle characteristics:	Not determined

9.2 Other information:

Volatile Organic Compound:	26.8000%
(CH) VOC % Switzerland:	24.400%

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability:

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected.

Section 11. Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP).

Acute Toxicity:	Based on available data the classification criteria are not met.
Acute Toxicity Oral	>5000
Acute Toxicity Dermal	>5000
Acute Toxicity Inhalation	Not Available
Skin corrosion/irritation:	Based on available data the classification criteria are not met.

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

Serious eye damage/irritation: Based on available data the classification criteria are not met.
Respiratory or skin sensitisation: Sensitization - Skin Category 1
Germ cell mutagenicity: Based on available data the classification criteria are not met.
Carcinogenicity: Based on available data the classification criteria are not met.
Reproductive toxicity: Based on available data the classification criteria are not met.
STOT-single exposure: Based on available data the classification criteria are not met.
STOT-repeated exposure: Based on available data the classification criteria are not met.
Aspiration hazard: Based on available data the classification criteria are not met.

Information about hazardous ingredients in the mixture

Ingredient	CAS	EC	LD50/ATE Oral	LD50/ATE Dermal	LC50/ATE Inhalation	LC50 Route
Carrageenan	9000-07-1, 2593-40-5	232-524-2	Not available	1100	Not available	Not available

Refer to Sections 2 and 3 for additional information.

11.2 Information on other hazards

Not Applicable

Section 12. Ecological information

12.1 Toxicity:

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability: Not available

12.3 Bioaccumulative potential: Not available

12.4 Mobility in soil: Not available

12.5 Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6 Endocrine disrupting properties: Not Applicable

12.6 Other adverse effects: Not available

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

	14.1 UN number:	14.2 UN Proper Shipping Name:	14.3 Transport hazard class (es):	Sub Risk:	14.4 Packing Group:
--	------------------------	--------------------------------------	--	------------------	----------------------------

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

UN Model Regulations	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (16-Hydroxy-7-hexadecenoic acid lactone, Tricyclodecenyl acetate)	9	-	III
IMDG	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (16-Hydroxy-7-hexadecenoic acid lactone, Tricyclodecenyl acetate) MARINE POLLUTANT	9	-	III
ADR,RID,ADN	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (16-Hydroxy-7-hexadecenoic acid lactone, Tricyclodecenyl acetate)	9	-	III
ICAO TI	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (16-Hydroxy-7-hexadecenoic acid lactone, Tricyclodecenyl acetate)	9	-	III

14.5 Environmental hazards: This is classified as an environmentally hazardous substance under the UN Model Regulations. This is classified as a Marine Pollutant under the IMDG Code.

14.6 Special precautions for user: None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SDS Reference No.: SD-000119S

We confirm that this product does not contain nanoforms or nanoparticles, based on verification from our supply chain.

HSNO Approval Number: New Zealand
 HSNO Approval Number: HSR002574: Food Additives and Fragrance Materials (Combustible) Group Standard 2020

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

Section 16. Other information

Concentration % Limits: SS 1=41.67% EH C2=41.88% EH C3=4.16%

Total Fractional Values: SS 1=2.40 EH C2=2.39 EH C3=24.05

Reference: SD-000119S

Key to revisions:

Not applicable

Key to abbreviations:

Abbreviation	Meaning
--------------	---------

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

Acute Tox. 4	Acute Toxicity - Dermal Category 4
Acute Tox. 4	Acute Toxicity - Oral Category 4
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Asp. Tox 1	Aspiration Hazard Category 1
Eye Dam. 1	Eye Damage / Irritation Category 1
Eye Irrit. 2	Eye Damage / Irritation Category 2
Flam. Liq. 3	Flammable Liquid, Hazard Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
P210	Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304/340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: 2WORK SOLID AIRCARE REFILL - LINEN BREEZE 2W10811

Version: 1

P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P331	Do not induce vomiting.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391	Collect spillage.
P403/233/235	Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
STOT SE 3	Specific Target Organ Toxicity (Single Exposure) Category 3
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Sens. 1	Sensitization - Skin Category 1
Skin Sens. 1A	Sensitization - Skin Category 1A
Skin Sens. 1B	Sensitization - Skin Category 1B

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.