

**Trade name:** edding refill ink whiteboard marker BTK25 (black) contained in: edding 360, edding 363

**Current version :** 6.1.1, issued: 27.10.2022

**Replaced version:** 6.1.0, issued: 09.05.2016

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**edding refill ink whiteboard marker BTK25 (black) contained in: edding 360, edding 363**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Refill ink

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

**Information provided by / telephone**

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Eye Irrit. 2; H319

Flam. Liq. 2; H225

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**



GHS02



GHS07

**Signal word**

Danger

**Hazard statement(s)**

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

**Trade name:** edding refill ink whiteboard marker BTK25 (black) contained in: edding 360, edding 363

**Current version :** 6.1.1, issued: 27.10.2022

**Replaced version:** 6.1.0, issued: 09.05.2016

**Region:** GB

#### Precautionary statement(s)

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370+P378	In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

#### Labelling information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

### 2.3 Other hazards

No data available.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable. The product is not a substance.

### 3.2 Mixtures

#### Chemical characterization

Alcoholic solution of organic pigments, binding agents and additives.

#### Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	ethanol		pls. refer to footnote (1)
	64-17-5 200-578-6 603-002-00-5 -	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 50.00 - < 100.00 wt%
2	1-methoxy-2-propanol		
	107-98-2 203-539-1 603-064-00-3 -	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10.00 - < 25.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Eye Irrit. 2; H319: C >= 50%	-	-

### 3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

#### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

#### After skin contact

Wash off immediately with soap and water.

**Trade name:** edding refill ink whiteboard marker BTK25 (black) contained in: edding 360, edding 363

**Current version :** 6.1.1, issued: 27.10.2022

**Replaced version:** 6.1.0, issued: 09.05.2016

**Region:** GB

**After eye contact**

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

**After ingestion**

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

**4.2 Most important symptoms and effects, both acute and delayed**

No data available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No data available.

## SECTION 5: Firefighting measures

**5.1 Extinguishing media**

**Suitable extinguishing media**

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

**Unsuitable extinguishing media**

High power water jet

**5.2 Special hazards arising from the substance or mixture**

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO)

**5.3 Advice for firefighters**

Use self-contained breathing apparatus. Wear protective clothing.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

**For emergency responders**

No data available. Personal protective equipment (PPE) - see Section 8.

**6.2 Environmental precautions**

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

**6.3 Methods and material for containment and cleaning up**

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

**6.4 Reference to other sections**

No data available.

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling**

**Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

**General protective and hygiene measures**

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

**Advice on protection against fire and explosion**

**Trade name:** edding refill ink whiteboard marker BTK25 (black) contained in: edding 360, edding 363

**Current version :** 6.1.1, issued: 27.10.2022

**Replaced version:** 6.1.0, issued: 09.05.2016

**Region:** GB

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

## 7.2 Conditions for safe storage, including any incompatibilities

### Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

### Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

### Incompatible products

None known

## 7.3 Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
Ethanol			
	WEL long-term (8-hr TWA reference period)	1920	mg/m <sup>3</sup> 1000 ppm
2	1-methoxy-2-propanol	107-98-2	203-539-1
<b>2000/39/EC</b>			
1-Methoxypropanol-2			
	WEL short-term (15 min reference period)	568	mg/m <sup>3</sup> 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup> 100 ppm
	Skin resorption / sensibilisation	Skin	
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
1-Methoxypropan-2-ol			
	WEL short-term (15 min reference period)	560	mg/m <sup>3</sup> 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup> 100 ppm
	Comments	Sk	

### 8.2 Exposure controls

#### Appropriate engineering controls

No data available.

#### Personal protective equipment

##### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

##### Eye / face protection

Safety glasses with side protection shield (EN 166)

##### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

##### Other

Normal chemical work clothing.

##### Environmental exposure controls

No data available.

**Trade name:** edding refill ink whiteboard marker BTK25 (black) contained in: edding 360, edding 363

**Current version :** 6.1.1, issued: 27.10.2022

**Replaced version:** 6.1.0, issued: 09.05.2016

**Region:** GB

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>	
liquid	
<b>Form</b>	
liquid	
<b>Colour</b>	
black	
<b>Odour</b>	
characteristic	
<b>pH value</b>	
not determined	
<b>Boiling point / boiling range</b>	
Value	78 °C
<b>Melting point/freezing point</b>	
No data available	
<b>Decomposition temperature</b>	
No data available	
<b>Flash point</b>	
Value	13 °C
<b>Ignition temperature</b>	
Value	287 °C
<b>Auto-ignition temperature</b>	
Comments	Product is not selfigniting.
<b>Explosive properties</b>	
The product is not explosive. Formation of explosive/highly flammable air-vapour mixtures is possible during/after use.	
<b>Flammability</b>	
No data available	
<b>Lower explosion limit</b>	
Value	1.7 % vol
<b>Upper explosion limit</b>	
Value	15.0 % vol
<b>Vapour pressure</b>	
Value	59 hPa
Reference temperature	20 °C
<b>Relative vapour density</b>	
No data available	
<b>Relative density</b>	
No data available	
<b>Density</b>	
No data available	
<b>Solubility in water</b>	
Comments	partially miscible
<b>Solubility</b>	
No data available	

**Trade name:** edding refill ink whiteboard marker BTK25 (black) contained in: edding 360, edding 363

**Current version :** 6.1.1, issued: 27.10.2022

**Replaced version:** 6.1.0, issued: 09.05.2016

**Region:** GB

**Partition coefficient n-octanol/water (log value)**

No data available

**Kinematic viscosity**

No data available

**Solvent content**

Value	79.1	%
-------	------	---

**Particle characteristics**

No data available

**9.2 Other information**

**Other information**

No data available.

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No data available.

**10.2 Chemical stability**

Stable under recommended storage and handling conditions (See section 7).

**10.3 Possibility of hazardous reactions**

No data available.

**10.4 Conditions to avoid**

None known

**10.5 Incompatible materials**

None known.

**10.6 Hazardous decomposition products**

No hazardous decomposition products known.

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute oral toxicity**

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		5660	mg/kg bodyweight
Species	rat		
Source	Manufacturer		

**Acute dermal toxicity**

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		9999.99	mg/kg bodyweight
Species	rabbit		
Source	Manufacturer		

**Acute inhalational toxicity**

No data available

**Skin corrosion/irritation**

No data available

**Serious eye damage/irritation**

No data available

**Respiratory or skin sensitisation**

No data available

**Trade name:** edding refill ink whiteboard marker BTK25 (black) contained in: edding 360, edding 363

**Current version :** 6.1.1, issued: 27.10.2022

**Replaced version:** 6.1.0, issued: 09.05.2016

**Region:** GB

<b>Germ cell mutagenicity</b>
No data available

<b>Reproduction toxicity</b>
No data available

<b>Carcinogenicity</b>
No data available

<b>STOT - single exposure</b>
No data available

<b>STOT - repeated exposure</b>
No data available

<b>Aspiration hazard</b>
No data available

<b>Delayed and immediate effects as well as chronic effects from short and long-term exposure</b>
Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.

## 11.2 Information on other hazards

### Endocrine disrupting properties

No data available.

### Other information

No data available.

## SECTION 12: Ecological information

### 12.1 Toxicity

<b>Toxicity to fish (acute)</b>
No data available

<b>Toxicity to fish (chronic)</b>
No data available

<b>Toxicity to Daphnia (acute)</b>
No data available

<b>Toxicity to Daphnia (chronic)</b>
No data available

<b>Toxicity to algae (acute)</b>
No data available

<b>Toxicity to algae (chronic)</b>
No data available

<b>Bacteria toxicity</b>
No data available

### 12.2 Persistence and degradability

No data available.

### 12.3 Bioaccumulative potential

No data available.

### 12.4 Mobility in soil

No data available.

### 12.5 Results of PBT and vPvB assessment

No data available.

### 12.6 Endocrine disrupting properties

No data available.

**Trade name:** edding refill ink whiteboard marker BTK25 (black) contained in: edding 360, edding 363

**Current version :** 6.1.1, issued: 27.10.2022

**Replaced version:** 6.1.0, issued: 09.05.2016

**Region:** GB

### 12.7 Other adverse effects

No data available.

### 12.8 Other information

#### Other information

Do not discharge product unmonitored into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

#### Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

## SECTION 14: Transport information

### 14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3

### 14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	PAINT
EmS	F-E, S-E
Label	3

### 14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	Paint
Label	3

### 14.4 Other information

No data available.

### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

### 14.6 Special precautions for user

No data available.

### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Trade name:** edding refill ink whiteboard marker BTK25 (black) contained in: edding 360, edding 363

**Current version :** 6.1.1, issued: 27.10.2022

**Replaced version:** 6.1.0, issued: 09.05.2016

**Region:** GB

### EU regulations

#### **Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

#### **REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

#### **Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

#### **Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is subject to Part I of Annex I, risk category:	P5b
--	-----

### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

### SECTION 16: Other information

#### **Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

#### **Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

#### **Creation of the safety data sheet**

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

#### **Alterations/supplements:**

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 17431

**Trade name:** edding refill ink whiteboard marker BTK25 black (1129001)

**Current version :** 1.3.0, issued: 18.12.2024

**Replaced version:** 1.1.1, issued: 27.10.2022

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**edding refill ink whiteboard marker BTK25 black (1129001)**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Refill ink

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

edding International GmbH  
Bookkoppel 7  
D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

**Information provided by / telephone**

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

**Details of the importer**

**Address**

edding UK Ltd.  
edding House, Merlin Centre  
AL4 0JY St Albans  
Hertfordshire  
United Kingdom

Telephone no. +44 (0)1727 84 66 88

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Eye Irrit. 2; H319

Flam. Liq. 2; H225

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**



**Trade name:** edding refill ink whiteboard marker BTK25 black (1129001)

**Current version :** 1.3.0, issued: 18.12.2024

**Replaced version:** 1.1.1, issued: 27.10.2022

**Region:** GB

GHS02	GHS07
<b>Signal word</b>	
Danger	
<b>Hazard statement(s)</b>	
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
<b>Precautionary statement(s)</b>	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370+P378	In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

### 2.3 Other hazards

No data available.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable. The product is not a substance.

### 3.2 Mixtures

#### Chemical characterization

Alcoholic solution of organic pigments, binding agents and additives.

#### Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration
			%
1	<b>ethanol</b>		<b>pls. refer to footnote (1)</b>
	64-17-5 200-578-6 603-002-00-5 -	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 50.00 - < 100.00 wt%
2	<b>1-methoxy-2-propanol</b>		
	107-98-2 203-539-1 603-064-00-3 -	Flam. Liq. 3; H226 STOT SE 3; H336	10.00 - 19.00 wt%

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Eye Irrit. 2; H319: C >= 50%	-	-

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

#### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

#### After skin contact

Wash off immediately with soap and water.

#### After eye contact

**Trade name:** edding refill ink whiteboard marker BTK25 black (1129001)**Current version :** 1.3.0, issued: 18.12.2024**Replaced version:** 1.1.1, issued: 27.10.2022**Region:** GB

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

**After ingestion**

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

**4.2 Most important symptoms and effects, both acute and delayed**

No data available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

**Unsuitable extinguishing media**

High power water jet

**5.2 Special hazards arising from the substance or mixture**

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO)

**5.3 Advice for firefighters**

Use self-contained breathing apparatus. Wear protective clothing.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

**For emergency responders**

No data available. Personal protective equipment (PPE) - see Section 8.

**6.2 Environmental precautions**

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

**6.3 Methods and material for containment and cleaning up**

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

**6.4 Reference to other sections**

No data available.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling****Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

**General protective and hygiene measures**

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

**Advice on protection against fire and explosion**

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

**Trade name:** edding refill ink whiteboard marker BTK25 black (1129001)

**Current version :** 1.3.0, issued: 18.12.2024

**Replaced version:** 1.1.1, issued: 27.10.2022

**Region:** GB

## 7.2 Conditions for safe storage, including any incompatibilities

### Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

### Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

### Incompatible products

None known

## 7.3 Specific end use(s)

No data available.

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

### Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
Ethanol			
	WEL long-term (8-hr TWA reference period)	1920 mg/m <sup>3</sup>	1000 ppm
2	1-methoxy-2-propanol	107-98-2	203-539-1
<b>2000/39/EC</b>			
1-Methoxypropanol-2			
	WEL short-term (15 min reference period)	568 mg/m <sup>3</sup>	150 ppm
	WEL long-term (8-hr TWA reference period)	375 mg/m <sup>3</sup>	100 ppm
	Skin resorption / sensibilisation	Skin	
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
1-Methoxypropan-2-ol			
	WEL short-term (15 min reference period)	560 mg/m <sup>3</sup>	150 ppm
	WEL long-term (8-hr TWA reference period)	375 mg/m <sup>3</sup>	100 ppm
	Comments	Sk	

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

### Personal protective equipment

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

#### Eye / face protection

Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

#### Other

Normal chemical work clothing.

#### Environmental exposure controls

No data available.

**Trade name:** edding refill ink whiteboard marker BTK25 black (1129001)

**Current version :** 1.3.0, issued: 18.12.2024

**Replaced version:** 1.1.1, issued: 27.10.2022

**Region:** GB

**SECTION 9: Physical and chemical properties**
**9.1 Information on basic physical and chemical properties**

<b>State of aggregation</b>		
liquid		
<b>Form</b>		
liquid		
<b>Colour</b>		
black		
<b>Odour</b>		
characteristic		
<b>pH value</b>		
not determined		
<b>Boiling point / boiling range</b>		
Value	78	°C
<b>Melting point/freezing point</b>		
No data available		
<b>Decomposition temperature</b>		
No data available		
<b>Flash point</b>		
Value	13	°C
<b>Ignition temperature</b>		
Value	287	°C
<b>Auto-ignition temperature</b>		
Comments	Product is not selfigniting.	
<b>Explosive properties</b>		
The product is not explosive. Formation of explosive/highly flammable air-vapour mixtures is possible during/after use.		
<b>Flammability</b>		
No data available		
<b>Lower explosion limit</b>		
Value	1.7	% vol
<b>Upper explosion limit</b>		
Value	15.0	% vol
<b>Vapour pressure</b>		
Value	59	hPa
Reference temperature	20	°C
<b>Relative vapour density</b>		
No data available		
<b>Relative density</b>		
No data available		
<b>Density</b>		
No data available		
<b>Solubility in water</b>		
Comments	partially miscible	
<b>Solubility</b>		
No data available		
<b>Partition coefficient n-octanol/water (log value)</b>		

**Trade name:** edding refill ink whiteboard marker BTK25 black (1129001)

**Current version :** 1.3.0, issued: 18.12.2024

**Replaced version:** 1.1.1, issued: 27.10.2022

**Region:** GB

No data available
-------------------

**Kinematic viscosity**

No data available
-------------------

**Solvent content**

Value	79.1	%
-------	------	---

**Particle characteristics**

No data available
-------------------

**9.2 Other information**
**Other information**

No data available.
--------------------

**SECTION 10: Stability and reactivity**
**10.1 Reactivity**

No data available.

**10.2 Chemical stability**

Stable under recommended storage and handling conditions (See section 7).

**10.3 Possibility of hazardous reactions**

No data available.

**10.4 Conditions to avoid**

None known

**10.5 Incompatible materials**

None known.

**10.6 Hazardous decomposition products**

No hazardous decomposition products known.

**SECTION 11: Toxicological information**
**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

<b>Acute oral toxicity</b>			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		5660	mg/kg bodyweight
Species	rat		
Source	manufacturer		

<b>Acute dermal toxicity</b>			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		9999.99	mg/kg bodyweight
Species	rabbit		
Source	manufacturer		

**Acute inhalational toxicity**

No data available
-------------------

**Skin corrosion/irritation**

No data available
-------------------

**Serious eye damage/irritation**

No data available
-------------------

**Respiratory or skin sensitisation**

No data available
-------------------

**Germ cell mutagenicity**

**Trade name:** edding refill ink whiteboard marker BTK25 black (1129001)

**Current version :** 1.3.0, issued: 18.12.2024

**Replaced version:** 1.1.1, issued: 27.10.2022

**Region:** GB

No data available

**Reproduction toxicity**

No data available

**Carcinogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration hazard**

No data available

**Endocrine disrupting properties**

No data available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness.  
Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.

**11.2 Information on other hazards**

**Other information**

No data available.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Toxicity to fish (acute)**

No data available

**Toxicity to fish (chronic)**

No data available

**Toxicity to Daphnia (acute)**

No data available

**Toxicity to Daphnia (chronic)**

No data available

**Toxicity to algae (acute)**

No data available

**Toxicity to algae (chronic)**

No data available

**Bacteria toxicity**

No data available

**12.2 Persistence and degradability**

No data available.

**12.3 Bioaccumulative potential**

No data available.

**12.4 Mobility in soil**

No data available.

**12.5 Results of PBT and vPvB assessment**

No data available.

**12.6 Endocrine disrupting properties**

No data available.

**Trade name:** edding refill ink whiteboard marker BTK25 black (1129001)

**Current version :** 1.3.0, issued: 18.12.2024

**Replaced version:** 1.1.1, issued: 27.10.2022

**Region:** GB

**12.7 Other adverse effects**

No data available.

**12.8 Other information**
**Other information**

Do not discharge product unmonitored into the environment.

**SECTION 13: Disposal considerations**
**13.1 Waste treatment methods**
**Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

**Packaging**

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

**SECTION 14: Transport information**
**14.1 UN number or ID number**

<b>ADR/RID/ADN</b>	UN1263
<b>IMDG</b>	UN1263
<b>ICAO-TI / IATA</b>	UN1263

**14.2 UN proper shipping name**

<b>ADR/RID/ADN</b>	PAINT
<b>IMDG</b>	PAINT
<b>ICAO-TI / IATA</b>	Paint

**14.3 Transport hazard class(es)**

<b>ADR/RID/ADN - Class</b>	3
Label	3
Classification code	F1
Tunnel restriction code	D/E
Hazard identification no.	33
Special Provision 640	640D
<b>IMDG - Class</b>	3
Label	3
<b>ICAO-TI / IATA - Class</b>	3
Label	3

**14.4 Packing group**

<b>ADR/RID/ADN</b>	II
<b>IMDG</b>	II
<b>ICAO-TI / IATA</b>	II

**14.5 Environmental hazards**

EmS	F-E, S-E
-----	----------

**14.6 Special precautions for user**

No data available.

**14.7 Maritime transport in bulk according to IMO instruments**

Not relevant

**SECTION 15: Regulatory information**
**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Trade name:** edding refill ink whiteboard marker BTK25 black (1129001)

**Current version :** 1.3.0, issued: 18.12.2024

**Replaced version:** 1.1.1, issued: 27.10.2022

**Region:** GB

### EU regulations

**Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

**REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

**Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is subject to Part I of Annex I, risk category: P5b

### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

### SECTION 16: Other information

**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

**Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.

**Creation of the safety data sheet**

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 679948