

Part no.:
43315

5m USB Type C to HDMI 4K60 Adapter Cable with HDR

Creates reliable 4K connections between a USB Type C equipped computer and an HDMI display at longer distances



| DESCRIPTION

- Creates a reliable 4K connection between a USB Type C equipped computer and an HDMI display at longer distances
- Supports HDMI resolutions up to 4K 4096x2160@60Hz
- High Dynamic Range support provides deeper blacks, brighter whites and a wider colour gamut
- Requires DisplayPort Alternate Mode support by the USB Port/Bus
- 2 year warranty

Adapter cables are cables which feature two different connections and allow users to connect two devices which feature differing connection standards.

The Lindy USB Type C to HDMI 4K60 Adapter Cable with HDR allows users to easily add external video capabilities to a computer featuring the USB Type C port with additional support for DisplayPort Alternate Mode. The HDMI connector of the adapter cable can be directly connected to the HDMI display with the 5m cable allowing for additional flexibility when positioning the HDMI display - perfect for a simple and adaptable installation. The cable combines a sleek yet functional design with superior performance to provide a reliable 4K connection over distances not possible with standard cables. An active chipset, housed neatly in the centre of the cable, allows active cables to amplify HDMI signals effectively creating much longer HDMI transmissions without the need for additional repeaters or extenders.

With support for resolutions up to 4096x2160@60Hz and with additional support for High Dynamic Range, 4K content can be viewed with crystal clear clarity, enhanced contrast and more lifelike colour. These cables are great for creating eye-catching retail displays, innovative working environments or immersive video playback in sports bars and home cinema installations. Support for uncompressed multi-channel audio allows for an impressive three-dimensional surround sound performance to compliment detailed, clear video.

This cable is powered by the USB Bus, so no external power supply is needed and with 'Plug and Play' installation, this converter cable can be installed into an AV system with minimum difficulty, ideal for both professional and first time users.

Connectors

- Connector A: USB Type C Male
- Connector B: HDMI Type A Male
- Housing Material: Type C: PVC, HDMI: ABS
- Connector Plating: Gold plating
- Pin Construction: Phosphor Bronze
- Pin Plating: Gold plating
- Dimensions (approx.) WxDxH:
 - A: 12.6x24x6.6mm (0.5x0.94x0.26in)
 - B: 22x45.1x12mm (0.87x1.77x0.47in)
 - Repeater: 20.5x57x12mm (0.81x2.24x0.47in)

Cable construction

- Length: 5m (16.40ft)
- Standard: HDMI 2.0
- Colour: Black
- Type: Round
- Jacket Diameter: 5.0mm (0.2in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 32AWG
- Shielding: AL/MG Braid 85%

Specifications

- Chipset: MCDP6 + ITE6563
- Supported Bandwidth: 18Gbps

- Power Delivery: -
- Maximum Resolution: 4096x2160@60Hz 4:4:4 10bit
- Nominal Attenuation: 0.1MHz-6MHz<12DB
- Minimum Bend Radius: 47mm (1.85in)
- Operating Temperature: 0°C - 35°C (32°F - 95°F)
- Storage Temperature: 0°C - 45°C (32°F - 113°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 2
- Product Compliance: CE, FCC, RoHS, REACH & UL, California Proposition 65

Purchasing Information

- No.: 43315
- EAN: 4002888433150

This product is also available in other lengths:

- 43315 - 5m (16.40ft)
- 43316 - 7.5m (24.61ft)
- 43317 - 10m (32.81ft)